

2021 - Effective December 1, 2020 - Half/Pack® Commercial Featuring Odyssey™ Controls - Sales Order Form**Base Units Half/Pack® Commercial Featuring Odyssey™ Controls**

<input type="checkbox"/>	20 cubic yard
<input type="checkbox"/>	23 cubic yard
<input type="checkbox"/>	28 cubic yard
<input type="checkbox"/>	32 cubic yard
<input type="checkbox"/>	Add Sumps to Body
<input type="checkbox"/>	Service Hoist Kit - 187" Wheelbase 5 Axle Units WILL NOT accept the service hoist option*
<input type="checkbox"/>	Service Hoist Lite (Quick Disconnect and Cylinders Only, No Pump or Reservoir)

*5 Axle 187" Wheelbase - Hendrickson Auxiliary Axles Only with 275/R70/22.5 or smaller tires.

Hopper Size

CHASSIS MUST CONFORM WITH HEIL'S MOST CURRENT CHASSIS SPECIFICATIONS AT WWW.HEIL.COM

Mounting Options

<input type="checkbox"/>	Full Factory Mount for Service Hoist or Serviceable Eject - Includes Body Props and Rear Pivot
<input type="checkbox"/>	Mount at Dealer Destination

Power Take Off / Pump Options

<input type="checkbox"/>	PTO Mounted Load Sense Piston pump - Includes PTO
--------------------------	---

Commercial Gripper

<input type="checkbox"/>	Commercial Gripper attachment to the fork cross shaft to service 32-96 gallon residential containers (Commercial Grabbers add 6.5" of overall height when arms are fully raised and forks fully tucked). *By selection this option you are confirming that understand the unit will be over 13' 6" when the arms are fully raised and the forks are fully tucked* This item requires form SF0748A - Over Height Acknowledgment letter be signed and turned at the time your order is placed.
--------------------------	---

Adjustable Fork's Options

<input type="checkbox"/>	Hydraulically Adjustable Side Pocket Forks in lieu of standard Fork Cross Shaft *Will not work in conjunction with Curotto Commercial Gripper*
<input type="checkbox"/>	Hydraulically Adjustable Bottom Pocket Forks in lieu of standard Fork Cross Shaft *Will not work in conjunction with Curotto Can or Curotto Commercial Gripper attachments* *By selection this option you are confirming that understand the unit will be over 13' 6" when the arms are fully raised and the forks are fully tucked* This item requires form SF0748A - Over Height Acknowledgment letter be signed and turned at the time your order is placed.

Control Options

<input type="checkbox"/>	Left Hand Dual Axis Joystick - Electric Controlled
<input type="checkbox"/>	Left Hand 2 Lever In-Cab Electrical Controls in lieu of Joystick
<input type="checkbox"/>	StreetSide mounted Outside 4 Button Electric Push Button Controls for Arms, Forks, and Packer circuits (Throttle Advance Not Included)
<input type="checkbox"/>	StreetSide mounted Outside Dual Lever controls and 4 Button Electric Push Button Controls for Pump Enable, Arms, Forks, and Packer circuits. <u>Includes Throttle advance.</u>
<input type="checkbox"/>	Upgrade to 12" In Cab Display in lieu of 7" Std (Non- 3rd Eye Camera Units Only) - See 3rd Eye below for 12" Display with camera options
<input type="checkbox"/>	Heil's Autonomous Lift Option [H.A.L.O.]

Lighting and Electrical Accessories

<input type="checkbox"/>	Single LED Windscreen Mounted Container Light
<input type="checkbox"/>	Multi-Function Lights
<input type="checkbox"/>	Body Side Backing Assist Lights - LED
<input type="checkbox"/>	Dual Oval Flat LED Strobes Mounted Mid-T/G - in-cab switch, pump on, and reverse activated
<input type="checkbox"/>	Dual Cab Guard Mounted Flood Lights
<input type="checkbox"/>	Preco™ Back Up Alarm
<input type="checkbox"/>	Dual LED Cab Mounted Oval Strobe Lights
<input type="checkbox"/>	Whelen Strobe Lights Kit
<input type="checkbox"/>	Cab Shield Mounted LED Light Facing rearward toward hopper opening

AWTI™ Radar Systems

<input type="checkbox"/>	AWTI™ Radar System used in conjunction with 3rd Eye Cameras - Must Select Camera Kit From 3rd Eye Camera Options
--------------------------	---

Camera Systems

All camera systems are mounted with protective camera brackets and twin tailgate flood lights.

CAMERA MONITOR LOCATION WILL BE CAB ROOF MOUNTED

Swivel monitor bracket will be provided for dual drive chassis

3rd Eye® Camera Systems & 3rd Eye Digital

Note: Camera systems will accommodate a maximum of 5 cameras.

Not including driver and forward facing cameras included in 3rd Eye® Digital system

<input type="checkbox"/>	Base 3rd Eye® Single Camera System with 7" Monitor and Single Camera Mounted on Tailgate
<input type="checkbox"/>	Upgraded base 3rd Eye® Single Camera System with 12" Monitor and Single Camera Mounted on Tailgate
<input type="checkbox"/>	Add on 3rd Eye® Camera (LH Cab) - Camera System Price Adder (Only available if base camera is selected)
<input type="checkbox"/>	Add on 3rd Eye® Camera (RH Cab) - Camera System Price Adder (Only available if base camera is selected)
<input type="checkbox"/>	Add on 3rd Eye® Camera (LH Alley) - Camera System Price Adder (Only available if base camera is selected)
<input type="checkbox"/>	Add on 3rd Eye® Camera (RH Alley) - Camera System Price Adder (Only available if base camera is selected)
<input type="checkbox"/>	Add on 3rd Eye® Camera (Hopper) - Camera System Price Adder (Only available if base camera is selected)

3rd Eye® Digital System: Includes (Driver and Forward Facing Camera (Window Unit), and Gateway - (In-Cab Monitor Not Included)

***Digital monitoring service not included and must be purchased and activated through**

2021 - Effective December 1, 2020 - Half/Pack® Commercial Featuring Odyssey™ Controls - Sales Order Form**Load Cell Scale Systems**☐ Heil Optimum Payload System (HOPS) using Air-Weigh Axle Scales☐ Air-Weigh™ Axle Scale System without Interlock**Auxiliary Axles Options***** NOTE: All axles MUST BE installed with tires so chassis can be re-certified to new GAWR and GVWR ratings****Watson & Chalin™ Options**☐ Watson & Chalin™ Self Steering Pusher Axle: 13,500 pound capacity, hub piloted or 20" spoke wheel hubs, automatic slack adjusters, type 16 air chambers, steering stabilizer kit and reverse lift kit -☐ Watson & Chalin™ Self Steering Tag Axle: 13,500 pound capacity, hub piloted or 20" spoke wheel hubs, automatic slack adjusters, type 16 air chambers, steering stabilizer kit and reverse lift kit, includes Tag Axle Spill Shield☐ Watson & Chalin™ Rigid Pusher Axle: 25,000 pound capacity, hub piloted or 20" spoke wheel hubs, 30/30 brake chambers, automatic slack adjusters, 1,300 cubic inch air tank and regulator kit☐ Watson & Chalin™ Rigid Tag Axle: 25,000 pound capacity, hub piloted or 20" spoke wheel hubs, 30/30 brake chambers, automatic slack adjusters, 1,300 cubic inch air tank and regulator kit, includes Tag Axle Spill Shield**Hendrickson™ Options**☐ Hendrickson™ Pusher Axle-13,500 pound capacity, Non-Steerable☐ Hendrickson™ Pusher Axle-13,500 pound capacity, Steerable☐ Hendrickson™ Tag Axle-13,500 pound capacity, Steerable, includes Tag Axle Spill Shield☐ Hendrickson™ Tag Axle-13,500 pound capacity, Non-Steerable, includes Tag Axle Spill Shield☐ Hendrickson™ Steerable Pusher Axle: 20,000 pound capacity☐ Hendrickson™ Steerable Tag Axle: 20,000 pound capacity, includes Tag Axle Spill Shield*** Note: All auxiliary applications must be approved by Heil prior to order acceptance****Auxiliary Axle Tire Options**☐ 255/70R-22.5 - Qty(2) load range H, 5,510 pound single max load at 120 psi with Steel Wheels☐ 275/70R-22.5 - Qty(2) load range H, 7,000 pound single max load at 120 psi with Steel Wheels☐ Upgrade to Polished Aluminum Wheels (Set of Two)**Body Options**☐ Articulating FEL Arms - Accommodate Econic SD Chassis - Stowed Height 13'6"☐ Sliding Top Door - Aluminum - May not be compatible with roof mounted CNG system☐ Tailgate Mounted **Aluminum** Roof Access Ladder (Only one selection allowed) **Not Available with CNrG Tailgate option**☐ Tailgate Mounted Roof Access Ladder **Steel** (Only one selection allowed) ***Not available with CNrG Tailgate Option***☐ CNrG Tailgate Mounted Aluminum Roof Access Ladder (only one selection allowed) *** Not Available with STD Tailgate***☐ Curbside Mounted Roof Access Ladder (Only one selection allowed) ***Not Available on 23yd body with Top Door***☐ Hopper Floor Liner (3/16" - AR400)☐ Hopper Floor Liner (1/4" - AR400)☐ Body Floor Liner (3/16" - AR400)☐ Body Side Wall Liners (3/16" - AR400)☐ Drain Plug for 3" hopper drain☐ Packer Mounted Retainer Teeth☐ Body Roof Retainer Teeth - 2 Rows at the front of the body - Minimizes Spring Back In Cardboard and Recycling Applications☐ Packer Follower - Reduces Garbage/Recycle Behind the Packer ***Includes Inverted Style cab protector** Other cab protectors not compatible with this option.☐ High Pressure Filter Monitor☐ 60 Gallon Washout Tank - side mounted - **Not available with pusher axle**☐ 60 Gallon Washout Tank - rear mounted - **Not available with tag axle**☐ Second 20 lb. Fire Extinguisher (Will be mounted to Curb side Hopper, if unable will be mounted under body)☐ Tool Box Bumper Mount - Steel 18"x18"x24"☐ Tool Box Bumper Mount - Aluminum 18"x18"x24"☐ Tool Box Bumper Mount - Poly - 18"x18"x24"☐ Extendable Broom Kit - Mounted Curbside of Body **(Not Available on 20/23 Yd)**☐ Extendable Broom Kit - Mounted Under Body☐ Street Side of Body Mounted Shovel Bracket Kit☐ Cab Protector Extension Raise - Manual Jack - Will Receive Steel Cab Shield in Lieu of Aluminum☐ Hydraulic Raise Cab Protector Kit - Cab Shield Fully Rotates into the Hopper - Will Receive Steel Cab Shield in Lieu of Aluminum☐ Aluminum Cab Protector☐ Aluminum Cab Protector Extension For Autocar Chassis☐ Rear Caution Decal☐ Wheel Chock Kit - Dual **(Mounted Under Body)**☐ Wheel Chock Kit - Dual **(Mounted on Curbside Body)**☐ Cable Fall Protection Kit☐ D-Ring Fall Protection☐ Hydraulic Oil Tank Quick Disconnect Kit - For use with filter buggy☐ Butterfly Style Quick Disconnects In Lieu of Service Loop Plumbing☐ Spill Kit included mounting brackets - **(Mounted on Front Head)**☐ Spill Kit **(In Toolbox) *Requires additional purchase of a tool box***☐ Hydraulic Oil Tank Heater - 500 watts☐ Bolt On Fender Extension Kit - Keeps Body Clean of Road Spray☐ California Back Up Alarm☐ Infinity Series Packer/Eject Cylinders with scrapers and hardened rods to 50 HRC - Includes Five (5) Year Packer/Eject Cylinder Only Warranty that covers dents and dings. **(This Option is Required if purchasing extended warranty's below)**☐ Lightning Cylinder Package: reduces front loader arm cycle time by up to 5 seconds and reduces front loader arm lifting capacity to a maximum of 5,500 lbs. This package is available via Custom request only, and also requires an End User signed waiver acknowledging the reduced arm lifting capacity of these cylinders.

2021 - Effective December 1, 2020 - Half/Pack® Commercial Featuring Odyssey™ Controls - Sales Order Form	
CNRG Tailgate Mounted CNG- NFPT - 52 -2019 Compliant - Includes Installation Fee	
<input type="checkbox"/>	60 DGE CNG System
<input type="checkbox"/>	75 DGE CNG System
<input type="checkbox"/>	90 DGE CNG System
<input type="checkbox"/>	105 DGE CNG System
FET Exempt CNRG Tailgate Mounted CNG For 20YD Bodies Only- Includes Installation Fee	
<input type="checkbox"/>	60 DGE CNG System
<input type="checkbox"/>	75 DGE CNG System
<input type="checkbox"/>	90 DGE CNG System
<input type="checkbox"/>	105 DGE CNG System
CNRG Options	
<input type="checkbox"/>	Front Bumper Fill with Kill Cap
<input type="checkbox"/>	Remote Fill, StreetSide Rear Fill Port
<input type="checkbox"/>	Remote Fill, Curbside Rear Fill Port
<input type="checkbox"/>	Defuel Transfer Hose - 35 ft.
<input type="checkbox"/>	1/4 Turn Shutoff Valve - Isolates CNRG Tanks from Remainder of CNG system
CNG Installation - Top of Body Installation	
<input type="checkbox"/>	CNG Installation Charge - Includes brackets, temporary tank rental, hardware, and mounting of CNG system
Extended Complete Body Warranty Options	
<input type="checkbox"/>	Two (2) Year (Months 13-24) (Maximum 4,000 hrs. of Operation) Complete Heil Body Warranty
<input type="checkbox"/>	Three (3) Year (Months 13-36) (Maximum 6,000 hrs. of Operation) Complete Heil Body Warranty
<input type="checkbox"/>	Four (4) Year (Months 13-48) (Maximum 8,000 hrs. of Operation) Complete Heil Body Warranty
<input type="checkbox"/>	Five (5) Year (Months 13-60) (Maximum 10,000 hrs. of Operation) Complete Heil Body Warranty
Extended Cylinder Warranty Options	
<input type="checkbox"/>	Two (2) Year (Months 13-24) (Maximum 4,000 hrs. of Operation) All other Non-Infinity Cylinder Warranty -
<input type="checkbox"/>	Three (3) Year (Months 13-36) (Maximum 6,000 hrs. of Operation) All other Non-Infinity Cylinder Warranty -
<input type="checkbox"/>	Four (4) Year (Months 13-48) (Maximum 8,000 hrs. of Operation) All other Non-Infinity Cylinder Warranty -
<input type="checkbox"/>	Five (5) Year (Maximum 10,000 hrs. of Operation) All other Non-Infinity Cylinder Warranty -
Extended Hydraulic Pump and Valve Warranty Options	
<input type="checkbox"/>	Two (2) Year (Months 13-24) (Maximum 4,000 hours of operation) Hydraulic Pump and Valve warranty
<input type="checkbox"/>	Three (3) Year (Months 13-36) (Maximum 6,000 hours of operation) Hydraulic Pump and Valve warranty
<input type="checkbox"/>	Four (4) Year (Months 13-48) (Maximum 8,000 hours of operation) Hydraulic Pump and Valve warranty
<input type="checkbox"/>	Five (5) Year (Months 13-60) (Maximum 10,000 hours of operation) Hydraulic Pump and Valve warranty
Paint Options	
NOTE: LIST PAINT CODES ON PAINT DIAGRAM	
<input type="checkbox"/>	Customized Paint Color - Paint Color Code NOT included in the Color Smart Brochure
<input type="checkbox"/>	Two Tone Paint
<input type="checkbox"/>	Paint Striping - first stripe
<input type="checkbox"/>	Paint Striping - each additional stripe
<input type="checkbox"/>	Metallic Paint
<input type="checkbox"/>	Clear coat Finish
<input type="checkbox"/>	Anti-Graffiti Clear coat Finish
<input type="checkbox"/>	Prime Paint Only - deduct
<input type="checkbox"/>	Heil CleanShield™ by BrandArmor™ Cab protector decal.