20	21 - Effective December 1, 2020 - Half/Pack® LowRider - Residential Sales Order Form ase Units Half/Pack LowRider With Odyssey Controls
	20 cubic yard CNrG Tailgate Not Available With This Body Size
_	
	23 cubic yard Note: If chosen CNrG Tailgate Reduces Tailgate Capacity by 2 Cubic Yards - 21 Cubic Yard Unit With CNrG
	28 cubic yard Note: If chosen CNrG Tailgate Reduces Tailgate Capacity by 2 Cubic Yards - 26 Cubic Yard Unit With CNrG
$\overline{}$	Service Hoist Kit - 187" Wheelbase 5 Axle Units WILL NOT accept the service hoist option*
(I)	Service Hoist Lite (Quick Disconnect and Cylinders Only, No Pump or Reservoir)
	xle 187" Wheelbase - Hendrickson Auxiliary Axles Only with 275/R70/22.5 or smaller tires, SSIS MUST CONFORM WITH HEIL'S MOST CURRENT CHASSIS SPECIFICATIONS AT WWW.HEIL.COM
	ounting Options
	Full Factory Mount for Service Hoist or Serviceable Eject - Includes Body Props and Rear Pivot
	Mount at Dealer Destination
	ver Take Off / Pump Options
Ü	PTO Mounted Load Sense Piston pump - Includes PTO
	Automated Option
\Box	Hopper Seal Brush Kit - Includes Sides and Front For Curotto Only
	Remote Curbside Curotto Can Controls
	Installation of Auto cover controls - Auto cover must be purchased with the Curotto Can
	In-Cab controls for integrated Forward Facing Dual Cab Guard Mounted LED Lights - Forward Work lamps must be purchased with the
	Hose Conversion Kit - Must be selected if utilizing a Curotto Can Built prior to 1/1/2018
	Monoblock Quick Disconnect - Mounted to Fork Weldment. Quick Lever Action. Over center chain binder can mounting – This option
	MUST be selected if ordered through Curotto Can
	Semi-Automated Option
	Curotto Can Control Kit - Must Select to Add Controls to Order
	Bayne Carry Can Control Kit - Must Select to Add Controls to Order
	mplete selection of premium Bayne carry cans to sult any application is provided in this price book for your convenience
	ontrol Options
	Left and Right-Hand Multifunction Joysticks Including Auxiliary and Packer Functions
	Left Hand 2-Lever Electric Control in lieu of Multifunction Joystick
_	Left Hand Dual Axis Joystick Electric Control in lieu of Multifunction Joystick
	StreetSide mounted Outside 4 Button Electric Push Button Controls for Arms, Forks, and Packer circuits. StreetSide mounted Outside Dual Lever controls and 4 Button Electric Push Button controls for Pump Enable, Arms, Forks, and Packer
	circuits, Includes Throttle advance. Upgrade to 12" In Cab Display in lieu of 7" Std. (Non- 3rd Eye Camera Units Only) - See 3rd Eye below for 12" Display with camera options)
	ghting and Electrical Accessories
_	Single Led Windscreen Mounted Container Light
_	Multi-Function Lights
_	Body Side Backing Assist Lights - LED
	Dual Oval Flat LED Strobes Mounted Mid-T/G - in-cab switch, pump on, and reverse activated
$\overline{}$	Preco™ Back Up Alarm
-	Whelen Strobe Lights Kit
	Cab Shield Mounted LED Light Facing reward toward hopper opening
-	WTI ™ Radar Systems
	AWTI™ Radar Systems used in conjunction with 3rd Eye Cameras - Must Select Camera Kit From 3rd Eye Camera Options
	amera Systems
	amera systems are mounted with protective camera brackets and twin tailgate flood lights.
P	ERÀ MONITOR LOCATION WILL BE CAB ROOF MOUNTED
-	el monitor bracket will be provided for dual drive chassis
	rd Eye® Camera Systems & 3rd® Eye Digital E: Camera systems will accommodate a maximum of 5 cameras.
	Not including driver and forward facing cameras included in 3rd Eye*
	Base 3rd Eye® Single Camera System with 7" Monitor and Single Camera Mounted on Tailgate
	Upgraded base 3rd Eye [®] Single Camera System with 12" Monitor and Single Camera Mounted on Tailgate
	Add on 3rd Eye® Camera (LH Cab) - Camera System Price Adder (Only available if base camera is selected)
	Add on 3rd Eye® Camera (RH Cab) - Camera System Price Adder (Only available if base camera is selected)
	Add on 3rd Eye® Camera (LH Alley) - Camera System Price Adder (Only available if base camera is selected)
	Add on 3rd Eye® Camera (RH Alley) - Camera System Price Adder (Only available if base camera is selected)
	Add on 3rd Eye® Camera (Hopper) - Camera System Price Adder (Only available if base camera is selected)
- 1	3rd Eye® Digital System: Includes (Driver and Forward Facing Camera (Window Unit), and Gateway - (In-Cab Monitor Not Included) -
	*Digital monitoring service not included and must be purchased and activated though 3rd Eye post delivery *

	oad Cell Scale Systems
	Heil Optimum Payload System (HOPS) using Air-Weigh Axle Scales
	Air-Weigh™ Axle Scale System without Interlock
	Auxiliary Axles Options
	OTE: All axies MUST BE installed with tires so chassis can be re-certified to new GAWR and GVWR ratings
	Vatson & Chalin™ Options
	Watson & Chalin™ Self Steering Pusher Axle: 13,500 pound capacity, hub piloted or 20" spoke wheel hubs, automatic slack
	adjusters, type 16 air chambers, steering stabilizer kit and reverse lift kit - Watson & Chalin Self Steering Tag Axle: 13,500 pound capacity, hub piloted or 20" spoke wheel hubs, automatic slack adjusters,
	type 16 air chambers, steering stabilizer kit and reverse lift kit. includes Tag Axle Spill Shield
	type 16 air chambers, steering stabilizer kit and reverse lift kit, includes Tag Axle Spill Shield. Watson & Chalin™ Rigid Pusher Axle: 25,000 pound capacity, hub piloted or 20" spoke wheel hubs, 30/30 brake chambers, automatic
\vdash	slack adjusters, 1,300 cubic inch air tank and regulator kit Watson & Chalin M. Rigid Tag Axle: 25,000 pound capacity, hub piloted or 20" spoke wheel hubs, 30/30 brake chambers, automatic
	slack adjusters, 1,300 cubic inch air tank and regulator kit, includes Tag Axle Spill Shield
	lendrickson" Options
-	
무	Hendrickson™ Pusher Axle-13.500 pound capacity, Non-Steerable
	Hendrickson™ Pusher Axle-13.500 pound capacity, Steerable
	Hendrickson™ Tag Axle-13.500 pound capacity, Steerable, includes Tag Axle Spill Shield
	Hendrickson™ Tag Axle-13.500 pound capacity, Non- Steerable, includes Tag Axle Spill Shield
	Hendrickson™ Steerable Pusher Axle: 20,000 pound capacity
	Hendrickson™ Steerable Tag Axle: 20,000 pound capacity, includes Tag Axle Spill Shield
	ote: All suxiliary applications must be approved by Hell prior to order acceptance
/	uxiliary Axle Tire Options
	265/JOB 22 5 Obi(2) load space H 5 520 mountains land a solo sixtil Co. LW.
	255/70R-22.5 - Qty(2) load range H, 5,510 pound single max load at 120 psi with Steel Wheels
	275/70R-22.5 - Qty(2) load range H, 7,000 pound single max load at 120 psi with Steel Wheels
Ü	Upgrade to Polished Aluminum Wheels (Set of Two)
	lody Options
_	Articulating FEL Arms – Accommodate Econic SD Chassis – Stowed Height 13'6"
1	Rodent Resistant Loom – Weaved Loom Completely Encapsulating ALL Body Side Harnesses Reducing Downtime from Chewed Wires
П	Sliding Top Door - Aluminum - May not be compatible with roof mounted CNG system
	Sliding Top door - Steel - May not be compatible with roof mounted CNG systems
	Tailgate Mounted Roof Access Ladder Aluminum (Only one selection allowed) *Not available with CNrG Tailgate or 20yd body Option*
	Curbside Mounted Roof Access Ladder (Only one selection allowed) *Not Available on 23yd body with Top Door*
	Hopper Floor Liner (3/16" - AR400)
	Hopper Floor Liner (1/4" - AR400)
	Body Floor Liner (3/16" - AR400)
	1/4" AR400 Body Floor in lieu of standard 3/16" AR400
	Packer Mounted Retainer Teeth
	High Pressure Filter Monitor
	Second 20 lb. Fire Extinguisher (Will be mounted to Curb side Hopper, if unable will be mounted under body)
1	Tool Box Bumper Mount - Steel 18"x18"x24"
	Tool Box Bumper Mount - Aluminum 18"x18"x24"
	Tool Box Bumper Mount - Poly - 18"x18"x24"
1	Extendable Broom Kit - Mounted Curbside of Body (Not Available on 20/23 Yd) Extendable Broom Kit - Mounted Under Body
늗	Cab Protector Extension Raise - Manual Jack -
	Rear Caution Decal
౼	Wheel Chock Kit - Dual (Mounted Under Body)
	Wheel Chock Kit - Dual (Mounted on Curbside Body)
	Cable Fall Protection Kit
ā	D-Ring Fall Protection
	Hydraulic Oil Tank Quick Disconnect Kit - For use with filter buggy
	Butterfly Style Quick Disconnects In Lieu of Service Loop Plumbing
	Spill Kit included mounting brackets - (Mounted on Front Head)
	Spill Kit (In Toolbox) *Requires additional purchase of a tool box*
	Hydraulic Oil Tank Heater - 500 watts
	Bolt On Fender Extension Kit - Keeps Body Clean of Road Spray
	California Back Up Alarm
	Infinity Series Packer/Eject Cylinders with scrapers and hardened rods to 50 HRC - Includes Five (5) Year Packer/Eject Cylinder Only
	Warranty that covers dents and dings (This Option is Required if purchasing extended warranty's below) Standard Arm Cylinders for 8000# lift capacity and standard lift cycle time.
	Standard Arm Symplers for 6000# int capacity and standard int cycle time.

	60 DGE CNrG System
	75 DGE CNrG System
	90 DGE CNrG System
	NrG Options
	Front Bumper Fill with Kill Cap
	Remote Fill, StreetSide Rear Fill Port
	Remote Fill, Curbside Rear Fill Port
	Defuel Transfer Hose - 35 ft.
	1/4 Turn Shutoff Valve – Isolates CNrG Tanks from Remainder of CNG system
	NG Installation - Top of Body Installation
	CNG Installation Charge - Includes brackets, temporary tank rental, hardware, and mounting of CNG system
ŧ	xtended Complete Body Warranty Options
	Two (2) Year (Months 13-24) (Maximum 4,000 hrs. of Operation) Complete Heil Body Warranty
	Three (3) Year (Months 13-36) (Maximum 6,000 hrs. of Operation) Complete Heil Body Warranty
	Four (4) Year (Months 13-48) (Maximum 8,000 hrs. of Operation) Complete Heil Body Warranty
	Regulres additional purchase of
	Five (5) Year (Months 13-60) (Maximum 10,000 hrs. of Operation) Complete Heil Body Warranty
-	Requires additional purchase of infinity packer/eject cylinders from above
	Two (2) Year (Months 13-24) (Maximum 4,000 hrs. of Operation) All other Non-Infinity Cylinder Warranty -
	Paralless additional and an extension of left discuss to the first and t
	Three (3) Year (Months 13-36) (Maximum 6,000 hrs. of Operation) All other Non-Infinity Cylinder Warranty -
_	Four (4) Year (Months 13-48) (Maximum 8,000 hrs. of Operation) All other Non-Infinity Cylinder Warranty -
	Boardens additional purchase of inflictory assertation
	Five (5) Year (Months 13-60) (Maximum 10,000 hrs. of Operation) All other Non-Infinity Cylinder Warranty -
E	xtended Hydraulic Pump and Valve Warranty Options
	Two (2) Year (Months 13-24) (Maximum 4,000 hours of operation) Hydraulic Pump and Valve warranty
	Three (3) Year (Months 13-36) (Maximum 6,000 hours of operation) Hydraulic Pump and Valve warranty
	Four (4) Year (Months 13-48) (Maximum 8,000 hours of operation) Hydraulic Pump and Valve warranty
	#Not a sed of if a set of a se
	Five (b) Year (Months 13-60) (Maximum 10,000 hours of operation) Hydraulic Pump and Valve warranty
	*Not needed if purchasing extended complete body
	E. LIST PAINT CODES ON PAINT DIAGRAM
Ü	Customized Paint Color - Paint Color Code NOT included in the Color Smart Brochure
	Two Tone Paint
	Paint Striping - first stripe
	Paint Striping - each additional stripe
	Metallic Paint
	Clear coat Finish
	Anti-Graffiti Clear coat Finish
	Prime Paint Only - deduct
	**