

# Features, Benefits and Specifications

## STANDARD FEATURES AND BENEFITS:

- Environmentally Sealed Toggle Switch Control for Enhanced Reliability and Easy Installation
- Dual Cylinder Lift for Maximum Stability
- Screw-In Grease Fittings at all Wear Points for Easy Maintenance
- Latch Chains and Snubber Kits for Increased Safety and Reduced Wear of Liftgate
- 150 Amp Circuit Breaker for Electrical Protection
- Adjustable Cylinder Shafts and Idler Arms for Precise Alignment of Truck Floor & Platform
- Power Down for Better Reliability in Cold Weather Operation
- Bronze Bushings at Critical Pivot Points for Reduced Maintenance Costs
- Wider Lift Arms for Maximum Stability
- Meets All TMC Electrical Guidelines for Reduced Service Requirements

## AVAILABLE OPTIONS FOR WT:

- In-Cab Shut Off Switch
- Pump and Motor Cover
- Power Unit Enclosure
- Special Platform and Ramp Sizes
- Aluminum Platform
- Expanded Metal Platform
- Bar Grate

Model No.	Platform	Rated Load Cap. lbs.	Lowering	Approx. Installed Weight	Bed Height Range
WT20EST	84" x 36" + 10"	2000	Power	938	40" to 54"
WT20EST	90" x 36" + 10"	2000	Power	958	40" to 54"
WT20P	84" x 36" + 10"	2000	Power	936	40" to 54"
WT20P	90" x 36" + 10"	2000	Power	956	40" to 54"
WT20EST	90" x 42" + 10"	1750	Power	981	40" to 54"
WT20EST	90" x 48" + 10"	1500	Power	1069	40" to 54"
WT20P	90" x 42" + 10"	1750	Power	989	40" to 54"
WT20P	90" x 48" + 10"	1500	Power	1051	40" to 54"
WT30EST	84" x 36" + 10"	3000	Power	936	40" to 54"
WT30EST	90" x 36" + 10"	3000	Power	956	40" to 54"
WT30P	84" x 36" + 10"	3000	Power	906	40" to 54"
WT30P	90" x 36" + 10"	3000	Power	926	40" to 54"
WT30EST	90" x 42" + 10"	2500	Power	1009	40" to 54"
WT30EST	90" x 48" + 10"	2000	Power	1081	40" to 54"
WT30P	90" x 42" + 10"	2500	Power	1037	40" to 54"
WT30P	90" x 48" + 10"	2000	Power	1101	40" to 54"
WT40EST	90" x 36" + 10"	4000	Power	1006	40" to 54"
WT40EST	90" x 42" + 10"	3500	Power	1059	40" to 54"
WT40EST	90" x 48" + 10"	3000	Power	1121	40" to 54"
WT40P	90" x 36" + 10"	4000	Power	1055	40" to 54"
WT40P	90" x 42" + 10"	3500	Power	1059	40" to 54"
WT40P	90" x 48" + 10"	3000	Power	1135	40" to 54"

Note: On "P" Model Gates a 70% ratio PTO is recommended

EST - Electric w/Toggle Switch Control, Power Down/Power Close  
P - PTO w/Power Close

Distributed By:

THIEMAN Reserves the right to Change Products Specifications at any time Without Prior Notice.  
Printed in U.S.A. Rev. 5/10 • 2M • M70079

**THIEMAN**  
**TAILGATES, INC.**  
*Raising Performance to New Levels*

600 East Wayne Street  
Celina, Ohio 45822  
Phone: 419-586-7727 or  
800-524-5210  
Fax: 419-586-9724  
[www.thiemantailgates.com](http://www.thiemantailgates.com)  
[info@thiemantailgates.com](mailto:info@thiemantailgates.com)

# Features, Benefits and Specifications

## STANDARD FEATURES AND BENEFITS:

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• Screw in Grease Fittings at All Wear Points for Easier Maintenance</li> <li>• Adjustable Cylinder Shaft for Precise Alignment of Truck Floor and Platform</li> <li>• 150 Amp Circuit Breaker for Electrical Protection</li> <li>• Gravity Down Platform for Less Demand on Power Unit</li> </ul> | <ul style="list-style-type: none"> <li>• Cam Activated, Power Close Platform for Easy Closing</li> <li>• Latch Chain for Increased Safety</li> <li>• Meets All TMC Electrical Guidelines for Reduced Service Requirements</li> </ul> |
|---|--|

## OPTIONS FOR TWL SERIES:

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Push Button Control</li> <li>• In-Cab Shut Off Switch</li> <li>• Remote Pendant Control</li> <li>• Expanded Metal Platform</li> <li>• Load Area, Ramp Change</li> </ul> | <ul style="list-style-type: none"> <li>• Power Down</li> <li>• PTO Power Source</li> <li>• Square Edge, No Ramp</li> <li>• Power Unit Enclosure</li> </ul> |
|--|--|

Model No.	Platform	Capacity	Lowering	Install Weight	Bed Height Range
TWL-125ET	66" x 26" + 8"	1250 lb.	Gravity	436 lb.	33"-47"
TWL-125ET	78" x 32" + 8"	1250 lb.	Gravity	531 lb.	33"-47"
TWL-125ET	84" x 32" + 8"	1250 lb.	Gravity	546 lb.	33"-47"
TWL-16ET	78" x 32" + 8"	1600 lb.	Gravity	561 lb.	37"-52"
TWL-16ET	84" x 32" + 8"	1600 lb.	Gravity	576 lb.	37"-52"
TWL-16ET	90" x 32" + 8"	1600 lb.	Gravity	596 lb.	37"-52"
TWL-20ET	78" x 32" + 8"	2000 lb.	Gravity	564 lb.	37"-52"
TWL-20ET	84" x 32" + 8"	2000 lb.	Gravity	579 lb.	37"-52"
TWL-20ET	90" x 32" + 8"	2000 lb.	Gravity	599 lb.	37"-52"

ET - Electric w/Toggle Switch Control/Power Close

Distributed By:

**THIEMAN**  
**TAILGATES INC.**  
*Raising Performance to New Levels*

600 East Wayne Street  
 Celina, Ohio 45822  
 Phone: (419) 586-7727 or  
 800-524-5210  
 Fax: (419) 586-9724  
 www.thieman.com  
 ttgates@wesnet.com

THIEMAN Reserves the right to Change Products  
 Specifications at any time Without Prior Notice.  
 Printed in U.S.A. 12/00 • 2M • MP46572