

6010T INDUSTRIAL TUB GRINDER

Specification Sheet



SPECIFICATIONS:

Weight	44,620 lbs (20239.3 kg)
Transport Width	8' 6" (2.59 m)
Transport Height	11' 4" (3.45 m)
Transport Length	36' 3" (11.07 m)
Incline Grade	Tracks Will Climb 50% Incline Grade
Track System	20" (50.8 cm) wide x 15' (4.6 m) Long Steel Track
Electrical	24 Volt
Engine (Option A)	475 hp (354.21 kw) CAT C15 Tier IV
Engine (Option B)	540 hp (402.68 kw) CAT C15 Tier IV 630 hp (470 kw) CAT C18 Tier IV
Clutch	HPTO Wet Clutch
Fuel Capacity	160 Gallons (605.6 L)
Hydraulic Oil Capacity	90 Gallons (340.7 L)
Tub Width	10' (3.05 m)
Depth	46" (116.8 cm)
Tub Diameter at Base	8' (2.44 m)
Tub Wall	1/4" Thick (0.64 cm)
Tub Floor	3/8" Thick (0.95 cm)
Tub Drive	Direct Hydraulic Drive
Service Access	90 Degree Tilting Tub
Stacking Conveyor-Short	10' 6"L x 30"W x 8"D (3.2m L x 76.2cm W x 20.3cm D)
Stacking Conveyor-Folding	26'L x 30"W x 8"D (7.92m L x 76.2cm W x 20.3cm D)
Discharge Augers	Dual 12" diameter augers with dual hydraulic motor drive
Tub Speed Sensor	Electronic Self Governing
Rotor - Shaft Diameter	6" (15.24 cm) Stress Proof Steel
Rotor Length	44" (111.76 cm)
Rotor Plates	16" (40.64 cm) Dia 1-1/2" (3.81 cm) Thick Plates
Feed Opening	25" (63.5 cm) x 45" (114.3 cm)
Screen Area	2403 Sq. In. (15,503 sq cm)
Hammer Rods	1-1/2" (3.81 cm) Dia., 43" (109.22 cm) Long
Bearings	4" (10.16 cm) Pillow Block Bearings
Hammermill Drive	Direct Thru HPTO Oil Cooled Clutch
Screens	Split Screens 1" (2.54 cm) Thick
Screen Area	2,403 Sq. In (15,503 sq cm)