

## TC-12 Chipper Specification Sheet



### **SPECIFICATIONS:**

Engine	CAT C4.4 129 HP (96 kw) KUBOTA V3800 Diesel 88 hp (74 kw)
Gross Weight	7,640 lbs.(3,465.5 kg)
Transport Width	79" (200 cm)
Transport Length	208" (528 cm)
Hitch	Pintle or 2-5/16" Ball
Tongue Weight	740 lbs.(335.7 kg)
Jack	7,000lbs (3,175.2 kg)
Axle	7,000lb (3,175.2kg) Torflex
Suspension	Torsional
Brakes	Electric
Tires	235/85R x 16E
Fuel Capacity	40 gal (152 L)
Hydraulic Oil Capacity	25 gal (95 L)
Electrical	24V
Lights	Clearance and Directional
Transmission	PT Tech HPTO
Chipping capacity	12" (30.5 cm)
Infeed Hopper opening	40" x 62" (102 cm x 157 cm)
Throat opening	12" x 20" (30 cm x 51 cm)
Disc size	42" (107 cm) dia. x 2" (5 cm)
Disc shaft size	3-15/16" (10 cm) dia.
Feed system	Hydraulic 2 Drum
Number of knives	4, 2 Slots
Size of knives	4-1/2" (11.5 cm) x 7-3/4" (19.5 cm) 3-bolt
Down pressure on feed wheel	Adjustable Spring Load, Optional Auto Feed Height System
Discharge System	360 degree, Hydraulic Rotation w/ Adjustable Chip Spout
Safety features	Breakaway Brake Switch, 2 E-Stop Switches, 2 Infeed Hopper Light Bars, and Disc Hood Closed Proximity Switch
Frame size	3" (7.6 cm) x 5" (12.7 cm) x 1/4" (0.64 cm)