



TRIPLE T ISUZU TRUCK

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

North Carolina Sheriffs's Association



Current report content is based on data as of 2021-04-07 09:58:21. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



TRIPLE T ISUZU TRUCK

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

North Carolina Sheriffs's Association (2021 NPR-HD Gas Cab Chassis, 1F4 176"WB, 153.5"CA, 14,500 GVWR. White, Standard model specifications with power windows and door locks

Selected Model and Options

	Code	Description	Weight
Model			
	1F4 04	NPR-HD Gas Cab Chassis 176"WB, 153.5"CA White, Standard model specifications with power windows and door locks	
Tires			
	I5H	LRR (low rolling resistance)	0.0 lbs.
Engine			
	L8T	GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise fuel control direct injection technology; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads; forged steel crankshaft; stainless steel exhaust manifold.	0.0 lbs.
Transmission			
	MYD	6L90-E Hydra-Matic, 6-speed automatic with lock-up converter and overdrive. Ratios: Gear and Ratios 4.027, 2.364, 1.532, 1.152, 0.0852, 0.667, Rev. 3.064:1	0.0 lbs.
Wheelbase			
	FNW	176 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in3 RBM 316,800 lb./ft./in per rail. 153.5"CA	0.0 lbs.
Air Cleaner			
	KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.	0.0 lbs.
Alternator			
	KW7	170 Amp. output with integral regulator.	0.0 lbs.
Battery			
	IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box	0.0 lbs.
Exhaust			
	I41	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.	0.0 lbs.
Front Axle			
	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	0.0 lbs.
Front Suspension			
	I0K	7,220 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar.	0.0 lbs.
Front Wheels			
	IB9	19.5" x 6", 6-hole disc, painted white	0.0 lbs.
Front Tires			
	I8B	225/70R19.5G (14 ply) tubeless Radial, all season tread	0.0 lbs.

Current report content is based on data as of 2021-04-07 09:58:21. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



TRIPLE T ISUZU TRUCK

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

North Carolina Sheriffs's Association (2021 NPR-HD Gas Cab Chassis, 1F4 176"WB, 153.5"CA, 14,500 GVWR. White, Standard model specifications with power windows and door locks

Selected Model and Options

	Code	Description	Weight
Rear Suspension			
	I8J	12,900 lbs. Capacity semi elliptical; main and auxiliary multi- leaf spring. Includes shock absorbers.	0.0 lbs.
Rear Axle			
	ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	0.0 lbs.
Ratio			
	092	4.300:1	0.0 lbs.
Rear Wheels			
	IC1	19.5" x 6", 6-hole disc, painted white	0.0 lbs.
Rear Tires			
	I9B	225/70R19.5G (14 ply) tubeless Radial, all season tread.	0.0 lbs.
Fuel Tank			
	A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	0.0 lbs.
Seat			
	AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	0.0 lbs.
Brakes			
	IR8	Dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard. 4 channel anti-lock brake system.	0.0 lbs.
Air Conditioning			
	C60	Air conditioner	0.0 lbs.
Power Windows & Door Locks			
	IL0	Yes	0.0 lbs.
Model Option			
	04	White, Standard model specifications with power windows and door locks	0.0 lbs.
Accessories			
	IX2	Rear body dome lamp switch	0.1 lbs.
	8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	0.0 lbs.

Current report content is based on data as of 2021-04-07 09:58:21. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.