



## TRIPLE T ISUZU TRUCK

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

# North Carolina Sheriffs's Association



Current report content is based on data as of 2021-04-07 08:47:17. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# TRIPLE T ISUZU TRUCK

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

North Carolina Sheriffs's Association (2022 NQR Crew Cab Chassis, NS4 176"WB, 114.5"CA, 17,950 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning

## Selected Model and Options

|                         | Code    | Description  | Weight   |
|-------------------------|---------|--|----------|
| <b>Model</b>            |         |  |          |
|                         | NS4     | NQR Crew Cab Chassis 176"WB, 114.5"CA  |          |
|                         | 54      | White, In rail fuel tank with power windows, power door locks and air conditioning   |          |
| <b>Tires</b>            |         |  |          |
|                         | I5H     | LRR (low rolling resistance)   | 0.0 lbs. |
| <b>Engine</b>           |         |  |          |
|                         | I1B     | 4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level. | 0.0 lbs. |
| <b>Transmission</b>     |         |  |          |
|                         | I1W     | Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,  | 0.0 lbs. |
| <b>Wheelbase</b>        |         |  |          |
|                         | IH7     | 176 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in <sup>3</sup> RBM 523,160 lb./ft./in. per rail. 114.5"CA  | 0.0 lbs. |
| <b>Air Cleaner</b>      |         |  |          |
|                         | KNX     | Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).  | 0.0 lbs. |
| <b>Alternator</b>       |         |  |          |
|                         | I2C     | 140 AMP. with integral regulator.  | 0.0 lbs. |
| <b>Battery</b>          |         |  |          |
|                         | IX1     | Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts   | 0.0 lbs. |
| <b>Exhaust</b>          |         |  |          |
|                         | IX7     | Single horizontal with DPF/SCR exhaust system  | 0.0 lbs. |
| <b>Front Axle</b>       |         |  |          |
|                         | ID2     | "I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.  | 0.0 lbs. |
| <b>Front Suspension</b> |         |  |          |
|                         | ID8     | 8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar  | 0.0 lbs. |
| <b>Front Wheels</b>     |         |  |          |
|                         | IB9     | 19.5" x 6", 6-hole disc, painted white   | 0.0 lbs. |
| <b>Front Tires</b>      |         |  |          |
|                         | XTN/R3M | 225/70R19.5F (12 ply) tubeless Radial, all season  | 0.0 lbs. |
| <b>Rear Suspension</b>  |         |  |          |
|                         | ID9     | 14,550 lbs. capacity. Semi-elliptical main and   | 0.0 lbs. |

Current report content is based on data as of 2021-04-07 08:47:17. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# TRIPLE T ISUZU TRUCK

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

North Carolina Sheriffs's Association (2022 NQR Crew Cab Chassis, NS4 176"WB, 114.5"CA, 17,950 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning

## Selected Model and Options

|                                       | Code    | Description   | Weight   |
|---------------------------------------|---------|---|----------|
| <b>Rear Axle</b>                      |         |   |          |
|                                       |         | auxiliary multi-leaf springs. Includes shock absorbers.   |          |
|                                       | ID3     | Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.  | 0.0 lbs. |
| <b>Ratio</b>                          |         |   |          |
|                                       | 098     | 5.125:1   | 0.0 lbs. |
| <b>Rear Wheels</b>                    |         |   |          |
|                                       | IC1     | 19.5" x 6", 6-hole disc, painted white  | 0.0 lbs. |
| <b>Rear Tires</b>                     |         |   |          |
|                                       | YTN/S3M | 225/70R19.5F (12 ply) tubeless Radial, all season tread.  | 0.0 lbs. |
| <b>Fuel Tank</b>                      |         |   |          |
|                                       | IF9     | 30 gal. rectangular fuel tank. Mounted between frame rail through the rail fuel fill. Fuel water separator with dash mounted warning light.   | 0.0 lbs. |
| <b>Seat</b>                           |         |   |          |
|                                       | AQB     | Driver seat is reclining high back. Two single occupant fold down seats with tray backs.  | 0.0 lbs. |
| <b>Brakes</b>                         |         |   |          |
|                                       | K40     | Butterfly valve type exhaust brake  | 0.0 lbs. |
|                                       | IT4     | Dual circuit, Hydro-Boost hydraulic brake system with EBD (Electronic Brake Distribution). Mechanical transmission mounted parking brake. Non-asbestos semi metallic linings are standard. Anti-lock brake system | 0.0 lbs. |
| <b>Air Conditioning</b>               |         |   |          |
|                                       | C60     | Air conditioner   | 0.0 lbs. |
| <b>Power Windows &amp; Door Locks</b> |         |   |          |
|                                       | IL0     | Yes   | 0.0 lbs. |
| <b>Floor Mats</b>                     |         |   |          |
|                                       | IQ6     | Standard Floor Mats   | 0.0 lbs. |
| <b>Model Option</b>                   |         |   |          |
|                                       | 54      | White, In rail fuel tank with power windows, power door locks and air conditioning  | 0.0 lbs. |
| <b>Accessories</b>                    |         |   |          |
|                                       | IX2     | Rear body dome lamp switch  | 0.1 lbs. |
|                                       | 8RP     | AM/FM/CD radio with Aux input/USB port and Bluetooth RPO  | 0.0 lbs. |

Current report content is based on data as of 2021-04-07 08:47:17. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.