



## TRIPLE T ISUZU TRUCK

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

# North Carolina Sheriffs's Association



Current report content is based on data as of 2021-04-07 09:24:58. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



## TRIPLE T ISUZU TRUCK

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

North Carolina Sheriffs's Association (2022 NQR Gas Crew Cab, 1S4 176"WB, 114.5"CA, 17,950 GVWR.  
White, Standard model specifications with power windows and door locks

### Selected Model and Options

	Code	Description	Weight
<b>Model</b>			
	1S4 04	NQR Gas Crew Cab 176"WB, 114.5"CA White, Standard model specifications with power windows and door locks	
<b>Vehicle Application</b>			
	RQ2	Truck Application	0.0 lbs.
<b>Tires</b>			
	I5H	LRR (low rolling resistance)	0.0 lbs.
<b>Engine</b>			
	LNJ	PSI 6.0L (366 CID) V8 gasoline engine; 311 HP at 4900 RPM; 353 lb-ft torque at 4150 RPM; sequential port fuel injection; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main- bearing cap; cast aluminum cylinder heads.	0.0 lbs.
<b>Transmission</b>			
	Y6V	Allison 1000 RDS 6-speed automatic transmission w/ PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1	0.0 lbs.
<b>Wheelbase</b>			
	FNW	176 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in <sup>3</sup> RBM 316,800 lb./ft./in per rail. 114.5"CA	0.0 lbs.
<b>Air Cleaner</b>			
	KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.	0.0 lbs.
<b>Battery</b>			
	IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box	0.0 lbs.
<b>Exhaust</b>			
	I41	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.	0.0 lbs.
<b>Front Axle</b>			
	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	0.0 lbs.
<b>Front Wheels</b>			
	IB9	19.5" x 6", 6-hole disc, painted white	0.0 lbs.
<b>Front Tires</b>			
	I8B	225/70R19.5G (14 ply) tubeless Radial, all season tread	0.0 lbs.
<b>Rear Axle</b>			
	ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	0.0 lbs.
<b>Ratio</b>			
	011	5.571:1	0.0 lbs.
<b>Rear Wheels</b>			

Current report content is based on data as of 2021-04-07 09:24:58. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



## TRIPLE T ISUZU TRUCK

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

North Carolina Sheriffs's Association (2022 NQR Gas Crew Cab, 1S4 176"WB, 114.5"CA, 17,950 GVWR.  
White, Standard model specifications with power windows and door locks

### Selected Model and Options

	Code	Description	Weight
	IC1	19.5" x 6", 6-hole disc, painted white	0.0 lbs.
<b>Rear Tires</b>			
	I9B	225/70R19.5G (14 ply) tubeless Radial, all season tread.	0.0 lbs.
<b>Fuel Tank</b>			
	A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	0.0 lbs.
<b>Seat</b>			
	AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	0.0 lbs.
<b>Air Conditioning</b>			
	C60	Air conditioner	0.0 lbs.
<b>Power Windows &amp; Door Locks</b>			
	IL0	Yes	0.0 lbs.
<b>Model Option</b>			
	04	White, Standard model specifications with power windows and door locks	0.0 lbs.
<b>Accessories</b>			
	IX2	Rear body dome lamp switch	0.1 lbs.
	8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	0.0 lbs.

Current report content is based on data as of 2021-04-07 09:24:58. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.