



## TRIPLE T ISUZU TRUCK

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

# North Carolina Sheriffs's Association



Current report content is based on data as of 2021-04-07 08:50:40. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



## TRIPLE T ISUZU TRUCK

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

North Carolina Sheriffs's Association (2022 NQR Gas Cab Chassis, 1R4 176"WB, 153.5"CA, 17,950 GVWR. White, Standard model specifications with power windows and door locks

### Selected Model and Options

|                            | Code      | Description   | Weight   |
|----------------------------|-----------|---|----------|
| <b>Model</b>               |           |   |          |
|                            | 1R4<br>04 | NQR Gas Cab Chassis 176"WB, 153.5"CA<br>White, Standard model specifications with power windows and door locks  |          |
| <b>Vehicle Application</b> |           |   |          |
|                            | RQ2       | Truck Application   | 0.0 lbs. |
| <b>Tires</b>               |           |   |          |
|                            | I5H       | LRR (low rolling resistance)  | 0.0 lbs. |
| <b>Engine</b>              |           |   |          |
|                            | LNJ       | PSI 6.0L (366 CID) V8 gasoline engine; 311 HP at 4900 RPM; 353 lb-ft torque at 4150 RPM; sequential port fuel injection; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads. | 0.0 lbs. |
| <b>Transmission</b>        |           |   |          |
|                            | Y6V       | Allison 1000 RDS 6-speed automatic transmission w/ PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1  | 0.0 lbs. |
| <b>Wheelbase</b>           |           |   |          |
|                            | FNW       | 176 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in <sup>3</sup> RBM 316,800 lb./ft./in per rail. 153.5"CA   | 0.0 lbs. |
| <b>Air Cleaner</b>         |           |   |          |
|                            | KNX       | Dry paper single element. Air cleaner canister standard with air restriction gauge.   | 0.0 lbs. |
| <b>Battery</b>             |           |   |          |
|                            | IL3       | Single Delco 12-V maintenance free 750 CCA frame mounted battery box  | 0.0 lbs. |
| <b>Exhaust</b>             |           |   |          |
|                            | I41       | Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.  | 0.0 lbs. |
| <b>Front Axle</b>          |           |   |          |
|                            | ID2       | "I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.   | 0.0 lbs. |
| <b>Front Wheels</b>        |           |   |          |
|                            | IB9       | 19.5" x 6", 6-hole disc, painted white  | 0.0 lbs. |
| <b>Front Tires</b>         |           |   |          |
|                            | I8B       | 225/70R19.5G (14 ply) tubeless Radial, all season tread   | 0.0 lbs. |
| <b>Rear Axle</b>           |           |   |          |
|                            | ID3       | Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.  | 0.0 lbs. |
| <b>Ratio</b>               |           |   |          |
|                            | 011       | 5.571:1   | 0.0 lbs. |
| <b>Rear Wheels</b>         |           |   |          |

Current report content is based on data as of 2021-04-07 08:50:40. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



## TRIPLE T ISUZU TRUCK

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

North Carolina Sheriffs's Association (2022 NQR Gas Cab Chassis, 1R4 176"WB, 153.5"CA, 17,950 GVWR. White, Standard model specifications with power windows and door locks

### Selected Model and Options

|                                       | Code | Description   | Weight   |
|---------------------------------------|------|---|----------|
|                                       | IC1  | 19.5" x 6", 6-hole disc, painted white  | 0.0 lbs. |
| <b>Rear Tires</b>                     |      |   |          |
|                                       | I9B  | 225/70R19.5G (14 ply) tubeless Radial, all season tread.  | 0.0 lbs. |
| <b>Fuel Tank</b>                      |      |   |          |
|                                       | A17  | 38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill. | 0.0 lbs. |
| <b>Seat</b>                           |      |   |          |
|                                       | AQB  | Driver seat is reclining high back. Two single occupant fold down seats with tray backs.  | 0.0 lbs. |
| <b>Air Conditioning</b>               |      |   |          |
|                                       | C60  | Air conditioner   | 0.0 lbs. |
| <b>Power Windows &amp; Door Locks</b> |      |   |          |
|                                       | IL0  | Yes   | 0.0 lbs. |
| <b>Model Option</b>                   |      |   |          |
|                                       | 04   | White, Standard model specifications with power windows and door locks  | 0.0 lbs. |
| <b>Accessories</b>                    |      |   |          |
|                                       | IX2  | Rear body dome lamp switch  | 0.1 lbs. |
|                                       | 8RP  | AM/FM/CD radio with Aux input/USB port and Bluetooth RPO  | 0.0 lbs. |

Current report content is based on data as of 2021-04-07 08:50:40. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.