

# **North Carolina Sheriffs's Association**



Current report content is based on data as of 2021-04-07 09:37:38. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



## **TRIPLE T ISUZU TRUCK**

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

North Carolina Sheriffs's Association (2022 NRR Gas Crew Cab, 1V4 176"WB, 114.5"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

### **Selected Model and Options**

Code	Description	Weight
1V4 04	NRR Gas Crew Cab 176"WB, 114.5"CA White, Standard model specifications with power windows and door locks	
RQ2	Truck Application	0.0 lbs.
15H	LRR (low rolling resistance)	0.0 lbs.
LNJ	PSI 6.0L (366 CID) V8 gasoline engine; 311 HP at 4900 RPM; 353 lb-ft torque at 4150 RPM; sequential port fuel injection; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main- bearing cap; cast aluminum cylinder heads.	0.0 lbs.
Y6V	Allison 1000 RDS 6-speed automatic transmission w/ PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1	0.0 lbs.
FNW	176 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in3 RBM 316,800 lb./ft./in per rail. 114.5"CA	0.0 lbs.
KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.	0.0 lbs.
IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box	0.0 lbs.
141	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.	0.0 lbs.
IZ6	"I"-beam rated at 7,275 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	0.0 lbs.
IB9	19.5" x 6", 6-hole disc, painted white	0.0 lbs.
I8B	225/70R19.5G (14 ply) tubeless Radial, all season tread	0.0 lbs.
ID3	Single-speed, 14,550 lb. capacity with oil lubricated	0.0 lbs.
	rear wheel bearings.	
<b>.</b>		
	L L / 1 · 1	0.0 lbs.
	1V4 04 RQ2 I5H LNJ Y6V FNW FNW KNX IL3 IL3 IL3 IL3 IL3 IL3 IL3	1V4 NRR Gas Crew Cab 176"WB, 114.5"CA   04 White, Standard model specifications with power windows and door locks   RQ2 Truck Application   15H LRR (low rolling resistance)   LNJ PSI 6.0L (366 CID) V8 gasoline engine; 311 HP at 4900 RPM; 353 lb-ft forque at 4150 RPM; sequential port fuel injection; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt mainbearing cap; cast aluminum cylinder heads.   Y6V Allison 1000 RDS 6-speed automatic transmission w/ PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1   FNW 176 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in3 RBM 316,800 lb./ft./in per rail. 114.5"CA   KNX Dry paper single element. Air cleaner canister standard with air restriction gauge.   IL3 Single Delco 12-V maintenance free 750 CCA frame mounted battery box   I41 Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.   IZ6 "I"-beam rated at 7,275 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.   IB9 19.5" x 6", 6-hole disc, painted white   I88 225/70R19.5G (14 ply) tubeless Radial, all season tread   ID3 Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.

Current report content is based on data as of 2021-04-07 09:37:38. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



## **TRIPLE T ISUZU TRUCK**

Andy Devane | 910-540-5507 | andy.devane@wemeantrucks.com

North Carolina Sheriffs's Association (2022 NRR Gas Crew Cab, 1V4 176"WB, 114.5"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

#### **Selected Model and Options**

Code	Description	Weight
IC1	19.5" x 6", 6-hole disc, painted white	0.0 lbs.
Rear Tires		
19B	225/70R19.5G (14 ply) tubeless Radial, all season tread.	0.0 lbs.
Fuel Tank		
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	0.0 lbs.
Seat		
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	0.0 lbs.
Air Conditioning		
C60	Air conditioner	0.0 lbs.
Power Windows & Door Locks		
ILO	Yes	0.0 lbs.
Model Option		
04	White, Standard model specifications with power windows and door locks	0.0 lbs.
Accessories		
IX2	Rear body dome lamp switch	0.1 lbs.
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	0.0 lbs.

Current report content is based on data as of 2021-04-07 09:37:38. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.