

Description

MODEL: PETERSEN RS-3 REAR STEER LOADER

STANDARD EQUIPMENT INCLUDED

20' TELESCOPIC BOOM, INCLUDES 4' TIP EXTENSION

9' REACH BELOW GRADE

STANDARD GRAPPLE BUCKET: 60" X 48"

CONTINUOUS BUCKET ROTATOR

SUSPENSION LOCKS: ELIMINATE NEED FOR DEPLOYING OUTRIGGERS

4-WAY OUTRIGGER STABILIZERS, FOR OCCASIONAL HEAVY LOADS OVER 4,000 LBS

TWIN BOOM DESIGN: ALLOWS FLEXING UNDER LEAD SHOCKS

BOOM UP WARNING LIGHT W/ ALARM (OVERHEIGHT)

HD SWING MOTOR: DIRECT DRIVE - 150,000 IN-LBS TORQUE, 270 DEGREE ROTATION

CLIMATE CONTROLLED OPERATOR'S STAION: INCLUDES

- ALL EQUIPMENT REQUIRED TO DRIVE UNIT FROM OPERATOR'S STATION
- ALL EQUIPMENT REQUIRED TO OPERATE BOOM
- TWIN, 6-WAY MECHANICAL JOYSTICKS
- AIR CONDITIONING, HEAT
- HD TRUCK TYPE OPERATOR'S SEAT
- WORK BRAKE W/ TOGGLE SWITCH
- WINDSHIELD WIPER
- 12V POWER PLUG
- STROBE & TURN SIGNAL LIGHT BAR ABOVE CAB

STANDARD WARRANTY: 1-YR HYDRAULIC & 3-YRS MAJOR STRUCTURAL

INCLUDES STANDARD PAINT & INSTALLATION ON SUITABLE CHASSIS

NOTE: CHASSIS SPEC MUST BE APPROVED BY PETERSEN REP PRIOR TO ORDER

DEALER SERVICES INCLUDED

FREIGHT TO AMICK EQUIPMENT

PDI & ONE (1) LOCAL MOVE TO TRUCK DEALER OR END USER

AECI MOBILE ON-SITE WARRANTY PKG., 1 YR

ON-SITE TRAINING - PROVIDED BY REQUEST