



3242 Eagle Portable Jaw Crusher


The 3242 Eagle portable jaw crusher provides high strength construction without unnecessary weight making this crusher ideal for portable and skid-mounted applications.

Features

- ❶ The 3242 Eagle portable jaw crusher frame is designed for ease of pitman/shaft assembly removal for transportation purposes.
- ❷ Grizzly bypass chute with flop gate allows for either removal of the material that passes the grizzly deck onto an available cross-belt conveyor for stockpiling or for blending with the crushed material.
- ❸ Hydraulic lift and leveling system enables quick and easy set up and tear down.
- ❹ Totally self-contained, reliable diesel/electric or all-electric power. You won't have to worry about hydraulic leaks and failures shutting you down.

Additional Features

- Built rock solid with proven technology and designed to last with minimal service and maintenance.
- Unique two-step, 5' grizzly deck for removal of fines before crushing.
- Includes removable electrical control panel featuring pre-wired receptacles for stackers.
- Manage the feeder speed for continuous flow of material into the impactor with variable frequency drive (VFD).
- Includes wireless remote control for the feeder shutdown and all motor stop.



3242 Eagle Portable Jaw Crusher Technical Specifications*

Crusher	3242
Overall Length	48' 7" / 14.8M
Gross Weight	114500lbs / 51900kg
Travel Length	45' 3" / 13.8M
Travel Width	11' 9" / 3.6M
Travel Height	13' 6" / 4.1M
Feed Hopper Capacity	12.9yd ³ / 9.9M ³
Feed Hopper Capacity (Tons)	17.4T / 15.8MT
Vibrating Feeder	19' x 39" / 5.8M x 1.0M
Feeder Grizzly Deck	60" single deck / 1524mm single deck
On-Plant Power Supply Diesel	275HP / 205 kW diesel engine and 80kW generator
On-Plant Power Supply Electric	150HP / 112kW all-electric power
Discharge Conveyor Width	48" / 1219mm

Jaw Crusher Specifications*

Model	Weight (lbs / kg)	RPM	Eccentric Stroke (Inches / Millimeters)	Power Required (HP / kW)
3242	53000 / 24091	250	1.25 / 31.75	150 - 200 / 112 - 149

*Design specifications subject to change without notice.