

**DV36 DOUBLE DRUM VIBRATORY ROLLER
US PRICE LIST**

Standard Equipment

ENGINE:

Yanmar 4TNV88
Tier 4 Interim certified
Horsepower
- 41 Hp (30 kW) @ 2400 RPM
Fuel tank capacity: 15.6 gallons (59 L)

OPERATOR STRUCTURE:

Foldable ROPS
Iso-mounted operator's platform
Instrument panel with vandal guard
Lateral shifting suspension seat with
-Vinyl
-2" retractable seatbelt
-Handrails
Single lever control with
-Ground speed and direction
-Vibration on/off control

DRUM AND CHASSIS:

Articulated chassis
Hydrostatic drive (both drums)
51.2" wide x 33.5" diameter with
-Chamfered drum edges
Drum drive motors
-Poclain drum drive motors with
fixed displacement
Hydraulic oil cooler
Dual frequency vibration (hi/lo)
Dual drum vibration selections
-Front drum only
-Both drums
-Auto vibration stop in neutral
Adjustable Vulcollon scrapers
-2 x scrapers per drum
Recessed drum drive motors
Isolated rubber drum mounts

TRANSMISSION:

Variable displacement axial piston
drive pump

ELECTRICAL:

Batteries - 1 x 12V @ 760 CCA
Master disconnect switch
Fuse protection cover

WATER SYSTEM:

Polyethylene water tank
Single water tank
- 92.5 gallon (350 L)
Pressurized sprinkler system
Adjustable sprinkler volume control
Two-stage water filtration
Water tank drain
Sprinkler system on/off switch

OTHER:

SAHR service brake
Multi disc parking/emergency brake
Back-up alarm
Lift and tie downs
Horn
Hour meter
Emergency stop button
Spin on fuel, engine oil and hydraulic
filters
Toolbox
Tilt open engine enclosure hood with
gas strut assist (lockable)
Indicator lights:
-Battery
-Engine Oil Pressure
-Intake pre-heater
-Engine temperature
-Parking brake on/off
-Hydraulic oil temperature
-Low fuel indicator
-Worklight indicator
-Turn signal indicator
-Fuel guage
-Operator hours