

**DV45 DOUBLE DRUM VIBRATORY ROLLER**  
**US PRICE LIST**

## Standard Equipment

**ENGINE:**

Yanmar 4TNV88  
 Tier 4 Interim certified  
 Horsepower  
     -41 Hp (30 kW) @ 2400 RPM  
 Fuel tank capacity: 15.6 gallons (59 L)

**OPERATOR STRUCTURE:**

Foldable ROPS  
 Iso-mounted operator's platform  
 Instrument panel with vandal guard  
 Lateral shifting suspension seat with  
     -Vinyl  
     -2" retractable seatbelt  
     -Handrails  
 Single lever control with  
     -Ground speed and direction  
     -Vibration on/off control

**DRUM AND CHASSIS:**

Articulated chassis  
 Hydrostatic drive (both drums)  
 54.3" wide x 33.5" diameter with  
     -Chamfered drum edges  
 Drum drive motors  
     -Poclain drum drive motors with  
         fixed displacement  
 Hydraulic oil cooler  
 Dual frequency vibration (hi/lo)  
 Dual drum vibration selections  
     -Front drum only  
     -Both drums  
     -Auto vibration stop in neutral  
 Adjustable Vulcollon scrapers  
     -2 x scrapers per drum  
 Recessed drum drive motors  
 Isolated rubber drum mounts

**TRANSMISSION:**

Variable displacement axial piston  
 drive pump

**ELECTRICAL:**

Batteries - 1 x 12V @ 760 CCA  
 Master disconnect switch  
 Fuse protection cover

**WATER SYSTEM:**

Polyethylene water tank  
 Single water tank  
     - 92.5 gallons (350 L)  
 Pressurized sprinkler system  
 Adjustable sprinkler volume control  
 Two-stage water filtration  
 Water tank drains  
 Sprinkler system on/off switch

**OTHER:**

SAHR service brake  
 Multi disc parking/emergency brake  
 Back-up alarm  
 Lift and tie downs  
 Horn  
 Hour meter  
 Emergency stop button  
 Spin on fuel, engine oil and hydraulic  
     filters  
 Toolbox  
 Tilt open engine enclosure hood with  
     gas strut assist (lockable)  
 Indicator lights:  
     -Battery  
     -Engine Oil Pressure  
     -Intake pre-heater  
     -Engine temperature  
     -Parking brake on/off  
     -Hydraulic oil temperature  
     -Low fuel indicator  
     -Worklight indicator  
     -Turn signal indicator  
     -Fuel guage  
     -Operator hours

<b>DV45 DOUBLE DRUM VIBRATORY ROLLER US PRICE LIST</b>
--

## Standard Equipment

DV45CC Combi

FRONT STEEL DRUM, REAR RUBBER

TIRES, CHASSIS:

- Articulated chassis

- Hydrostatic drive

- 1 Front steel drum

- 54.3" wide by 33.5" diameter with

  - Chamfered drum edges

- 4 Rear rubber tires 10.5/80-16

- Drive motors

  - Poclain drive motors with fixed displacement

  - Recessed design

- Hydraulic oil cooler

- Dual frequency vibration (hi/low)

  - front drum only

- Front drum vibration selections

  - Front drum only

  - Auto vibration stop in neutral

- 2 adjustable Vulcollon scrapers

  - (Front Drum)

- Isolated rubber drum mounts

  - (Front Drum)