

COMPACTION ROLLERS

6000

- High Performance
- Excellent Visibility
- Best in Class Operator Comfort
- Long Working Life
- Optimized for Serviceability
- Available with Steel or Combination Drums





	COMPACTIO	N ROLLERS	
OPERATION	6000	DRUMS	6000
Engine	24 hp Kubota	Front	'
Brakes-Service	Hydrostatic	Thickness	0.5"
Brakes-Parking	Yes	Width	47"
Drive System		Diameter	26"
Travel Speed	0-10 mph		
Fuel Capacity	12 gal	Rear: Thickness	0.4"
Hydraulic Oil Capacity	10.5 gal	Width:	47"
Water Capacity	54 gal	Diameter	26"
Steering	Gear pump with constant displacement		
		WATER SYSTEM	
DIMENSIONS		Tank	54 Gal
Length	98.5"	Туре	Pressurized
Width	52.75"	Scrapers	Spring Loaded Rubber
Height (w/o ROPS/Cab)	68.75"		
Wheelbase	67"		
Curb Clearance	21.8"	COMPACTIVE EFFECT	
		Amplitude	0.020"
Turning Radius	8.5' / 12.5' (inside/outside)	Vibration (VPM)	3,960/3,660 vpm
		Centrifugal Force	7,600/6,500 lbs
WEIGHT			
Operating Weight	5,700 Lbs	OPTIONAL EQUIPMENT	
Max Operating Weight	6,000 Lbs	Combination Steel/Rubber	
			Feb-18

Calder Brothers Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacture at any time without notice or obligation.

Sold & Serviced by:



Calder Brothers Corporation 250 E. Warehouse Ct. Taylors, SC 29687 Phone (864) 244-4800 Fax (864) 244-5007 www.CalderBrothers.com