

FEEDER MOBILE STACKER

THE EDGE FMS MOBILE HOPPER FEEDER IS DESIGNED FOR OPERATORS WHO EITHER REQUIRE A CONTROLLED FLOW OF MATERIAL OUTPUT OR NEED TO FEED DIRECTLY USING AN EXCAVATOR OR WHEEL LOADER

[REQUEST A QUOTE](#)



The EDGE FMS mobile hopper feeder is designed for operators who either require a controlled flow of material output or need to feed directly using an excavator or wheel loader. Incorporating a high torque variable speed feed conveyor and various discharge conveyor lengths ranging from 30ft to 75ft, EDGE's mobile feed stockpilers effectively eliminates the need to have both a separate hopper feed unit and a stacker unit.

With its excellent ability to hold a buffer of material; the EDGE mobile hopper feeders can regulate the flow of material ensuring it is the perfect partner for barge, train and truck loading or to feed screeners and crushers. With various power-source options and infinite number of add on options such as an overband magnet, wireless remote functionality and radio reject grid; the mobile feed stacker is ideal for numerous applications. As with all EDGE Innovate's material handling range; the feeder stacker series can be customised to suit the client's specific requirements.

FEEDER MOBILE STACKER FEATURES

[REQUEST FREE QUOTE](#)

[DOWNLOAD BROCHURE](#)



- Can accept loads directly from excavator, wheel loader, crushers or screener
- Eliminates the need for double handling of material, reducing labour and maintenance costs
- Impressive stockpiling rates from 100 -1000+ tonnes per hour
- Variable speed belt feeder to ensure efficient material transfer from hopper to discharge conveyor
- Improved material quality by reduced compaction, degradation, segregation and contamination
- Various hopper options depending on operators loading method or application
- Discharge heights of up to 10.3m (33'11")
- Conical stockpile capacity of up to 1780m³ (2328 yds³)

CHOOSE MODEL:

FMS65 **FMS75**

WEIGHT

15.23 TONNE (16.7UST)

TRANSPORT LENGTH

TRANSPORT WIDTH

2.55M (8'6")

TRANSPORT HEIGHT

W

2'

TI

APPLICATIONS

- Aggregates
- Coal
- Compost
- Construction and demolition waste (C&D)
- Food products
- Mulch
- Sand and gravel

OPTIONS

Discharge conveyor lengths from 9m to 23m (30-75')

Power-source options: Diesel/Hydraulic, Electric/Hydraulic, Dual Power, Direct Electric, Diesel Genset

Hydraulic / manual tipping grid

Two deck vibrating grid with remote tipping

Shredder unit

Over-band magnet

Remote stop/start feeder

Feed and discharge conveyor widths from 40" to 48"

Complete remote functionality

Fold down head section for barge/train wagon loading

Jack legs to enable radial stockpiling.

Various hopper liners

Hopper crash box

Hopper extensions

Full, 1/2 and quarter length rubber conveyor skirting available

Various belt types and plies available

Variable speed discharge conveyor

PRODUCT GALLERY

CLICK TO VIEW