PSMU-600/PSMU-1000 **MAINTENANCE UNITS**

- 600 Gallon Tank with 30 GPM Hydraulically Driven Pump
 - ▶ 18 HP Engine, 8' Circulating Spraybar, Solvent Tank
 - Hand Spray with 40' Hose and Reel
 - Single Diesel Burner with Thermostat Control
- 1000 Gallon Tank with 150 GPM Hydraulically Driven Pump
 - > 27 HP Engine, 12' Circulating Spraybar, Solvent Tank
 - Hand Spray with 40' Hose and Reel
 - Single Diesel Burner with Thermostat Control





PRECISION SPRAY 600 gallon Maintenance Unit with:

600 Gallon, 7,000lbs Tandem Rubber Torsion Axle Trailer Mount Distributor - Single Flue, Diesel Fired with Kohler CH-18 Pintle Hitch, Dial Thermometer, Stop/Turn/Tail Lights Spray Bar, Wash Down Solvent Tank, Clean-Out, 25' Hand Spray Wand, Electric Brakes and safety chains Thermostatic Control, Hydrostatic Powered 30 GPM Pump, 8' Spray bar Full Circulating, Key Fob Operated 18 HP, 2 cyl. Electric Start 38ci/624cc Gasoline Engine

Model
Size
Tank
Dimension

PSMU-600 600 gallon 49 x 74 x 64

PRECISION SPRAY 1000 gallon Maintenance Unit with:

Rubber Torsion Axles, Pintle Hitch, Rear Tank Gauge, Dial Thermometer, Stop/Turn/Tail Lights 1000 Gallon Tandem Axle Trailer Mount Distributor - Single Flue, Diesel Fired with Thermostatic Clean-Out, 25' Hand Spray Wand, 27 hp Diesel Engine, Requires Truck Air Supply, (2) 7,000lb Control, 150 GPM Pump, 12' Spray bar Full Circulating (2/8/2 - Mechanical Fold Down), Wash Down.

_	odel	
Tank	Size	
	Tank I	

PSMU-1000

1000 gallon

49 x 74 x 96

Calder Brothers Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacture at any time without notice or obligation

Sold & Serviced by:



Calder Brothers Corporation 250 E. Warehouse Ct. Taylors, SC 29687 Phone (864) 244-4800 Fax (864) 244-5007 www.CalderBrothers.com