

## FELLING TRAILERS, INC.

1525 Main Street South, Sauk Centre, MN 563 Phone: 800-245-2809 - www.felling.com



4500-A

FT-10 CL		Compact Loader Trailer	r
GVWR LBS:	GAWR LBS:	WEIGHT LBS:	CAPACITY LBS:
9,980	10,160	2,500	7,480

• 14" Solid Steel Pan Sides





Shown with optional spare wheel and tire mounted

Standard & Other (	Options Description	Std. Option	Std. Qty	y. Unit
Frame Type	Pan Style with 14" Sides	Х	1.00	Std
Deck Length	Main Deck Length	Х	14.00	Feet
Deck Type	Pressure Treated Wood	Х	1.00	Std
Ramps; Rear	52" L X 76" W Full Width Mesh Top (Exp Metal 1-1/2 x 6#) with Spring Assist	Х	1.00	Std
Appx Deck Height	16" Loaded, 18" Unloaded	Х	1.00	Inches
Width	102" OD 79" ID	Х	1.00	Inches
Tie Downs	D-Rings, 5/8" (6 on each side & 2 in the front)	Х	14.00	Each
Brakes	Electric, Dexter FSA (Fwd Self Adj) On All Axles	Х	1.00	Std
Axles	6K Dexter, Drop	Х	2.00	Std
Axles, Acc	Dexter EZ-Lube Hubs	Х	1.00	Std
Suspension	Dexter Spring	Х	1.00	Std
Tires & Wheels	ST225/75R 15 D, 6 Bolt [15 x 6] White Mod	Х	4.00	Std
Hitch Length	Center of Coupler to Headboard, Appx	Х	5.00	Feet
Hitch Type	2 5/16" Ball Adjustable, [B] 21,000 lb Plate Mount	Х	1.00	Std
Jack	7K Drop Leg ** Top Wind **	Х	1.00	Std
Plug	7 Pole RV	Х	1.00	Std
Lights	LED Lights (Peterson), Sealed Wiring Harness (Sealco)	Х	1.00	Std
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	Х	1.00	Std
Stripe Color	White	Х	1.00	Std
Standard	(1) Land Leveler/Land Plain Storage with 2 D-Rings	Х	1.00	Std
Standard	(1) Pallet Fork Holders with D-Rings	Х	1.00	Std
Standard	(1) Removable Trencher/Auger Tray (Appx 43" x 78" with Plywood Floor)	Х	1.00	Std
Standard	(3) Auger Bit Holders	х	1.00	Std

Prices subject to change without notice. Pricing Listed in US Dollars. Capacity calculated with proper load placement and hitch transfer to tow vehicle.



## FELLING TRAILERS, INC.



4500-A

1525 Main Street South, Sauk Centre, MN 563 ISO 9001 Certified Quality Management System • WBENC-Certified WBE | THE TRAILER EXPERTS - SINCE 1974 Phone: 800-245-2809 - www.felling.com

Standard	3/8" Safety Chains, Grade 70	х	1.00	Std
Standard	4" Trencher tray spacers (Qty. 5 Standard)	Х	1.00	Std
Standard	Mesh in Tongue	Х	1.00	Std
GVWR	Derated to 9,980 lbs	Х	1.00	Std