

HOT DIP GALVANIZING AVAILABLE ON ALL MODELS.

Drop-Deck Standard Specifications		Deck Length (starting)	Deck Width	Trailer Weight (Approx.)	Deck Height (loaded)	Frame	Cross- members	Axles	Wheels & Tires	Ramps	Jack	GVWR (lbs.)
FT-10	E	16' (4.87 m.)	102" OD, 82" ID	2,500 lbs. / 1,134 kg.	20" (50.8 cm.)	6" Struc. Chan.	3" Jr. I	(2) 6K Dexter, Drop	ST225/75R15 D, 6 bolt	5' x 14" Spring Assist	7K	9,980 lbs. ***
	I	16' (4.87 m.)	102" OD, 82" ID	2,980 lbs. / 1,351 kg.	19" (48.3 cm.)	6 x 12# I-Beam	3" Jr. I	(2) 7K Dexter, Drop	ST235/80R16 E, 8 bolt	5' x 16" Spring Assist	12K	9,980 lbs. ***
	L	16' (4.87 m.)	102" OD, 81" ID	2,500 lbs. / 1,134 kg.	19" (48.3 cm.)	6"x4"x3/8" angle iron	3" Jr. I	(2) 6K Dexter, Straight	ST225/75R15 D, 6 bolt	5' x 14" Spring Assist	7K	9,980 lbs. ***
	Pan	16' (4.87 m.)	102" OD, 79" ID	2,500 lbs. / 1,134 kg.	15" (38.1 cm.)	8" pan sides	4" & 3" Jr. I	(2) 6K Dexter, Drop	ST225/75R15 D, 6 bolt	5' x 16" Spring Assist	7K	9,980 lbs. ***
FT-12	E	16' (4.87 m.)	102" OD, 82" ID	2,700 lbs. / 1,224 kg.	21" (53.3 cm.)	7" Struc. Chan.	3" Jr. I	(2) 6K Dexter, Drop	ST235/80R16 E, 8 bolt	5' x 14" Spring Assist	12K	14,700 lbs.
	I	16' (4.87 m.)	102" OD, 82" ID	2,980 lbs. / 1,351 kg.	19" (48.3 cm.)	6 x 12# I-Beam	3" Jr. I	(2) 7K Dexter, Drop	ST235/80R16 E, 8 bolt	5' x 16" Spring Assist	12K	14,980 lbs.
	L	16' (4.87 m.)	102" OD, 81" ID	2,700 lbs. / 1,224 kg.	20" (50.8 cm.)	6"x4"x3/8" angle iron	3" Jr. I	(2) 6K Dexter, Straight	ST235/80R16 E, 8 bolt	5' x 14" Spring Assist	12K	14,700 lbs.
	Pan	16' (4.87 m.)	102" OD, 79" ID	2,700 lbs. / 1,224 kg.	16" (40.6 cm.)	10" pan sides	4" & 3" Jr. I	(2) 6K Dexter, Drop	ST235/80R16 E, 8 bolt	5' x 16" Spring Assist	12K	14,700 lbs.
FT-14	E	16' (4.87 m.)	102" OD, 82" ID	3,200 lbs. / 1,451 kg.	21" (53.3 cm.)	7" Struc. Chan.	3" Jr. I	(2) 7K Dexter, Drop	ST235/80R16 E, 8 bolt	6' x 14.5" Spring Assist	12K	17,200 lbs.
	I	16' (4.87 m.)	102" OD, 82" ID	3,600 lbs. / 1,632 kg.	21" (53.3 cm.)	8 x 15# I-Beam	3" Jr. I	(2) 7K HD Dexter, Drop	215/75R17.5 H 8 Bolt	6' x 16" Spring Assist	12K	17,600 lbs.
	L	16' (4.87 m.)	102" OD, 80" ID	3,200 lbs. / 1,451 kg.	20" (50.8 cm.)	7"x4"x3/8" angle iron	3" Jr. I	(2) 7K Dexter, Straight	ST235/80R16 E, 8 bolt	6' x 14.5" Spring Assist	12K	17,200 lbs.
	Pan	16' (4.87 m.)	102" OD, 79" ID	3,200 lbs. / 1,451 kg.	16" (40.6 cm.)	10" pan sides	4" & 3" Jr. I	(2) 7K Dexter, Drop	ST235/80R16 E, 8 bolt	6' x 16" Spring Assist	12K	17,200 lbs.
FT-16	E	18' (5.49 m.)	102" OD, 81" ID	3,600 lbs. / 1,632 kg.	23" (58.4 cm.)	8" H-Beam	4" Jr. I	(2) 8K Dexter, Oil Bath	215/75R17.5 H 8 Bolt	6' x 14.5" Spring Assist	12K	19,600 lbs.
	I	18' (5.49 m.)	102" OD, 83" ID	4,000 lbs. / 1,814 kg.	24" (60 cm.)	10 x 15# I-Beam	4" Jr. I	(2) 8K Dexter, Oil Bath	215/75R17.5 H 8 Bolt	6' x 16" Spring Assist	12K	20,000 lbs.
	Pan	18' (5.49 m.)	102" OD, 77" ID	3,600 lbs. / 1,632 kg.	16" (40.6 cm.)	12" pan sides	4" & 3" Jr. I	(2) 8K Dexter, Oil Bath	215/75R17.5 H 8 Bolt	6' x 16" Spring Assist	12K	19,600 lbs.
FT-20**	E	20' (6.09 m.)	102" OD, 82" ID	4,000 lbs. / 1,814 kg.	24.5" (62.2 cm.)*	8" H-Beam	4" Jr. I	(2) 10K Dexter, Oil Bath	235/75R17.5 J 8 Bolt	6' x 14.5" Spring Assist	12K	24,000 lbs.
	I	20' (6.09 m.)	102" OD, 82" ID	4,600 lbs. / 2,086 kg.	24" (60 cm.)	10 x 17# I-Beam	4" Jr. I	(2) 10K Dexter, Oil Bath	235/75R17.5 J 8 Bolt	6' x 16" Spring Assist	12K	24,600 lbs.
FT-24**	I	20' (6.09 m.)	102" OD, 82" ID	4,900 lbs. / 2,222 kg.	24" (60 cm.)	10 x 17# I-Beam	4" Jr. I	(2) 12K Dexter, Oil Bath	235/75R17.5 J 8 Bolt	6' x 16" Spring Assist	12K	25,900 lbs.
FT-24-3	E	20' (6.09 m.)	102" OD, 82" ID	4,000 lbs. / 1,814 kg.	22" (55.8 cm.)	8" H-Beam	4" Jr. I	(3) 8K Dexter, Oil Bath	215/75R17.5 H 8 Bolt	6' x 14.5" Spring Assist	12K	28,000 lbs.

*With optional drop torsion axle **Available with Spring Suspension *** FT-10 - GVWR of 12,980 with conspicuity tape option

Additional lengths available • Measurements are approximate • Some models may be shown with optional equipment • All specifications are subject to change

CUSTOMIZATION: *Definition* - To modify or build according to individual or personal specifications or preference.

Felling Trailers believes that **"It's All In The Details"** when it comes to building a trailer. We build trailers to accommodate your equipment and to suit your needs, right down to the last detail. The options and features are limitless...contact Felling Trailers to design the trailer that is right for you. Felling Your Trailer **EXPERTS**.

Your **FELLING TRAILERS** Dealer:

Join Us Online



FELLING TRAILERS

Manufactured & Distributed by: **Felling Trailers, Inc.**

1525 Main St. S. • Sauk Centre, MN 56378

(320) 352-5239 • (320) 352-5230 FAX

Visit us online at **www.felling.com**

E-mail us at: **trailers@felling.com**

Call 1-800-245-2809

for your nearest dealer.

