## **FELLING TRAILERS, INC.**

Product Sheet

1525 Main Street South, Sauk Centre, MN 563 Phone: 800-245-2809 - www.felling.com 4500-A


## **FT-12 EZ-T**

## Tilts - Drop Deck EZ Tilt Series

 GVWR LBS:
 GAWR LBS:
 WEIGHT LBS:
 CAPACITY LBS:

 13,800
 14,000
 3,500
 10,300

- Rotating Torsion Suspension
- Elec/Hydraulic Lift System with Corded Remote
- 3.5' Approach Plate
- Winch Mount under Deck is Standard
- 5 Degree Load Angle





Deck Length       Tilt Deck Length (15' deck + 3.5' Smooth Steel Approach)       X         Deck Type       Anti-Skid Paint Applied to Approach plate       X         Deck Type       Pressure Treated Wood       X	18.50 1.00 1.00	Feet Std Std
Deck Type Pressure Treated Wood X		
	1.00	Std
		Jiu
Appx Deck Height 20.5" Unloaded X	1.00	Inches
Width 102" OD, 75.5" ID (Between axle mounts) X	1.00	Inches
Tie Downs D-Rings, 5/8" Straight X	8.00	Each
Brakes Electric, FSA (Fwd Self Adj) On All Axles X	1.00	Std
Axles 7K Drop X	2.00	Std
Axles, Acc SuperLube Hubs X	1.00	Std
Suspension Rotating, Torsion X	1.00	Std
Tires & Wheels ST235/80R 16 E, 8 Bolt [16 x 6] White Mod X	4.00	Std
Hitch Length Center of Coupler to Headboard, Appx X	6.00	Feet
Hitch Type 2 5/16" Ball Adjustable, [B] 20,000 lb Channel Mount, Range 15.5" to 23.5" X	1.00	Std
Hitch Height Approximate Adjustment Hitch Range 15.5" to 23.5" X	1.00	Std
Jack 12K Drop Leg Spring Foot ** Side Wind ** X	1.00	Std
Plug 7 Pole RV X	1.00	Std
Lights 4 Tail Light System, LED, Sealed Wiring Harness X	1.00	Std
Trailer Color Felling Black # CCA945378 (White Felling Decal) X	1.00	Std
Standard Elec/Hydraulic Pump with Corded Remote and 12 V Battery in Lockable Enclosure X	1.00	Std
Standard Document Holder X	1.00	Std
Standard 3/8" Safety Chains, Grade 70 X	1.00	Std
GVWR 13,800 lbs X	1.00	Std