

#### **FELLING TRAILERS, INC.**

**Product Sheet** 

1525 Main Street South, Sauk Centre, MN 563 Phone: 800-245-2809 - www.felling.com 4500-A

FT-40-2 T

#### Tilts - Deckover

GVWR LBS: 45,520

## **GAWR LBS:**

36,320

WEIGHT LBS:


**CAPACITY LBS:** 

9,200

36,320

- GAWR 36,320 lbs on 215/75R 17.5 H Tires
- 235/75R 17.5 Tires increases GAWR to 40,000 lbs
- 10" H-Beam Main Frame
- 12" Channel Tilt Deck Frame

- 4" I-Beam crossmembers approx 18" oc
- See Option Page for Stationary Deck
- \* NOTE: Dealer must add 12% FET on retail price. Tax is to be calculated & remitted by dealer.





Standard & Other (	Options Description	Std. Option	Std. Qt	y. Unit
Stationary Deck	Stationary Deck	Х	4.00	Feet
Deck Length	Tilt Deck Length (Includes Approx. 12" Approach Plate)	X	25.00	Feet
Deck Type	White Oak	Х	1.00	Std
Appx Deck Height	36" Loaded	X	1.00	Inches
Width	102" OD	X	1.00	Inches
Tie Downs	D-Rings, Bent, 1" Standard w/ Stationary Deck	X	12.00	Std
Brakes	Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)	X	1.00	Std
Axles	25K Oil Bath	X	2.00	Std
Suspension	49" Spread (Spring), 9700 Hutch	X	1.00	Std
Tires & Wheels	215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Hub Pilot	X	8.00	Std
Hitch Length	Center of Coupler to Headboard, Appx	X	5.00	Feet
Hitch Type	3" Adjustable Lunette Eye/Pintle, [C] 66,000 lb Plate Mount (3/4" Bolt)	X	1.00	Std
Jack	25K Drop Leg 2 Speed	X	1.00	Std
Plug	7 Pole Semi	X	1.00	Std
Lights	LED Lights (Peterson), Sealed Wiring Harness (Sealco)	X	1.00	Std
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	X	1.00	Std
Stripe Color	White	X	1.00	Std
Standard	1/2" Safety Chains, Grade 70	X	1.00	Std
Standard	2 Steps,1 on the Standard Hitch and 1 in front of Axles on Roadside	X	2.00	Std
Standard	Document Holder	Х	1.00	Std
Standard	Tool Box, with Lockable Cover	Х	1.00	Std
Standard	Single Self Actuating Hydraulic Cushion Cylinder	X	1.00	Std
Standard	Air bag assist tilt (up only)	X	1.00	Std



# FELLING TRAILERS, INC.

### **Product Sheet**

1525 Main Street South, Sauk Centre, MN 563

4500-A

Standard	Air Operated Lock Mechanism	Χ	1.00	Std
Standard	Hydraulic Tank with Locking Tilt Valve	Х	1.00	Std
GVWR	45,520 lbs	Χ	1.00	Std