

## FELLING TRAILERS, INC.

Product Sheet

1525 Main Street South, Sauk Centre, MN 563 Phone: 800-245-2809 - www.felling.com 4500-A

FT-14 I

**DD I Series** 

GVWR LBS:

GAWR LBS:

WEIGHT LBS:

**CAPACITY LBS:** 


16,100

14,000

3,600

12,500

- 8x15# I-beam Main Frame
- 3" (80K) Jr I-beam crossmembers
- 18" on center





· Shown with optional dovetail & lip up

Deck Length         Main Deck Length         X         1.6.0         Feet           Deck Type         White Oak 2" Nom         X         1.00         Std           Ramps; Rear         6" x 16" Angle Iron Spring Assist         X         1.00         Pair           Ramps, Acc         Full Width Ramp Rod         X         1.00         Std           Appx Deck Height         21" Loaded, 24" Unloaded         X         1.00         Inches           Width         102" OD, 82" ID         X         1.00         Inches           Width         102" OD, 82" ID         X         1.00         Inches           Tie Downs         D-Rings, 5/8" Straight         X         8.00         Std           Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X         1.00         Std           Axles         7K Heavy Duty Dexter, Drop         X         2.00         Std           Axles, Acc         Dexter EZ-Lube Hubs         X         1.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         1.00         Std           Hitch Length         Center of Cou	Standard & Other C	Options Description	Std. Option	Std. Qty	. Unit
Ramps, Rear         6' x 16" Angle Iron Spring Assist         X         1.00         Pair           Ramps, Acc         Full Width Ramp Rod         X         1.00         Std           Appx Deck Height         21" Loaded, 24" Unloaded         X         1.00         Inches           Width         102" OD, 82" ID         X         1.00         Inches           Width         102" OD, 82" ID         X         1.00         Inches           Tie Downs         D-Rings, 5/8" Straight         X         8.00         Std           Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X         1.00         Std           Axles         7K Heavy Duty Dexter, Drop         X         2.00         Std           Axles, Acc         Dexter EZ-Lube Hubs         X         1.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)         X         1.00         Std	Deck Length	Main Deck Length	X	16.00	Feet
Ramps, Acc         Full Width Ramp Rod         X         1.00         Std           Appx Deck Height         21" Loaded, 24" Unloaded         X         1.00         Inches           Width         102" OD, 82" ID         X         1.00         Inches           Tie Downs         D-Rings, 5/8" Straight         X         8.00         Std           Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X         1.00         Std           Axles         7K Heavy Duty Dexter, Drop         X         2.00         Std           Axles, Acc         Dexter EZ-Lube Hubs         X         1.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind **	Deck Type	White Oak 2" Nom	Χ	1.00	Std
Appx Deck Height         21" Loaded, 24" Unloaded         X         1.00         Inches           Width         102" OD, 82" ID         X         1.00         Inches           Tie Downs         D-Rings, 5/8" Straight         X         8.00         Std           Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X         1.00         Std           Axles         7K Heavy Duty Dexter, Drop         X         2.00         Std           Axles, Acc         Dexter EZ-Lube Hubs         X         1.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind **         X         1.00         Std           Plug         7 Pole RV         X	Ramps; Rear	6' x 16" Angle Iron Spring Assist	Χ	1.00	Pair
Width         102" OD, 82" ID         X         1.00         Inches           Tie Downs         D-Rings, 5/8" Straight         X         8.00         Std           Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X         1.00         Std           Axles         7K Heavy Duty Dexter, Drop         X         2.00         Std           Axles, Acc         Dexter EZ-Lube Hubs         X         1.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot * * Side Wind **         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         4 Tail Light System, LED, Sealed Wiring Harness         <	Ramps, Acc	Full Width Ramp Rod	Х	1.00	Std
Tie Downs         D-Rings, 5/8" Straight         X         8.00         Std           Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X         1.00         Std           Axles         7K Heavy Duty Dexter, Drop         X         2.00         Std           Axles, Acc         Dexter EZ-Lube Hubs         X         1.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind **         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         4 Tail Light System, LED, Sealed Wiring Harness         X         1.00         Std           Standard         3/8" Safety Chains, Grade 70 <td>Appx Deck Height</td> <td>21" Loaded, 24" Unloaded</td> <td>Х</td> <td>1.00</td> <td>Inches</td>	Appx Deck Height	21" Loaded, 24" Unloaded	Х	1.00	Inches
Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X         1.00         Std           Axles         7K Heavy Duty Dexter, Drop         X         2.00         Std           Axles, Acc         Dexter EZ-Lube Hubs         X         1.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind **         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         4 Tail Light System, LED, Sealed Wiring Harness         X         1.00         Std           Trailer Color         Felling Black # CCA945378 (White Felling Decal)         X         1.00         Std           Standard         Do	Width	102" OD, 82" ID	Х	1.00	Inches
Axles         7K Heavy Duty Dexter, Drop         X         2.00         Std           Axles, Acc         Dexter EZ-Lube Hubs         X         1.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind **         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         4 Tail Light System, LED, Sealed Wiring Harness         X         1.00         Std           Trailer Color         Felling Black # CCA945378 (White Felling Decal)         X         1.00         Std           Standard         Document Holder         X         1.00         Std	Tie Downs	D-Rings, 5/8" Straight	Х	8.00	Std
Axles, Acc         Dexter EZ-Lube Hubs         X         1.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind **         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         4 Tail Light System, LED, Sealed Wiring Harness         X         1.00         Std           Trailer Color         Felling Black # CCA945378 (White Felling Decal)         X         1.00         Std           Standard         3/8" Safety Chains, Grade 70         X         1.00         Std           Standard         Document Holder         X         1.00         Std	Brakes	Electric, Dexter FSA (Fwd Self Adj) On All Axles	Х	1.00	Std
Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind **         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         4 Tail Light System, LED, Sealed Wiring Harness         X         1.00         Std           Trailer Color         Felling Black # CCA945378 (White Felling Decal)         X         1.00         Std           Standard         3/8" Safety Chains, Grade 70         X         1.00         Std           Standard         Document Holder         X         1.00         Std	Axles	7K Heavy Duty Dexter, Drop	Х	2.00	Std
Tires & Wheels 215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel X 4.00 Each Hitch Length Center of Coupler to Headboard X 5.00 Feet Hitch Type 2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt) X 1.00 Std Hitch Height Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd) X 1.00 Std Jack 12K Drop Leg Spring Foot ** Side Wind ** X 1.00 Std Plug 7 Pole RV X 1.00 Std Lights 4 Tail Light System, LED, Sealed Wiring Harness X 1.00 Std Trailer Color Felling Black # CCA945378 (White Felling Decal) X 1.00 Std Standard 3/8" Safety Chains, Grade 70 X 1.00 Std Standard Document Holder X 1.00 Std	Axles, Acc	Dexter EZ-Lube Hubs	Х	1.00	Std
Hitch Length Center of Coupler to Headboard X 5.00 Feet Hitch Type 2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt) X 1.00 Std Hitch Height Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd) X 1.00 Std  Jack 12K Drop Leg Spring Foot ** Side Wind ** X 1.00 Std  Plug 7 Pole RV X 1.00 Std  Lights 4 Tail Light System, LED, Sealed Wiring Harness X 1.00 Std  Trailer Color Felling Black # CCA945378 (White Felling Decal) X 1.00 Std  Standard 3/8" Safety Chains, Grade 70 X 1.00 Std  Standard Document Holder X 1.00 Std	Suspension	Dexter Spring, 36" Spread	Х	1.00	Std
Hitch Type 2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt) X 1.00 Std  Hitch Height Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd) X 1.00 Std  Jack 12K Drop Leg Spring Foot ** Side Wind ** X 1.00 Std  Plug 7 Pole RV X 1.00 Std  Lights 4 Tail Light System, LED, Sealed Wiring Harness X 1.00 Std  Trailer Color Felling Black # CCA945378 (White Felling Decal) X 1.00 Std  Standard 3/8" Safety Chains, Grade 70 X 1.00 Std  Standard Document Holder X 1.00 Std	Tires & Wheels	215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel	Х	4.00	Each
Hitch Height         Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind **         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         4 Tail Light System, LED, Sealed Wiring Harness         X         1.00         Std           Trailer Color         Felling Black # CCA945378 (White Felling Decal)         X         1.00         Std           Standard         3/8" Safety Chains, Grade 70         X         1.00         Std           Standard         Document Holder         X         1.00         Std	Hitch Length	Center of Coupler to Headboard	Х	5.00	Feet
Jack         12K Drop Leg Spring Foot ** Side Wind **         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         4 Tail Light System, LED, Sealed Wiring Harness         X         1.00         Std           Trailer Color         Felling Black # CCA945378 (White Felling Decal)         X         1.00         Std           Standard         3/8" Safety Chains, Grade 70         X         1.00         Std           Standard         Document Holder         X         1.00         Std	Hitch Type	2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)	Х	1.00	Std
Plug         7 Pole RV         X         1.00         Std           Lights         4 Tail Light System, LED, Sealed Wiring Harness         X         1.00         Std           Trailer Color         Felling Black # CCA945378 (White Felling Decal)         X         1.00         Std           Standard         3/8" Safety Chains, Grade 70         X         1.00         Std           Standard         Document Holder         X         1.00         Std	Hitch Height	Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd)	Х	1.00	Std
Lights 4 Tail Light System, LED, Sealed Wiring Harness X 1.00 Std  Trailer Color Felling Black # CCA945378 (White Felling Decal) X 1.00 Std  Standard 3/8" Safety Chains, Grade 70 X 1.00 Std  Standard Document Holder X 1.00 Std	Jack	12K Drop Leg Spring Foot ** Side Wind **	Х	1.00	Std
Trailer ColorFelling Black # CCA945378 (White Felling Decal)X1.00StdStandard3/8" Safety Chains, Grade 70X1.00StdStandardDocument HolderX1.00Std	Plug	7 Pole RV	Х	1.00	Std
Standard 3/8" Safety Chains, Grade 70 X 1.00 Std Standard Document Holder X 1.00 Std	Lights	4 Tail Light System, LED, Sealed Wiring Harness	Х	1.00	Std
Standard Document Holder X 1.00 Std	Trailer Color	Felling Black # CCA945378 (White Felling Decal)	Х	1.00	Std
	Standard	3/8" Safety Chains, Grade 70	Х	1.00	Std
GVWR 16,100 lbs X 1.00 Std	Standard	Document Holder	Х	1.00	Std
	GVWR	16,100 lbs	Х	1.00	Std