

## **FELLING TRAILERS, INC.**

Product Sheet

1525 Main Street South, Sauk Centre, MN 563 Phone: 800-245-2809 - www.felling.com 4500-A

## FT-16 IT-I

## **DD IT-I Series**

**GVWR LBS:** 

GAWR LBS:

WEIGHT LBS:

**CAPACITY LBS:** 

18,400


16,000

4,200

14,200

- 8x15# I-beam Main Frame
- 3" (80K) Jr I-beam crossmembers
- 17" Avg on center

- (2) Cushion Cylinders
- Deck Length = Tilt Angle
- 14' = 17 Degrees 16' = 15 Degrees
- 18' = 13 Degrees 20' = 12 Degress





• Shown with optional aluminum wheels, medium toolbox, and Ruby Red Metallic paint

Stationary Deck         Stationary Deck         X 4.00 Feet           Deck Length         Tilt Deck Length (Includes 2' Steel Punch Plate Approach)         X 16.00 Feet           Deck Type         White Oak 2" Nom         X 1.00 Std           Appx Deck Height         22.5" Loaded, 24.5" Unloaded         X 1.00 Inches           Width         102" OD, 81" ID         X 1.00 Inches           Width         102" OD, 81" ID         X 1.00 Std           Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X 10.00 Std           Axles         8K Dexter Oil Bath Drop         X 2.00 Std           Suspension         Dexter Spring, 36" Spread         X 1.00 Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X 4.00 Each           Hitch Length         Center of Coupler to Headboard         X 5.00 Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt),         X 1.00 Std           Jack         12K Drop Leg Spring Foot ** Side Wind **         X 1.00 Std           Plug         7 Pole RV         X 1.00 Std           LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders)         X 1.00 Std           Standard         3/8" Safety Chains, Grade 70         X 1.00 Std           Standard<	Standard & Other C	Options Description	Std. Option	Std. Qty	. Unit
Deck Type         White Oak 2" Nom         X         1.00         Std           Appx Deck Height         22.5" Loaded, 24.5" Unloaded         X         1.00         Inches           Width         102" OD, 81" ID         X         1.00         Inches           Tie Downs         D-Rings, 5/8 Straight         X         10.00         Std           Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X         1.00         Std           Axles         8K Dexter Oil Bath Drop         X         2.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt),         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind **         X         1.00         Std           Plug         7 Pole RV         X	Stationary Deck	Stationary Deck	Х	4.00	Feet
Appx Deck Height         22.5" Loaded, 24.5" Unloaded         X         1.00         Inches           Width         102" OD, 81" ID         X         1.00         Inches           Tie Downs         D-Rings, 5/8 Straight         X         10.00         Std           Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X         1.00         Std           Axles         8K Dexter Oil Bath Drop         X         2.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt),         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind ***         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         LED,4 tail light system, Sealed Wining Harness	Deck Length	Tilt Deck Length (Includes 2' Steel Punch Plate Approach)	Χ	16.00	Feet
Width         102" OD, 81" ID         X         1.00         Inches           Tie Downs         D-Rings, 5/8 Straight         X         10.00         Std           Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X         1.00         Std           Axles         8K Dexter Oil Bath Drop         X         2.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt),         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind **         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders)         X         1.00         Std           Standard <td< td=""><td>Deck Type</td><td>White Oak 2" Nom</td><td>Х</td><td>1.00</td><td>Std</td></td<>	Deck Type	White Oak 2" Nom	Х	1.00	Std
Tie Downs         D-Rings, 5/8 Straight         X         10.00         Std           Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X         1.00         Std           Axles         8K Dexter Oil Bath Drop         X         2.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt),         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind ***         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders)         X         1.00         Std           Standard         3/8" Safety Chains, Grade 70         X         1.00         Std           Standard <td>Appx Deck Height</td> <td>22.5" Loaded, 24.5" Unloaded</td> <td>Х</td> <td>1.00</td> <td>Inches</td>	Appx Deck Height	22.5" Loaded, 24.5" Unloaded	Х	1.00	Inches
Brakes         Electric, Dexter FSA (Fwd Self Adj) On All Axles         X         1.00         Std           Axles         8K Dexter Oil Bath Drop         X         2.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt),         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind **         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders)         X         1.00         Std           Standard         3/8" Safety Chains, Grade 70         X         1.00         Std           Standard         Document Holder         X         1.00         Std	Width	102" OD, 81" ID	Х	1.00	Inches
Axles         8K Dexter Oil Bath Drop         X         2.00         Std           Suspension         Dexter Spring, 36" Spread         X         1.00         Std           Tires & Wheels         215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel         X         4.00         Each           Hitch Length         Center of Coupler to Headboard         X         5.00         Feet           Hitch Type         2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt),         X         1.00         Std           Hitch Height         Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd)         X         1.00         Std           Jack         12K Drop Leg Spring Foot ** Side Wind **         X         1.00         Std           Plug         7 Pole RV         X         1.00         Std           Lights         LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders)         X         1.00         Std           Trailer Color         Felling Black # CCA945378 (White Felling Decal)         X         1.00         Std           Standard         Document Holder         X         1.00         Std	Tie Downs	D-Rings, 5/8 Straight	Х	10.00	Std
Suspension Dexter Spring, 36" Spread X 1.00 Std  Tires & Wheels 215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel X 4.00 Each  Hitch Length Center of Coupler to Headboard X 5.00 Feet  Hitch Type 2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt), X 1.00 Std  Hitch Height Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd) X 1.00 Std  Jack 12K Drop Leg Spring Foot ** Side Wind ** X 1.00 Std  Plug 7 Pole RV X 1.00 Std  Lights LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders) X 1.00 Std  Trailer Color Felling Black # CCA945378 (White Felling Decal) X 1.00 Std  Standard 3/8" Safety Chains, Grade 70 X 1.00 Std	Brakes	Electric, Dexter FSA (Fwd Self Adj) On All Axles	Х	1.00	Std
Tires & Wheels 215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel X 4.00 Each Hitch Length Center of Coupler to Headboard X 5.00 Feet Hitch Type 2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt), X 1.00 Std Hitch Height Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd) X 1.00 Std  Jack 12K Drop Leg Spring Foot ** Side Wind ** X 1.00 Std  Plug 7 Pole RV X 1.00 Std  Lights LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders) X 1.00 Std  Trailer Color Felling Black # CCA945378 (White Felling Decal) X 1.00 Std  Standard 3/8" Safety Chains, Grade 70 X 1.00 Std  Standard Document Holder X 1.00 Std	Axles	8K Dexter Oil Bath Drop	Х	2.00	Std
Hitch Length Center of Coupler to Headboard X 5.00 Feet  Hitch Type 2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt), X 1.00 Std  Hitch Height Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd) X 1.00 Std  Jack 12K Drop Leg Spring Foot ** Side Wind ** X 1.00 Std  Plug 7 Pole RV X 1.00 Std  Lights LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders) X 1.00 Std  Trailer Color Felling Black # CCA945378 (White Felling Decal) X 1.00 Std  Standard 3/8" Safety Chains, Grade 70 X 1.00 Std  Standard Document Holder X 1.00 Std	Suspension	Dexter Spring, 36" Spread	Х	1.00	Std
Hitch Type 2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt), X 1.00 Std  Hitch Height Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd) X 1.00 Std  Jack 12K Drop Leg Spring Foot ** Side Wind ** X 1.00 Std  Plug 7 Pole RV X 1.00 Std  Lights LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders) X 1.00 Std  Trailer Color Felling Black # CCA945378 (White Felling Decal) X 1.00 Std  Standard 3/8" Safety Chains, Grade 70 X 1.00 Std  Standard Document Holder X 1.00 Std	Tires & Wheels	215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel	Х	4.00	Each
Hitch Height Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd) X 1.00 Std  Jack 12K Drop Leg Spring Foot ** Side Wind ** X 1.00 Std  Plug 7 Pole RV X 1.00 Std  Lights LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders) X 1.00 Std  Trailer Color Felling Black # CCA945378 (White Felling Decal) X 1.00 Std  Standard 3/8" Safety Chains, Grade 70 X 1.00 Std  Standard Document Holder X 1.00 Std	Hitch Length	Center of Coupler to Headboard	Х	5.00	Feet
Jack12K Drop Leg Spring Foot ** Side Wind **X1.00StdPlug7 Pole RVX1.00StdLightsLED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders)X1.00StdTrailer ColorFelling Black # CCA945378 (White Felling Decal)X1.00StdStandard3/8" Safety Chains, Grade 70X1.00StdStandardDocument HolderX1.00Std	Hitch Type	2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt),	Х	1.00	Std
Plug7 Pole RVX1.00StdLightsLED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders)X1.00StdTrailer ColorFelling Black # CCA945378 (White Felling Decal)X1.00StdStandard3/8" Safety Chains, Grade 70X1.00StdStandardDocument HolderX1.00Std	Hitch Height	Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd)	Х	1.00	Std
Lights LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders) X 1.00 Std  Trailer Color Felling Black # CCA945378 (White Felling Decal) X 1.00 Std  Standard 3/8" Safety Chains, Grade 70 X 1.00 Std  Standard Document Holder X 1.00 Std	Jack	12K Drop Leg Spring Foot ** Side Wind **	Х	1.00	Std
Trailer ColorFelling Black # CCA945378 (White Felling Decal)X1.00StdStandard3/8" Safety Chains, Grade 70X1.00StdStandardDocument HolderX1.00Std	Plug	7 Pole RV	Х	1.00	Std
Standard 3/8" Safety Chains, Grade 70 X 1.00 Std Standard Document Holder X 1.00 Std	Lights	LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fende	ers) X	1.00	Std
Standard Document Holder X 1.00 Std	Trailer Color	Felling Black # CCA945378 (White Felling Decal)	Х	1.00	Std
	Standard	3/8" Safety Chains, Grade 70	Х	1.00	Std
	Standard	Document Holder	Х	1.00	Std
Standard Dual Cushion Cylinders X 2.00 Std	Standard	Dual Cushion Cylinders	Х	2.00	Std
GVWR 18,400 lbs X 1.00 Std	GVWR	18,400 lbs	Х	1.00	Std