

FELLING TRAILERS, INC.

Product Sheet

1525 Main Street South, Sauk Centre, MN 563 Phone: 800-245-2809 - www.felling.com 4500-A

FT-24 S

Sprayer


GVWR LBS: 30,600

GAWR LBS: 24,000

WEIGHT LBS: 6,600

24,000

• Built Per Customer Specs





Deck Length Main Deck Length X 20.00 Feet Beavertail 30" Length X 2.50 Feet Deck Type 24.5" Wheel Troughs with 53" Open Center X 1.00 Std Ramps, Acc None X 1.00 Std Width 102" OD, 53 ID X 1.00 Inches Tie Downs Tie Loops X 4.00 Std Brakes Electric, Dexter FSA (Fwd Self Adj) On All Axles X 1.00 Std Axles 12K Dexter Oil Bath X 2.00 Std Suspension Dexter Spring X 1.00 Std Tires & Wheels ST235/80R 16 E, 8 Bolt [16 x 6] Hub Pilot X 8.00 Std Hitch Length Center of Coupler to Headboard, Appx X 15.00 Feet
Deck Type 24.5" Wheel Troughs with 53" Open Center X 1.00 Std Ramps, Acc None X 1.00 Std Width 102" OD, 53 ID X 1.00 Inches Tie Downs Tie Loops X 4.00 Std Brakes Electric, Dexter FSA (Fwd Self Adj) On All Axles X 1.00 Std Axles 12K Dexter Oil Bath X 2.00 Std Suspension Dexter Spring X 1.00 Std Tires & Wheels ST235/80R 16 E, 8 Bolt [16 x 6] Hub Pilot X 8.00 Std
Ramps, Acc None X 1.00 Std Width 102" OD, 53 ID X 1.00 Inches Tie Downs Tie Loops X 4.00 Std Brakes Electric, Dexter FSA (Fwd Self Adj) On All Axles X 1.00 Std Axles 12K Dexter Oil Bath X 2.00 Std Suspension Dexter Spring X 1.00 Std Tires & Wheels ST235/80R 16 E, 8 Bolt [16 x 6] Hub Pilot X 8.00 Std
Width 102" OD, 53 ID X 1.00 Inches Tie Downs Tie Loops X 4.00 Std Brakes Electric, Dexter FSA (Fwd Self Adj) On All Axles X 1.00 Std Axles 12K Dexter Oil Bath X 2.00 Std Suspension Dexter Spring X 1.00 Std Tires & Wheels ST235/80R 16 E, 8 Bolt [16 x 6] Hub Pilot X 8.00 Std
Tie Downs Tie Loops X 4.00 Std Brakes Electric, Dexter FSA (Fwd Self Adj) On All Axles X 1.00 Std Axles 12K Dexter Oil Bath X 2.00 Std Suspension Dexter Spring X 1.00 Std Tires & Wheels ST235/80R 16 E, 8 Bolt [16 x 6] Hub Pilot X 8.00 Std
Brakes Electric, Dexter FSA (Fwd Self Adj) On All Axles X 1.00 Std Axles 12K Dexter Oil Bath X 2.00 Std Suspension Dexter Spring X 1.00 Std Tires & Wheels ST235/80R 16 E, 8 Bolt [16 x 6] Hub Pilot X 8.00 Std
Axles 12K Dexter Oil Bath X 2.00 Std Suspension Dexter Spring X 1.00 Std Tires & Wheels ST235/80R 16 E, 8 Bolt [16 x 6] Hub Pilot X 8.00 Std
Suspension Dexter Spring X 1.00 Std Tires & Wheels ST235/80R 16 E, 8 Bolt [16 x 6] Hub Pilot X 8.00 Std
Tires & Wheels
·
Hitch Length Center of Coupler to Headhoard Appy V 15 00 Foot
Thich Length Center of Couplet to Heauboard, Appx
Hitch Type 2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt) X 1.00 Std
Hitch Type, Acc Mesh in Center of Tongue X 1.00 Std
Jack 12K Drop Leg ** Side Wind ** X 1.00 Std
Plug 7 Pole RV X 1.00 Std
Lights LED Lights (Peterson), Sealed Wiring Harness (Sealco) X 1.00 Std
Trailer Color Felling Black # CCA945378 (White Felling Decal) X 1.00 Std
Stripe Color White X 1.00 Std
Standard 1/2" Safety Chains, Grade 70 X 1.00 Std
Standard Document Holder X 1.00 Std