

A PRODUCT OF HI-VAC® CORPORATION

Aquatech model B-15, technical specifications

Debris tank

15 yds. of capacity

56,000# double acting dump hoist

Rear splash plate bumper

Top hinged hydraulic open/close rear door

Four individual hydraulic cylinder door locks

Two debris level sight eyes located in rear door

Stainless steel/rubber boot ball check valve

Pivoting tank support prop, rear door safety prop

6" rear drain valve with 15' x 6" drain hose

Debris tank flush out system

Water tank system

3/8" thick polyethylene UV stabilized water tank

Capacity of 1600 gallons

Curb side fill

Anti-siphon air gap system

Self-cleaning tank design with 2.5" quick drain

Water pump system

80 GPM @ 2000 PSI high pressure water pump

Water filter at pump inlet

Kevlar poly chain drive system

Multi flow water system

Air vac system

PD vacuum system 5000 CFM's and 18" Hg

Kevlar reinforced poly chain drive

Powered by HD horizontal transfer case

Stainless steel micro screen filter

Vacuum relief valves

Boom assembly

Top loading boom design

One piece HD rubber debris hose

Slewing gear power with 360 degree rotation

Double acting dual hydraulic extension system 19' over all reach

Hydraulic power up/down/right/left

Rear boom storage

Boom mounted internal air vac valve

Boom clean out port

Hose reel assembly

Rear mounted hose reel assembly

800' X 1" hose capacity

Hydraulically articulated 180 degree street to curb rotation

Sewer hose 1" x 400' 2500 PSI

20' leader hose

Operating controls, gauges, instruments

6 position Joystick boom control mounted in rear control station

4 position joystick hose reel control mounted in rear control station

Hydraulic control to dump tank open close door at side station

Engine throttle, vacuum pressure gauge

Chassis tachometer

Vacuum gauge

Hose reel speed control

Water pressure gauge

Electronic engine throttle control

Low water warning alarm

Wireless remote system

Boom un-stowed alarm system

Back up alarm

Also includes the following optional equipment

Fenders & mud flaps

Rear tow hooks

One flexible hose guide (tiger tail) with storage

One 8" X 6' intake tube with clamp and gasket

One 6' X 8" extension tube with clamp and gasket

Two tube holder front bumpers

One 15 degree nozzle

One 30 degree nozzle

Dual split screen monitor reversing camera system

Lights

LED style D.O.T. lighting

Warranty

Water tank system lifetime warranty

Debris tank lifetime warranty

Poly chains lifetime warranty

Drive system 5 year warranty

Mounted on

2021 or newer Freightliner chassis

Cab white/black frame