# **RJ-100SC** Self-Contained Compactor/Container



Malls

Shopping centers

Dairies

Large restaurants

Cafeterias

In-flight kitchens

Supermarkets

Food processors

Theme parks/resorts

Hospitals and institutions

Hotels and motels







Ouik Clean® Tank

Full door seal with P-Seal

CYCON Life-Xtender® Cyclic Control System

Load from both ground and dock level

## **CYCON Cyclic Control System**

### Standard on all **RJ-100SC Compactors**

- Reliable, solid state circuitry eliminates all pressure and limit switches
- CYCON's no-shock cycle control extends cylinder and hose wear life
- Automatic "container full assurance system" — the ram dwells against the load at full pressure, resulting in better compaction
- Smoother running, quieter operation
- Advanced hydraulic design enables the system to operate at minimum pressure levels until the need for more pressure is automatically sensed
- More accurate Advanced Warning or Container Full options
- Dramatically improved cold weather performance

# **RJ-100SC** Compactor with 30 and 34 Cubic Yard Capacity Container

## **Marathon Engineering**

Marathon's RJ-100SC self-contained compactor/container makes handling wet or dry waste simple. It is easy to load from both the ground and dock levels. In addition, a hopper can be used to double or triple the loading capacity. Waste can be fed continuously while the unit is cycling. The 22-ton (19,958 kg) plus crushing power of the RJ-100SC will reduce your refuse to a fraction of its original size. The universal double-end pickup and dock-friendly design make the RJ-100SC ideal for dock-fed applications. Other features include fire hose connections on each unit, hinge grease fittings, and ground and guide rollers.

#### P-Seal

The P-shaped **Door Seal** is specially designed for portable compaction containers to provide a superior watertight closure. The mounting is engineered for quick and easy installation when replacement is necessary, requiring no field fitting, cutting, or welding.



## **Double-Hinge with Bronze Bushing**

Every RJ-100SC is tested for watertightness before leaving the factory. Liquid retention is ensured by the Marathon **Double-Hinge**. It creates uniform seal compression while eliminating the seal "scrubbing" and damage so often encountered with competitive designs. The **Double-Hinge** also saves expensive driver and truck time because only one easy-tooperate ratchet makes it work.

#### **Bubble Gate and Auto Relatch**

The innovative "Bubble Gate" adds a full cubic yard to container capacity. Superior compaction ratios result from its special curved

costs of disposal.

The ultimate in latch systems, Marathon's "Auto Relatch" eliminates the need to hold the door while operating the latch ratchet. This design enables the operator to use both hands on the ratchet.





## SELF-CONTAINED COMPACTORS



Marathon's Remote Power Pack. separate from the compactor/container, remains free of damage caused during hauling to and from disposal sites and free of problems caused by landfill dust. Two simple-to-use, hydraulic quick

> packing head. Weather Cover and the UL® & CUL® Listed Motor Control Panel are standard equipment.


> All Marathon Remote Power Packs are built in-house

to our quality standards and each

unit must pass a series of stringent tests before it can be shipped with the selected compactor.



The optional doghouse offers a totally enclosed charge box with heavy-duty "T" handle latches.



The Qwik Clean® Tank feature, standard on all RJ-100SC compactors, funnels any liquid seepage which can occur during compaction into an enclosed area underneath the charge box floor. The liquid is automatically discharged at the disposal site, in effect flushing the container and the area behind the ram. The 12-inches (305mm) high, 750-gallon (2839 liters) capacity sump area is designed to provide easier hook access for roll-off drivers.

# **Pandora Platform Functionality** Optional on all RJ-100SC Compactors **RJ-100SC** Compactor with PLC and wireless modem Secure wireless custom network Pandora Server Pandora **Notification Server**

## SELF-CONTAINED COMPACTORS


# **RJ-100SC** Self-Contained Compactor/Container

### **Dimensions and Specifications**

Specifications								
Charge Box Capacity								
[Mfr. Rating]	1.5 cu yd 1.15 m <sup>3</sup>							
[NWRA Rating]	1.32 cu yd	1.01 m³						
Clear Top Opening	35"L x 60"W	W 889mm x 1524mm						
Performance Characteristics:								
Cycle Time	37 sec. 37 sec.							
<b>Total Normal Force</b>	36,300 lbs. 161 kN							
Total Maximum Force	45,200 lbs. 201 kN							
Normal Ram Face Pressure	20.9 psi 144 kPa							
Maximum Ram Face Pressure	25.9 psi 179 kPa							
Ram Penetration	6.5"	165mm						
Electrical Equipment:								
Electric Motor 3/60/230-460	10 hp	7.5kW						
<b>Electric Control Voltage</b>	120 VAC 120VAC							
Panel Box Assembly								
UL® and CUL® Listed	Key Operated 120 VAC							
All Circuits Fused	3-Button Controls: Keylock Start, Stop,							
All Gircuits Puseu	Reverse							
Hydraulic Equipment:								
Hydraulic Pump	10 gpm 38 L/min							
Normal Pressure	1850 psi 128 bar							
Maximum Pressure	2300 psi	159 bar						
Hydraulic Cylinder - Bore	5"	127mm						
- Rod	2.5" 64mm							

RJ-100SC	А	В	C	D**	Е	WT.
30 cu yds	4'0"	3' 25⁄8"	7' 4½"	22' 1¾16"	8' 8"	9,400 lbs.
	1219mm	981mm	2238mm	6736mm	2642mm	4273 kg
34 cu yds	4'0"	3' 2 <sup>5</sup> ⁄8"	7' 4½"	24' 2"	8' 8"	9,900 lbs.
	1219mm	981mm	2238mm	7366mm	2261mm	4500 kg

Overall height with hydraulic tailgate raised: 16'6". Hoist should be equipped with selector valve (1500 psi minimum) in order to control hydraulic tailgate.



Dimensions not shown: 8' 41/8" (2543mm) Overall Width Ground Roller Widths: 61 1/8" (1569mm) Inside Rollers 67 1/8" (1712mm) Roller Centers 72 1/8" (1851mm) Outside Rollers



You can add the Pandora Remote Monitoring System to many of our most popular compactors. For information about adding Pandora, please contact your Marathon salesperson.

#### Compactor Rental and Leasing Programs Available

For detailed specifications, recommendations, or free economic studies comparing various systems, contact Marathon Customer Care at

1-800-633-8974



#### **Authorized Dealer:**



Marathon Equipment Company P.O. Box 1798 Vernon, AL 35592-1798 800.633.8974

www.marathonequipment.com

Sourcewell Contract #060612-ESG









Pictures in this literature are illustrative only. Specifications are subject to change without notice in order to accommodate improvements to the equipment. Certified in compliance with ANSI standard Z245.2, applicable OSHA Regulations, and certified under WASTEC's Stationary Compactor Certification Program. Products must be used with safe practice and in accordance with said regulations and standards.

<sup>\*\*</sup> Other lengths available. Call factory for details.