



800-523-3654

BALER & COMPACTOR

www.ptrco.com

Stationary Compactors



TP-3000HD

Tram-Pak Stationary Compactor

Designed For

- * Retailers * Hospitals * Hotels * Distribution Centers *
- * Manufacturing Centers * Recycling Centers * Home Centers *

Our TP-3000HD compactor is designed for long lasting performance and durability. All components are built using heavy-duty structural steel components and welded by AWS certified technicians. This unit has total U.L. approval, standard 3 button controls (On/Off key switch, mushroom stop, auto reverse) and a 13' Sealtite.

Specifications

Charge Box Capacity	3.2 Cu Yd
Clear Top Opening (L x W)	68" x 60"
Capacity Per Hour	158 cy/hr

Performance Characteristics

Cycle Time	65 sec
Total Normal Force	62,000 lbs
Total Maximum Force	74,000 lbs
Normal Ram Face Pressure	35 psi
Maximum Ram Face Pressure	41 psi

Electrical Equipment

Electrical Motor	208 / 230 / 460	3 Phase
Electrical Control Voltage		120 VAC

Hydraulic Equipment

Hydraulic Pump Capacity	15 gpm
Normal Pressure	2200 psi
Maximum Pressure	2600 psi
Hydraulic Cylinder	6" Bore
Hydraulic Cylinder	4" Rod
Weight	6,850 lbs



PTR Baler & Compactor Company • 2207 E Ontario St. • Philadelphia, PA 19134
215-533-5100 • (FAX) 215-533-8906 • 800-523-3654 • www.PTRCO.com



Printed in the U.S.A.
© PTR Baler & Compactor