

AMPLIROLL® CAPACITIES

MODEL	LIFTING CAP.	SUGGEST BODY LENGTH	AVERAGE CONTAINER LENGTHS	MINIMUM CONTAINER LENGTHS	DISTANCE PIN TO REAR ROLLER	HOOK HEIGHT standard / optional	MAX. DUMP ANGLE	SHIPPING WEIGHT	CA/CT
AL 35-11	6,600 LBS.	11 FT	10 - 12 FT.	8 FT.	114"	36 .25	57	995	82 - 98"
AL 90S-12	13,000 LBS.	12 FT	9 - 13.5 FT.	8 FT.	113"	36 .25/ 54	58	1790	84 - 108"
AL 90L-14	13,000 LBS.	14 FT	10 - 14 FT.	10 FT.	134"	36 .25/ 54	61	1790	108 - 126"
AL 95SS-12	18,000 LBS.	12 FT	11 - 13 FT.	10 FT.	136"	54	54	2408	96 - 120"
AL 95S-15	18,000 LBS.	14 FT	13 - 16 FT.	10 FT.	151"	54	54	2408	120 - 138"
AL 95L-16	18,000 LBS.	16 FT	14 - 17.5 FT.	11 FT.	163"	54	54	2417	126 - 150"
AMP 100SS-12	20,000 lbs	12 FT	11 - 13 FT.	10 FT.	136"	54 / 36 or MA 36 - 54	58	2408	120-130
AMP 100S-15	20,000 lbs	14 FT	13 - 16 FT.	10 FT.	151"	54 / 36 or MA 36 - 54	60	2417	130-144
AMP 100L-16	20,000 lbs	16 FT	14 - 17.5 FT.	12 FT.	163"	54 / 36 or MA 36 - 54	60	2417	140-158
AL 100SS-12	20,000 LBS.	12 FT	11 - 13 FT.	10 FT.	136"	54	54	2408	96 - 120"
AL 100S-15	20,000 LBS.	14 FT	13 - 16 FT.	10 FT.	151"	54	54	2408	120 - 138"
AL 100L-16	20,000 LBS.	16 FT	14 - 17.5 FT.	11 FT.	163"	54	54	2417	126 - 150"
AL 100SST-12	20,000 LBS.	12 FT	11 - 13 FT.	10 FT.	136"	Adjustable	54	2408	96 - 120"
AL 100ST-15	20,000 LBS.	14 FT	13 - 16 FT.	10 FT.	151"	54" to	54	2408	120 - 138"
AL 100LT-16	20,000 LBS.	16 FT	14 - 17.5 FT.	11 FT.	163"	36.25"	54	2417	126 - 150"
AL 120SS-10	26,000 LBS.	10 FT	10 - 12 FT.	9 FT.	117"	54/ 61.75	52	3307	96 - 108"
AL 120SS-12	26,000 LBS.	12 FT	11 - 14 FT.	9 FT.	127"	54/ 61.75	52	3307	102 - 110"
AL 120S-14	26,000 LBS.	14 FT	13 - 16 FT.	11 FT.	146"	54/ 61.75	53	3307	120 - 138"
AL 120L-16	26,000 LBS.	16 FT	12 - 17.5 FT.	12 FT.	169"	54/ 61.75	60	3450	138 - 156"
AMP 140-183-16	31,000 LBS.	16 FT	14 - 18 FT.	13 FT.	183"	61.75/ 54	51	4260	158 - 180" S 132 - 162" T
AMP 140-189-18	31,000 LBS.	18 FT	15 - 20 FT.	13 FT.	191"	61.75/ 54	51	4260	170" - 192" S 144 - 174" T
AMP 140-165-15	35,000 LBS.	14 FT	14 - 18 FT.	12 FT.	165"	61.75/ 54	61	4510	152 - 169" S 126 - 151" T
AMP 140-181-17	35,000 LBS.	16 FT	16 - 19 FT.	12 FT.	181"	61.75/ 54	61	4510	164 - 182" S 138 - 164" T
AMP 140-197-18	35,000 LBS.	18 FT	13 - 20 FT.	13 FT.	197"	61.75/ 54	56	4686	180 - 198" S 154 - 186" T
AMP 140-220-20	35,000 LBS.	20 FT	18 - 22 FT.	14 FT.	220"	61.75/ 54	56	4994	204 - 222" S 178 - 204" T
AMP 150-165-15	40,000 LBS.	14 FT	12 - 18 FT.	12 FT.	165"	61.75/ 54	61	4510	126 - 151" T
AMP 150-181-17	40,000 LBS.	16 FT	12 - 19 FT.	12 FT.	181"	61.75/ 54	61	4510	138 - 164" T
AMP 150-197-18	40,000 LBS.	18 FT	13 - 20 FT.	14 FT.	197"	61.75/ 54	56	4686	154 - 186" T
AMP 150-220-20	40,000 LBS.	20 FT	15 - 22 FT.	15 FT.	220"	61.75/ 54	56	4994	178 - 204" T
AMP 160-212-20	50,000 LBS.	20 FT	18 - 22 FT.	15 FT.	213"	61.75	51	5565	174 - 190" T
AMP 160-232-22	50,000 LBS.	22 FT	20 - 24 FT.	16 FT.	232"	61.75	56	5730	186 - 210" T
AMP 160-185-17	60,000 LBS.	16 FT	14 - 20 FT.	13 FT.	189"	61.75	54	5148	138 - 168" T
AL 160/2000-22	65,000 LBS.	22 FT	16 - 24 FT.	16 FT.	223"	61.75	57	7030/ 6420 without stabilizer	186 - 200" T



One Truck. Infinite Possibilities.



- Easy to operate, from inside the truck
- Maneuverable, up to 60 degrees.
- Versatile, you can have any attachment you need for a job.
- Safety, ground level loading.
- Efficient, no need for workers to wait on the truck.
- Savings, fewer trucks, means less operating costs.

 **marrel**
CORPORATION

4750 14 Mile Road NE • Rockford, MI 49341

Phone: (616) 863-9155 • Fax: (616) 863-9177
Toll Free: (866) 822-3580 • www.amplirollusa.com
E-mail: equipment@amplirollusa.com