

New vehicle



Current report content is based on data as of 2021-04-20 07:52:40. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



ISUZU TRUCK OF FAYETTEVILLE

Joe Green

New vehicle (2022 NPR-XD Crew Cab Chassis, NZ3 150"WB, 88.5"CA, 16,000 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning

	Code	Description	Weight	MSRP
Model				
	NZ3	NPR-XD Crew Cab Chassis 150"WB, 88.5"CA		\$62,900.00
	54	White, In rail fuel tank with power windows, power door locks and air conditioning		\$0.00
Tires		, and the second		
	I5H	LRR (low rolling resistance)	0.0 lbs.	Inc.
Engine				
	I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ftlb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.	0.0 lbs.	Inc.
Transmission				
	I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,	0.0 lbs.	Inc
Wheelbase				
	IH6	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in RBM 523,160 lb./ft./in. per rail. 88.5"CA	0.0 lbs.	Inc.
Air Cleaner				
Alternator	KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).	0.0 lbs.	Inc.
Aiternator	I2C	140 AMP. with integral regulator.	0.0 lbs.	Inc.
Battery	120	140 AMI : With integral regulator.	0.0 ibs.	IIIO.
<u> </u>	IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts	0.0 lbs.	Inc
Exhaust				
	IX7	Single horizontal with DPF/SCR exhaust system	0.0 lbs.	Inc
Front Axle		· ·		
	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	0.0 lbs.	Inc
Front Suspens	ion			
	ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar	0.0 lbs.	Inc
Front Wheels				
	IB9	19.5" x 6", 6-hole disc, painted white	0.0 lbs.	Inc
Front Tires				
	XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season	0.0 lbs.	Inc
Rear Suspensi		, , , , , , , , , , , , , , , , , , , ,		
	19K	14,308 lbs. capacity. Semi-elliptical main and	0.0 lbs.	Inc

Current report content is based on data as of 2021-04-20 07:52:40. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



ISUZU TRUCK OF FAYETTEVILLE

Joe Green

New vehicle (2022 NPR-XD Crew Cab Chassis, NZ3 150"WB, 88.5"CA, 16,000 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning

Code	Description	Weight	MSRF
	auxiliary multi-leaf springs. Includes shock absorbers.		
Rear Axle			
136	R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings.	0.0 lbs.	Inc
Ratio			
099	4.777	0.0 lbs.	Inc
Rear Wheels			
IC1	19.5" x 6", 6-hole disc, painted white	0.0 lbs.	Inc
Rear Tires			
YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.	0.0 lbs.	Inc
Fuel Tank			
IF9	30 gal. rectangular fuel tank. Mounted between frame rail through the rail fuel fill. Fuel water separator with dash mounted warning light.	0.0 lbs.	Inc
Seat			
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	0.0 lbs.	Inc
Brakes			
K40	Butterfly valve type exhaust brake	0.0 lbs.	Inc
IR8	Dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard. 4 channel antilock brake system.	0.0 lbs.	Inc
Air Conditioning			
C60	Air conditioner	0.0 lbs.	Inc
Power Windows & Door L	ocks		
IL0	Yes	0.0 lbs.	Inc
Floor Mats			
IQ6	Standard Floor Mats	0.0 lbs.	Inc
Model Option			
54	White, In rail fuel tank with power windows, power door locks and air conditioning	0.0 lbs.	Inc
Accessories			
IX2	Rear body dome lamp switch	0.1 lbs.	Inc
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	0.0 lbs.	Inc
Totals			
	Base Price Destination Charge DEF Fill Charge		\$62,900.0 \$1,325.0 \$10.0
			φ10.0
	Total Options Price		

Current report content is based on data as of 2021-04-20 07:52:40. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial:



ISUZU TRUCK OF FAYETTEVILLE

Joe Green

New vehicle (2022 NPR-XD Crew Cab Chassis, NZ3 150"WB, 88.5"CA, 16,000 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning

Selected Model and Options						
Code	Description	Weight	MSRP			
	Total		\$64,242.94			

Current report content is based on data as of 2021-04-20 07:52:40. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.