



# ISUZU TRUCK OF FAYETTEVILLE

Joe Green

New vehicle (2022 NRR Crew Cab Chassis, NV3 150"WB, 88.5"CA, 19,500 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning

## Selected Model and Options

	Code	Description	Weight	MSRP
<b>Model</b>				
	NV3	NRR Crew Cab Chassis 150"WB, 88.5"CA		\$68,044.00
	54	White, In rail fuel tank with power windows, power door locks and air conditioning		\$0.00
<b>Tires</b>				
	I5H	LRR (low rolling resistance)	0.0 lbs.	Inc.
<b>Engine</b>				
	I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.	0.0 lbs.	Inc.
<b>Transmission</b>				
	I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,	0.0 lbs.	Inc.
<b>Wheelbase</b>				
	IH6	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in <sup>3</sup> RBM 523,160 lb./ft./in. per rail. 88.5"CA	0.0 lbs.	Inc.
<b>Air Cleaner</b>				
	KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).	0.0 lbs.	Inc.
<b>Alternator</b>				
	I2C	140 AMP. with integral regulator.	0.0 lbs.	Inc.
<b>Battery</b>				
	IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts	0.0 lbs.	Inc.
<b>Exhaust</b>				
	IX7	Single horizontal with DPF/SCR exhaust system	0.0 lbs.	Inc.
<b>Front Axle</b>				
	I26	"I"-beam rated at 7,275 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	0.0 lbs.	Inc.
<b>Front Suspension</b>				
	ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar	0.0 lbs.	Inc.
<b>Front Wheels</b>				
	IB9	19.5" x 6", 6-hole disc, painted white	0.0 lbs.	Inc.
<b>Front Tires</b>				
	XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season	0.0 lbs.	Inc.
<b>Rear Suspension</b>				
	ID9	14,550 lbs. capacity. Semi-elliptical main and	0.0 lbs.	Inc.

Current report content is based on data as of 2021-04-20 08:40:24. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# ISUZU TRUCK OF FAYETTEVILLE

Joe Green

New vehicle (2022 NRR Crew Cab Chassis, NV3 150"WB, 88.5"CA, 19,500 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning

## Selected Model and Options

	Code	Description	Weight	MSRP
Rear Axle				
		auxiliary multi-leaf springs. Includes shock absorbers.		
	ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	0.0 lbs.	Inc.
Ratio				
	011	5.571:1	0.0 lbs.	Inc.
Rear Wheels				
	IC1	19.5" x 6", 6-hole disc, painted white	0.0 lbs.	Inc.
Rear Tires				
	YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.	0.0 lbs.	Inc.
Fuel Tank				
	IF9	30 gal. rectangular fuel tank. Mounted between frame rail through the rail fuel fill. Fuel water separator with dash mounted warning light.	0.0 lbs.	Inc.
Seat				
	AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	0.0 lbs.	Inc.
Brakes				
	K40	Butterfly valve type exhaust brake	0.0 lbs.	Inc.
	IT4	Dual circuit, Hydro-Boost hydraulic brake system with EBD (Electronic Brake Distribution). Mechanical transmission mounted parking brake. Non-asbestos semi metallic linings are standard. Anti-lock brake system	0.0 lbs.	Inc.
Air Conditioning				
	C60	Air conditioner	0.0 lbs.	Inc.
Power Windows & Door Locks				
	IL0	Yes	0.0 lbs.	Inc.
Floor Mats				
	IQ6	Standard Floor Mats	0.0 lbs.	Inc.
Model Option				
	54	White, In rail fuel tank with power windows, power door locks and air conditioning	0.0 lbs.	Inc.
Accessories				
	IX2	Rear body dome lamp switch	0.1 lbs.	Inc.
	8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	0.0 lbs.	Inc.
Totals				
		Base Price		\$68,044.00
		Destination Charge		\$1,325.00
		DEF Fill Charge		\$10.00
		Total Options Price		\$
		Tire Weight Tax		\$7.94
		Total		\$69,386.94

Current report content is based on data as of 2021-04-20 08:40:24. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.