

## ISUZU TRUCK OF FAYETTEVILLE

Joe Green

New vehicle (2022 NRR Cab Chassis, NU1 109"WB, 86.5"CA, 19,500 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning

Model  NU1 NRR Cab Chassis 109"WB, 86.5"CA White, In rail fuel tank with power windows door locks and air conditioning  Tires  I5H LRR (low rolling resistance)  Engine  I1B 4HK1-TC, diesel engine 317 CID (5.19L), 2550 RPM: 452 ftlb. gross torque at 1850 cylinder, 16 valve, four cycle, overhead car turbocharged, inter-cooled, water cooled E direct injection, electronically controlled confuel system, engine cruise control function. check switch and light. Engine Warning system and low coolant level.  Transmission  I1W Aisin A465id 6-speed automatic transmissis Ratios: 3.742, 2.003, 1.343,  Wheelbase  IAB 109 inches, includes ladder type channel from C section straight frame 33.5 inches wide. strength 44,000 psi; section modulus 7.20 316,800 lb./ft/in. per rail. 86.5"CA  Air Cleaner  KNX Dry Paper single element. (Donaldson branches cleaner canister standard with air restriction in the driver's Multi-Information Display (M.)  Alternator  I2C 140 AMP. with integral regulator.  Battery  IX1 Dual 12-Volt maintenance free group 31.75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust syndraulic power steering. Ratio 18.8-20.9:16 front Suspension  IDB 8440 lbs. Capacity semi elliptical tapered le Includes shock absorbers and stabilizer batteries with elliptical tapered le Includes shock absorbers and stabilizer batteries.	0.0 lbs.	\$62,584.00 \$0.00
Tires  ISH LRR (low rolling resistance)  Engine  ISH 4HK1-TC, diesel engine 317 CID (5.19L), 2 2550 RPM: 452 ftlb. gross torque at 1850 cylinder, 16 valve, four cycle, overhead car turbocharged, inter-cooled, water cooled E direct injection, electronically controlled cor fuel system, engine cruise control function. check switch and light. Engine Warning system and low coolant level.  Transmission  IW Aisin A465id 6-speed automatic transmissi Ratios: 3.742, 2.003, 1.343,  Wheelbase  IA8 109 inches, includes ladder type channel from C section straight frame 33.5 inches wide. strength 44,000 psi; section modulus 7.20 316,800 lb./ft./in. per rail. 86.5°CA  Air Cleaner  KNX Dry Paper single element. (Donaldson branche cleaner canister standard with air restriction in the driver's Multi-Information Display (Michael Cooleaner)  IZC 140 AMP. with integral regulator.  Battery  IX1 Dual 12-Volt maintenance free group 31 75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust symptomic power steering. Ratio 18.8-20.9:16 proposed in cludes shock absorbers and stabilizer batteries and	0.0 lbs.	\$0.00
Tires  I5H LRR (low rolling resistance)  Engine  I1B 4HK1-TC, diesel engine 317 CID (5.19L), 2 2550 RPM: 452 ftlb. gross torque at 1850 cylinder, 16 valve, four cycle, overhead can turbocharged, inter-cooled, water cooled E direct injection, electronically controlled confuel system, engine cruise control function. check switch and light. Engine Warning system audible warning for low oil pressure, high of temperature, and low coolant level.  Transmission  I1W Aisin A465id 6-speed automatic transmissing Ratios: 3.742, 2.003, 1.343,  Wheelbase  IAB 109 inches, includes ladder type channel for C section straight frame 33.5 inches wide. strength 44,000 psi; section modulus 7.20 316,800 lb./ft./in. per rail. 86.5"CA  Air Cleaner  KNX Dry Paper single element. (Donaldson branche cleaner canister standard with air restriction in the driver's Multi-Information Display (MI)  Alternator  I2C 140 AMP. with integral regulator.  Battery  IX1 Dual 12-Volt maintenance free group 31 75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust system and stabilizer batteries and stabilizer batteries.	0.0 lbs.	\$0.00
Engine  I1B	215 HP at 0.0 lbs.	1
Engine  I1B	215 HP at 0.0 lbs.	1
I1B 4HK1-TC, diesel engine 317 CID (5.19L), 2 2550 RPM: 452 ftlb. gross torque at 1850 cylinder, 16 valve, four cycle, overhead car turbocharged, inter-cooled, water cooled E direct injection, electronically controlled con fuel system, engine cruise control function. check switch and light. Engine Warning system audible warning for low oil pressure, high of temperature, and low coolant level.  Transmission  I1W Aisin A465id 6-speed automatic transmissing Ratios: 3.742, 2.003, 1.343,  Wheelbase  IA8 109 inches, includes ladder type channel for C section straight frame 33.5 inches wide. strength 44,000 psi; section modulus 7.20 316,800 lb./ft./in. per rail. 86.5"CA  Air Cleaner  KNX Dry Paper single element. (Donaldson branche cleaner canister standard with air restriction in the driver's Multi-Information Display (Minches) Multi-Information Disp		Inc
2550 RPM: 452 ftlb. gross torque at 1850 cylinder, 16 valve, four cycle, overhead car turbocharged, inter-cooled, water cooled E direct injection, electronically controlled confuel system, engine cruise control function. check switch and light. Engine Warning system audible warning for low oil pressure, high of temperature, and low coolant level.  Transmission  I1W Aisin A465id 6-speed automatic transmissing Ratios: 3.742, 2.003, 1.343,  Wheelbase  IAB 109 inches, includes ladder type channel for C section straight frame 33.5 inches wide. strength 44,000 psi; section modulus 7.20 316,800 lb./ft./in. per rail. 86.5"CA  Air Cleaner  KNX Dry Paper single element. (Donaldson branches cleaner canister standard with air restriction in the driver's Multi-Information Display (Minternator  I2C 140 AMP. with integral regulator.  Battery  IX1 Dual 12-Volt maintenance free group 31 75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust syndraulic power steering. Ratio 18.8-20.9:19 front Suspension  IDB 8440 lbs. Capacity semi elliptical tapered le Includes shock absorbers and stabilizer batteries and stabili		
I1W Aisin A465id 6-speed automatic transmissi Ratios: 3.742, 2.003, 1.343,  Wheelbase  IA8 109 inches, includes ladder type channel fr C section straight frame 33.5 inches wide. strength 44,000 psi; section modulus 7.20 316,800 lb./ft./in. per rail. 86.5"CA  Air Cleaner  KNX Dry Paper single element. (Donaldson brancleaner canister standard with air restriction in the driver's Multi-Information Display (Minumer of the driver's Multi-Information Display (Minumer of the driver)  I2C 140 AMP. with integral regulator.  Battery  IX1 Dual 12-Volt maintenance free group 31 75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust strength of the driver's maintenance in the	GR valve, nmon rail Oil level stem with	Inc
Ratios: 3.742, 2.003, 1.343,  Wheelbase  IA8 109 inches, includes ladder type channel fr C section straight frame 33.5 inches wide. strength 44,000 psi; section modulus 7.20 316,800 lb./ft./in. per rail. 86.5"CA  Air Cleaner  KNX Dry Paper single element. (Donaldson brancleaner canister standard with air restriction in the driver's Multi-Information Display (MIAIternator  I2C 140 AMP. with integral regulator.  Battery  IX1 Dual 12-Volt maintenance free group 31 75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust syndraulic power steering. Ratio 18.8-20.9:1  Front Suspension  ID8 8440 lbs. Capacity semi elliptical tapered le Includes shock absorbers and stabilizer batteries and s		
IA8 109 inches, includes ladder type channel fr C section straight frame 33.5 inches wide. strength 44,000 psi; section modulus 7.20 316,800 lb./ft./in. per rail. 86.5"CA  Air Cleaner  KNX Dry Paper single element. (Donaldson branche cleaner canister standard with air restriction in the driver's Multi-Information Display (Minumer of the driver's Multi-Information Display (Minumer of the driver)  Alternator  I2C 140 AMP. with integral regulator.  Battery  IX1 Dual 12-Volt maintenance free group 31 75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust symptomic power steering. Ratio 18.8-20.9:1  Front Suspension  ID8 8440 lbs. Capacity semi elliptical tapered leg Includes shock absorbers and stabilizer batteries.	on, 0.0 lbs.	Inc
C section straight frame 33.5 inches wide. strength 44,000 psi; section modulus 7.20 316,800 lb./ft./in. per rail. 86.5"CA  Air Cleaner  KNX Dry Paper single element. (Donaldson brain cleaner canister standard with air restriction in the driver's Multi-Information Display (Mildernator)  I2C 140 AMP. with integral regulator.  Battery  IX1 Dual 12-Volt maintenance free group 31 75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust set single horizontal with DPF/SC		
KNX Dry Paper single element. (Donaldson bran cleaner canister standard with air restriction in the driver's Multi-Information Display (MI Alternator  12C 140 AMP. with integral regulator.  Battery  IX1 Dual 12-Volt maintenance free group 31 75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust symptoms. Ratio 18.8-20.9:1  Front Axle  IZ6 "I"-beam rated at 7,275 lbs. Includes integrated by the standard power steering. Ratio 18.8-20.9:1  Front Suspension  ID8 8440 lbs. Capacity semi elliptical tapered by Includes shock absorbers and stabilizer batteries.	Yield	Ind
cleaner canister standard with air restriction in the driver's Multi-Information Display (Mithernator)  I2C 140 AMP, with integral regulator.  Battery  IX1 Dual 12-Volt maintenance free group 31 75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust system and stabilizer batteries with the stable integral power steering. Ratio 18.8-20.9:1  Front Suspension  ID8 8440 lbs. Capacity semi elliptical tapered leading to the stabilizer batteries with air restriction in the driver's Multi-Information Display (Mitheritation		
Battery  IX1 Dual 12-Volt maintenance free group 31 75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust symmetry  Front Axle  IZ6 "I"-beam rated at 7,275 lbs. Includes integred hydraulic power steering. Ratio 18.8-20.9:17  Front Suspension  ID8 8440 lbs. Capacity semi elliptical tapered led Includes shock absorbers and stabilizer battering.	indicator	Inc
Battery  IX1 Dual 12-Volt maintenance free group 31 75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust symmetry  Front Axle  IZ6 "I"-beam rated at 7,275 lbs. Includes integree hydraulic power steering. Ratio 18.8-20.9:1  Front Suspension  ID8 8440 lbs. Capacity semi elliptical tapered le Includes shock absorbers and stabilizer batters.		
IX1 Dual 12-Volt maintenance free group 31 75 batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust symmetry  Front Axle  IZ6 "I"-beam rated at 7,275 lbs. Includes integrated hydraulic power steering. Ratio 18.8-20.9:1  Front Suspension  ID8 8440 lbs. Capacity semi elliptical tapered le Includes shock absorbers and stabilizer batteries.	0.0 lbs.	Inc
batteries with threaded posts  Exhaust  IX7 Single horizontal with DPF/SCR exhaust system of the sys		
Front Axle  IZ6 "I"-beam rated at 7,275 lbs. Includes integr hydraulic power steering. Ratio 18.8-20.9:1  Front Suspension  ID8 8440 lbs. Capacity semi elliptical tapered le Includes shock absorbers and stabilizer ba	60 CCA 0.0 lbs.	Inc
Front Axle  IZ6 "I"-beam rated at 7,275 lbs. Includes integr hydraulic power steering. Ratio 18.8-20.9:1  Front Suspension  ID8 8440 lbs. Capacity semi elliptical tapered le Includes shock absorbers and stabilizer ba		
IZ6 "I"-beam rated at 7,275 lbs. Includes integr hydraulic power steering. Ratio 18.8-20.9:1 Front Suspension  ID8 8440 lbs. Capacity semi elliptical tapered le Includes shock absorbers and stabilizer ba	vstem 0.0 lbs.	Inc
hydraulic power steering. Ratio 18.8-20.9:1  Front Suspension  ID8 8440 lbs. Capacity semi elliptical tapered le Includes shock absorbers and stabilizer ba		
ID8 8440 lbs. Capacity semi elliptical tapered le Includes shock absorbers and stabilizer ba		Inc
Includes shock absorbers and stabilizer ba		
Front Wheels	. •	Inc
IB9 19.5" x 6", 6-hole disc, painted white	0.0 lba	Inc
Front Tires	0.0 lbs.	
XTN/R3M 225/70R19.5F (12 ply) tubeless Radial, all		Inc
Rear Suspension  ID9 14,550 lbs. capacity. Semi-elliptical main a		

Current report content is based on data as of 2021-04-20 08:32:47. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial:



## ISUZU TRUCK OF FAYETTEVILLE

Joe Green

New vehicle (2022 NRR Cab Chassis, NU1 109"WB, 86.5"CA, 19,500 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning

Code	Description	Weight	MSRF
	auxiliary multi-leaf springs. Includes shock absorbers.		
Rear Axle			
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	0.0 lbs.	Inc
Ratio			
011	5.571:1	0.0 lbs.	Inc
Rear Wheels			
IC1	19.5" x 6", 6-hole disc, painted white	0.0 lbs.	Inc
Rear Tires	· · · · · · · · · · · · · · · · · · ·		
YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.	0.0 lbs.	Inc
Fuel Tank			
IF9	30 gal. rectangular fuel tank. Mounted between frame rail through the rail fuel fill. Fuel water separator with dash mounted warning light.	0.0 lbs.	Inc
Seat			
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	0.0 lbs.	Inc
Brakes			
K40	Butterfly valve type exhaust brake	0.0 lbs.	Inc
IT4	Dual circuit, Hydro-Boost hydraulic brake system with EBD (Electronic Brake Distribution). Mechanical transmission mounted parking brake. Non-asbestos semi metallic linings are standard. Anti-lock brake system	0.0 lbs.	Inc
Air Conditioning			
C60	Air conditioner	0.0 lbs.	Inc
Power Windows & Door L	.ocks		
IL0	Yes	0.0 lbs.	Inc
Floor Mats			
IQ6	Standard Floor Mats	0.0 lbs.	Inc
Model Option			
54	White, In rail fuel tank with power windows, power door locks and air conditioning	0.0 lbs.	Inc
Accessories			
IX2	Rear body dome lamp switch	0.1 lbs.	Inc
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	0.0 lbs.	Ind
Totals			
	Base Price		\$62,584.0
	Destination Charge		\$1,325.0
	DEF Fill Charge		\$10.0
	Total Options Price		
	Tire Weight Tax		\$7.9
	Total		\$63,926.9

Current report content is based on data as of 2021-04-20 08:32:47. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.