





# **TECHNICAL SPECIFICATION**

## PINNACLE 64T DAYCAB

				WEIGH	T (LB)
CUST	OMER/VEHICLE	INFO	DESCRIPTION	FRONT	REAR
S	0029J2	CHASSIS (BASE MODEL)	PINNACLE 64T DAYCAB	5,214	2,800
S	99X93X	ASSEMBLY PLANT	Made in Macungie, PA USA	0	0
	MP2001	CUSTOMER FLEET SIZE	DEALER FLEET WITH LESS THAN 25 VEHICLES IN OWN FLEET OF ANY VEHICLE BRAND	0	0
S	M45001	ORDER TYPE REQUIREMENTS	RETAIL OR STOCK - CUSTOM SPECIFICATIONS	0	0
S	013001	TYPE OF SERVICE	COMMERCIAL	0	0
s	M98018	WARRANTY REGISTRATION LOCATION	US - WARRANTY REGISTRATION LOCATION	0	0
s	505015	INITIAL REGISTRATION LOCATION	ALL 50 STATES, CARB ENGINE EMISSION (US17 / US21 / ZERO EMISSION)	0	0
S	534014	LANGUAGE-PUBS/DECAL/SIGNS	ENGLISH	0	0
	005005	VEHICLE USE & BODY/TRAILER TYPE	VAN TRAILER	0	0
S	78XB1X	TRANSPORT CYCLE	LOCAL DISTRIBUTION	0	0
S	DKXG2X	GROSS COMBINATION WEIGHT	80,000 LB (36 TONNES) GROSS COMBINATION WEIGHT	0	0
S	7OBC1X	BRAKE REGULATION	BRAKE REGULATION, STOPPING DISTANCE 76M (250FT)	0	0
	QCXA1X	TOPOGRAPHY	GRADES <3% GREATER THAN 98% OF DRIVING DISTANCE MAX GRADE 8%	0	0
S	E1BD1X	AMBIENT TEMP UPPER LIMIT (GTA)	AMBIENT TEMPERATURE HOT. WARMER THAN 104 F (40 C) ALLOWED UP TO 25 HOURS PER YEAR	0	0
S	032A79	TERRAIN GRADE	ON HIGHWAY, STARTING GRADES<16%	0	0
S	033A10	LOADING SURFACE	CONCRETE LOADING AND / OR UNLOADING SURFACE	0	0
S	0341A1	VEHICLE VOCATION	LINEHAUL / LONG HAUL SERVICE	0	0

				WEIGH	IT (LB)
ENGINE/TRANSMISSIONS		IONS	DESCRIPTION	FRONT	REAR
s	1002Z0	ENGINE PACKAGE, COMBUSTION	MP8-415C MACK 415HP @ 1400-1700 RPM (PEAK) 1950 RPM (GOV) 1660 LB-FT, US'21	2,165	541
S	Q1CA1X	GEAR SELECTION TUNING	BASIC, GEAR-SELECTION TUNING	0	0
S	3GCA1X	GHG APPLICATION, VEHICLE	GREEN HOUSE GAS HIGHWAY APPLICATION	0	0
	136AH0	TRANSMISSION	FULLER FR-15210B (14.80/1.00)	523	175
s	V4EZ9X	GEARBOX 12TH GEAR LOCK-OUT	WITHOUT 12TH GEARBOX GEAR LOCK-OUT	0	0



				WEIGH	IT (LB)
EXHA	UST/EMISSIONS		DESCRIPTION	FRONT	REAR
s	CIRAA4	CARB 2008 IDLE REGULATION	IDLE EMISSION CERTIFICATION, CARB (WITH DECAL LOCATED ON LOWER LH CORNER / DRIVER DOOR	0	0
s	DPF04F	DPF DIESEL PARTICULATE FILTER	CLEARTECH ONE BOX E.A.T.S. RH SIDE UNDER CAB US17 / US21	0	0
s	MCF01F	CHASSIS MOUNTED EMISSIONS FINISH	PAINTED DEF & DPF COVER	0	0
	DF10M1	DEF TANK	11.8 GALLON (45 L) 22" LEFT SIDE FRAME MOUNTED	-39	-22
s	6MDAAX	AD-BLUE TANK VENTILATION FILTER	WITHOUT DEF TANK VENTILATION FILTER	0	0
	130AA9	EXHAUST	UNDERFRAME RIGHT SIDE INBOARD MOUNTED	-52	-26
s	Q0AA1X	EXHAUST SYSTEM MATERIAL FINISH	W/O BRIGHT FINISH EXHAUST	0	0
	78AC9X	EMISSION ON BOARD DIAG CONTROL	EMISSION OBD, DISPLAY ONLY, USA2021	0	0

				WEIGH	T (LB)
ENGIN	E EQUIPMENT		DESCRIPTION	FRONT	REAR
s	125045	AIR CLEANER	UNDER HOOD SINGLE ELEMENT DRY TYPE W/AIR INTAKE FROM BOTH SIDES OF HOOD	0	0
s	121AA5	BUG SCREEN	BLACK ALUMINUM BUG SCREEN MOUNTED BEHIND GRILLE, WITHOUT WINTER FRONT COVER	0	0
s	1130L3	AIR COMPRESSOR/DRYER	WABCO AIR DR SS-HP AIR DRYER W/ WABCO 318 (18.7 CFM) AIR COMPRESSOR	0	0
S	KOXA1X	AIR DRYER POSITION (CA)	AIR DRYER POSITION STANDARD	0	0
S	132AB4	ALTERNATOR	DELCO 12V 130A (24SI) BRUSH-TYPE	16	0
S	316AA6	BATTERIES	(3) MACK 12V 650/1950 CCA THREADED STUD TYPE	0	0
s	393AA9	BATTERY BOX - MOUNTING	RH RAIL UNDER CAB (3 BATTERY MAX)	0	0
S	L5XA1X	BATTERY BOX COVER	MOLDED PLASTIC	0	0
S	NCXA5X	STARTER MOTOR	12 VOLT DELCO 39MT-MXT	31	0
S	110AA6	ENGINE BRAKE	MACK MP8 POWERLEASH	0	0
s	JMXB1X	ENGINE BRAKE LIGHTING (CA)	VEHICLE AND TRAILER (IF APPLICABLE) STOP LAMPS ACTIVATE UPON SERVICE BRAKE APPLICATION ONLY(3899000)	0	0
S	118AB8	FAN DRIVE	BEHR FAN AND ELECTRONIC MODULATING VISCOUS FAN DRIVE	0	0
s	119AI9	COOLANT PROTECTION	ETHYLENE GLYCOL FULLY FORMULATED COOLANT (50/50 MIX DYED PINK) TO -34DEG, W/ FILTER	0	0
	H9XK1X	RADIATOR TYPE	RADIATOR, CORE AREA W/O FEPTO 1345sq in (86sq dm), CORE AREA W/ FEPTO 1296sq in (83sq dm)	0	0
S	124AA3	HOSES - RADIATOR/HEATER	MACK EPDM RADIATOR & HEATER HOSES	0	0
s	293043	FUEL-WATER SEPARATOR	MACK W/MANUAL DRAIN VALVE W/ HOT RECIRCULATION (INTEGRAL W/ PRIMARY FUEL FILTER)	0	0
S	MBXA1X	PRIMARY FUEL FILTER POSITION (CA)	STANDARD FUEL FILTER POSITION	0	0
S	MCA00A	ENGINE HEATERS	NO COLD WEATHER STARTING AIDS PROVIDED	0	0
S	QHXC1X	OIL PAN	OIL PAN	0	0
s	36AA1X	TETHER DEV PKG, CAPS & COVERS	FURNISH CAP RETAINER FOR OIL FILL & RADIATOR OVERFLOW TANK	0	0
S	2YBZ1X	ENGINE STOP, EMERGENCY (CA)	WITHOUT ENGINE STOP, EMERGENCY	0	0

			WEIGH	T (LB)
CLUTCH/TRANS EQUIP	PMENT	DESCRIPTION	FRONT	REAR
492032	GEAR SHIFTER	EATON/FULLER SHIFTER	0	0
133AD1	CLUTCH	EATON ADVANTAGE EZ-PEDAL 9-SPRING,2PLATE 15.5" CERAMIC 6 PADDLES, MANUAL ADJUST	5	0
MCB04B	CLUTCH ACTUATION SYSTEM & PEDAL PAD	MECHANICAL CLUTCH CABLE SYSTEM WITH RUBBER PEDAL	0	0
2XAB1X	CLUTCH PEDAL PAD	RUBBER PAD	3	0
1950J5	DRIVELINE - MAIN	SPICER SPL250HDXL LITE - LARGE (PROPS-L)	-6	-6



				WEIGH	IT (LB)
CLUTCH/TRANS EQUIPMENT		IPMENT	DESCRIPTION	FRONT	REAR
	204044	DRIVELINE - INTERAXLE	SPICER SPL170XL "LITE SERIES"	0	0
s	76AA1X	PROPELLR SHAFT MAIN, UNVSL JNT	UNIVERSAL JOINT HALF-ROUND TYPE	0	0
S	XAAAW8	PROP SHAFT INTERAXL UNIV JOINT	HALF-ROUND UNIVERSAL JOINT	0	0
s	4LDA1X	TRANSMISSION OUTPUT TORQU	E TRANSMISSION OUTPUT TORQUE BASIC	0	0
S	RCXB1X	BELL HOUSING	ALUMINUM	0	0
s	7RXB1X	LUBRICANTS, TRANSMISSION	SYNTHETIC OIL IN TRANSMISSION	0	0
	139AA2	TRANSMISSION OIL COOLER	TRANS OIL COOLER (INTEGRAL OIL PUMP)	45	3

				WEIGH	iT (LB)
FRONT AXLE EQUIPMENT		MENT	DESCRIPTION	FRONT	REAR
s	240AA6	FRONT AXLE	12000# (5400 KG) MACK FXL12 STRAIGHT SPINDLE/UNITIZED BEARINGS	0	0
s	244AB2	SPRINGS - FRONT	MACK TAPERLEAF HD 12000# (5400 KG) GROUND LOAD RATING, EQUAL BIAS	0	0
s	2410A1	FRONT AXLE BRAKES	MERITOR "S" CAM TYPE 16.5" x 5" Q+	16	0
S	U3XA1X	BRAKE, FRONT	CAST IRON	0	0
s	U0AA1X	FRONT BRAKE ADJ. MANUFACTURE	HALDEX - AUTOMATIC	0	0
S	V7AB1X	FRONT BRAKE CHAMBER MFG.	FRONT BRAKE CHAMBER MANUFACTURER, HALDEX	0	0
s	0KXB1X	HUB MATERIAL, FRONT	ALUMINUM	73	0
S	245AA5	STEERING	TRW THP60 POWER	64	0
s	7VXC1X	LUBRICANTS, FRONT AXLE	PETROLEUM/SYNTHETIC (50/50) OIL FRONT AXLE	0	0

				WEIGH	IT (LB)
REAR A	AXLE EQUIPME	ENT	DESCRIPTION	FRONT	REAR
	268AB1	REAR AXLES - TANDEM	38000# (17200kg) MACK S38R FABRICATED STEEL HOUSING	0	1,420
S	6MAA1X	REAR AXLE CASING WIDTH	W/O WIDE TRACK AXLE	0	0
	018AA6	CARRIER - REAR AXLE	CRDP150/151 AVAILABLE WITH OPTIONAL DRIVER CONTROLLED INTERWHEEL DIFFERENTIAL LOCKS, SEE 254 SYMBOL	0	0
	TAXD7X	REAR AXLE RATIO	3.25 RATIO	0	0
	1860F6	REAR SUSPENSION - TANDEM	SS38 MACK MULTILEAF (CAMELBACK) 38000# CAPACITY, STANDARD SPRING THICKNESS	0	1,451
	XZXB1X	REAR SUSP. BEAM BUSHINGS	RUBBER	0	0
	GWXABX	BOGIE SPREAD, REAR	50" AXLE SPACING (BOGIE WHEELBASE)	0	0
	2AAAAX	REAR SPRING INSULATOR MAT'L	RUBBER SHOCK INSULATORS	0	0
	XYXB1X	TRANSVERSE TORQUE RODS, R SUSP	TRANSVERSE TORQUE ROD (REAR AXLE ONLY)	0	67
S	237027	AUX.SPRING BRAKE QTY	(2) DOUBLE DIAPHRAGM TYPE, MECHANICAL SPRING RELEASE	0	0
	253AA4	BRAKES - REAR	MERITOR "S" CAM 16.5"x7" Q+ (Total for QTY = 2)	0	27
S	U4XA1X	BRAKE, DRIVE, REAR	CAST IRON	0	0
s	U1AA1X	REAR BRAKE ADJ MANUFACTURE	HALDEX - AUTOMATIC (Total for QTY = 2)	0	0
	V1AB1X	REAR BRAKE CHAMBER SIZE	REAR SPRING BRAKE CHAMBERS 30/30 TYPE	0	0
s	300AS0	REAR BRAKE CHAMBER	HALDEX "GOLD SEAL PLUS" (3" STROKE) BRAKE CHAMBERS (Total for QTY = 2)	0	0
s	0LXI1X	HUB MATERIAL, DRIVE	ALUMINUM PRESET REAR HUB W/INTEGRATED SPINDLE NUT	0	212
s	7WXA1X	LUBRICANTS, REAR AXLE(s)	FACTORY OPTION LUBE - REAR AXLE	0	0
S	698098	ANTILOCK BRAKE SYSTEM	MACK ROAD STABILITY ADVANTAGE BENDIX ABS/ATC/ESP W/YAW CONTROL 4S4M	7	0
S	URXD1X	BRAKE VALVE VERSION	BENDIX SWITCHES AND VALVES WHERE POSSIBLE	0	0



				WEIGH	T (LB)
FRAME	E EQUIPMENT/	FUEL TANKS	DESCRIPTION	FRONT	REAR
	271187	WHEELBASE	187"	-125	-125
S	374056	AF (OVERHANG)	56"	9	67
	MCE01E	FRAME RAILS & LINERS	6 x 90 x 266mm - (0.24" x 3.54" x 10.47"); RBM 1,390,000 LB-IN	0	0
S	281AA2	CROSSMEMBERS	STEEL	0	0
	Q5AA1X	REAR CROSSMEMBER OPTIONS	STEEL CLOSING REAR CROSSMEMBER	7	-26
	X6XA1X	REAR FRAME TREATMENT	WITHOUT TAPERED FRAME RAIL ENDS	0	7
s	2HXA1X	MUDFLAP, FRONT AXLE	BLACK POLYARMOUR (NO NAME TO APPEAR ON FLAP) (NOT ANTI-SPRAY TYPE)	0	0
S	4DXP1X	FRONT BUMPER	FLUSH-STAINLESS CLAD ALUMINUM	98	-4
S	2RAA1X	FUEL LEVEL SENDER UNIT, LIQUID	BASIC FUEL LEVEL SENDER MOUNTED ON L.H TANK	0	0
	288AB2	FUEL TANK - LH	53 GALLON (200 L) 22" ALUMINUM ROUND	49	20
	290AA1	FUEL TANK - RH	W/O RH FUEL TANK	0	0
S	JHXA1X	FUEL HOSES, LIQUID	NYLON TUBE	0	0
s	8520C2	FUEL FILLER NECK OPTIONS	WITHOUT FILLER NECK SCREEN, WITH NON-LOCKABLE FUEL TANK CAP	0	0
	12AA1X	FUEL LINE OPTIONS, LIQUID	W/O FUEL LINE OPTION	-2	0
S	Q2AA1X	CAB INSTEP VERSION	STANDARD 2 STEP CAB ACCESS	0	0

				WEIGH	T (LB)
AIR/BRAKE			DESCRIPTION	FRONT	REAR
S	UWXD1X	AIRTANK DRAIN VALVE	MANUAL DRAIN VALVES, WITH LANYARD ON SUPPLY TANK ONLY	0	0
S	U2XB1X	AIRTANK MATERIAL	STEEL	0	0
S	141AA1	RELOCATE AIR RESERVOIRS	W/O RELOCATED AIR TANKS	0	0
S	1JAABX	PARKING BRAKE VALVE	TWO (2) VALVE DUAL BRAKE SYSTEM - TRAILER SUPPLY AND TRACTOR-TRAILER PARK	0	0

				WEIGH	IT (LB)
ELECTRICAL			DESCRIPTION	FRONT	REAR
s	3120A2	ROOF & SIDE MARKER LIGHTS	(5) TRUCKLITE CHROME BULLET ROOF MARKER & STANDARD MARKER / DIRECTIONAL SIGNAL	0	0
s	LSXJ7X	DAYTIME RUNNING LIGHTS	W/OVERRIDE SWITCH, PARK BRAKE & ENGINE RUNNING ACTIVATED	0	0
s	X2AA1X	DRL OVERRIDE SPEED THRESHOLD	DRL OVERRIDE SPEED THRESHOLD 8 KMPH (5 MPH)	0	0
	NEXC1X	TAIL LAMPS	INCANDESCENT TAIL LAMPS	0	0

				WEIGH	T (LB)
TRAIL	ER CONNECTIO	ONS	DESCRIPTION	FRONT	REAR
s	330AI6	FIFTH WHEEL	AIR - JOST JSK37USL SERIES, LH RELEASE (AVAIL: 6.73",7.76",8.74")	0	0
S	6DXH1X	5TH WHEEL MOUNTING BRACKETS	SLIDING 5TH WHEEL MTG, 24" TRAVEL	0	0
S	LIXA1X	FIFTH WHEEL ANGLE MATERIAL	STEEL FIFTH WHEEL ANGLES	0	0
S	9DAABX	5TH WHEEL ANGLE THICKNESS	5TH WHEEL ANGLE, 10MM THICKNESS	0	0
	6BX5PX	5TH WHEEL OFFSET	50" BOGIESPREAD = 0" OFFSET, 52" BS = 1", 54" BS = 2", 55" BS = 2.5"	0	0
	E5BADX	GROUND TO 5TH WHEEL TOP HGT.	1220MM (48") GROUND TO 5TH WHEEL TOP HEIGHT	0	0
	6EXBMX	FIFTH WHEEL LEG-HEIGHT (KAX Result)	171MM (6.75"), FIFTH WHEEL LEG-HEIGHT (SELECTED BY KAX)	0	0
S	53XBAX	TRAILER GLAD HAND COUPLINGS	GLAD HAND COUPLINGS - NORTH AMERICAN STD	0	0

### TECHNICAL SPECIFICATION (cont.)



				WEIGHT (LB	
TRAIL	ER CONNECTIO	ONS	DESCRIPTION	FRONT	REAR
s		TRAILER BRAKE VALVE	HAND CONTROL VALVE FOR TRAILER BRAKES W/ AIR CONNECTIONS OR SERVICE BRAKES W/O AIR CONNECTIONS	0	0
S		TRAILER AIR BRAKE CONNECTIONS, BACK OF CAB	0	0	
S	51XD1X	TRAILER BRAKE HOSEHANGER	HOSE TENDER, POGO STICK (CHASSIS MOUNTED)	0	0
S	321021	TRAILER ELECTRICAL RECEPT	SINGLE, 7 PINS STD SAE TYPE, BACK OF CAB	0	0
s	5ZXC1X	TRAILER BRAKE HOSES & CABLES	TRAILER AIR HOSES (12' NON-COILED TYPE)	0	0
S	2UAA1X	TRAILR ELECTRICAL CABLE CONFIG	TRAILER ELECTRICAL CORD (12' NON-COILED TYPE)	0	0
s	3SAA1X	TRAILER CONNECTORS HOLDER	ELECTRICAL PLUG HOLDER (INCLUDES GLAD HAND STORAGE)	0	0

					IT (LB)
PTO			DESCRIPTION	FRONT	REAR
S	2WAZ1X	PTO TRANS NEUTRAL CONTRL CHECK	W/O NEUTRAL CONTROL	0	0

					HT (LB)
SPECIALTY EQUIPMENT		ENT	DESCRIPTION	FRONT	REAR
S	MCQ01Q	LANE SUPPORT SYSTEM (LSS)	WITHOUT LANE SUPPORT SYSTEM	0	0
S	2PEZ1X	DATA CAPTURE	WITHOUT DATA CAPTURE	0	0
S	1PAZ1X	CAMERA, SURVEILLANCE	WITHOUT CAMERA	0	0
S	7VEZ1X	AUXILIARY POWER UNIT	WITHOUT AUXILIARY POWER UNIT	0	0

				WEIGH	IT (LB)
CAB INTERIOR (A THRU G)		IRU G)	DESCRIPTION	FRONT	REAR
S	S 198048 GAUGES - UNIT OF MEASURE U.S. UNITS (PREDOMINANT)		0	0	
	E1AAAX	GAUGE - REAR AXLE OIL TEMP	REAR AXLE OIL TEMP GAUGE IN DID (DRIVER INFORMATION DISPLAY)	0	0
s	173AA5	AIR CONDITIONING/HEATER	BLEND AIR HVAC W/"ATC" TEMP REGULATION	0	0
S	I0XAHX	DOME LAMP, INTERIOR	(4) DOME LAMPS - DOOR AND SWITCH ACTIVATED	0	0
s	V8DZ1X	CARBON MONOXIDE DETECTION SYS	DE DETECTION WITHOUT CARBON MONOXIDE DETECTION SYSTEM		0
S	184AA2	FLOOR COVERING	POLYURETHANE FLOOR MAT WITHOUT REMOVABLE INSERTS	0	0

				WEIGH	T (LB)
CAB IN	NTERIOR (H TH	RU R)	DESCRIPTION	FRONT	REAR
S	S C52082 INSTMNT CLUSTER LANGUAGE DE		DEFAULT: ENGLISH, SPANISH, FRENCH	0	0
s	20XA1X	KEY TYPES FOR DOORS	ALL CHASSIS KEYED AT RANDOM	0	0
s	13AA1X	DOOR OPENING OPTIONS	W/O ELECTRONIC KEYLESS ENTRY	0	0
s	S E3XC1X FORWA	FORWARD OVERHEAD STORAGE	COMPARTMENT W/NET	0	0
	174AA1	AUDIO ACCOMMODATION	W/O RADIO OR RADIO ACCOMMODATION PACKAGE	-8	0
s	1WAB1X	POWER LEADS	POWER LEADS (5-WAY BINDING POSTS FOR CB RADIO) IN HEADER CONSOLE	0	0
	5CXAEX	AUDIO SPEAKER LOCATION	SPEAKER LOCATION, BEHIND DOORS, MIDDLE HIGH SIDE PANEL	0	0
s	5JXALX	COM.RADIO PREP KIT (CB)	MOUNTING PLATE AND VELCRO STRAP IN HEADER CONSOLE	0	0
s	21XA1X	AUXILIARY REAR WINDOW	REAR WINDOW (FIXED TYPE)	0	0
S	IFXB1X	REAR WALL STORAGE COMPARTMENT	STORAGE POUCH REAR	0	0

20210104 BLAN2021000324C626 4/20/2021



				WEIGH	IT (LB)
AB II	NTERIOR (S THE	RU Z)	DESCRIPTION	FRONT	REA
	004014	INTERIOR TRIM LEVELS	STANDARD PACKAGE, STEEL GRAY (Package 11A)	0	0
	196AAA	SEAT - DRIVER'S	MACK-AIR, HIGH BACK, 1 CHAMBER AIR LUMBAR	71	16
	MAPB2X	SEAT COVERING - DRIVER'S	DRIVER'S SEAT - STEEL GREY VINYL	0	0
	592082	SEAT BELT(S)	LAP & SHOULDER (DRIVER'S SEAT ONLY)	0	0
	2QAA1X	IGNITION TYPE	KEY TYPE	0	0
	161005	STEERING WHEEL	2 SPOKE URETHANE GRIP, GUNMETAL SPOKES, W/O SWITCHES	0	0
	WSXBAX	WINDSHIELD TYPE	TWO PIECE WINDSHIELD	0	0
	145AA1	CAB GLASS	TINTED WINDSHIELD & SIDE WINDOWS & REAR WINDOW (IF EQUIPPED)	0	0
	148AA3	WINDSHIELD WIPERS	2 SPEED ELECTRIC MOTOR W/INTERMITTENT FEATURE	0	0
				WEIGH	HT (LB)
AB -	SLEEPER BOX		DESCRIPTION	FRONT	REA
	4ZXZ1X	REFRIGERATOR	W/O SLEEPER BOX REFRIGERATOR	0	0
				WEIGH	HT (LB)
AB E	XTERIOR		DESCRIPTION	FRONT	REA
	88AA1X	EMBLEMS OPTION	W/O MISC ORNAMENT CHANGE OPTION	0	0
	MCG04G	AIR INTAKE GRILL / HOOD LATCH - FINISH	BLACK AIR INTAKE WITH BLACK HOOD LATCHES	0	0
	400AG0	GRILLE	HERITAGE DESIGN CHROME GRILLE W/ BLACK BACKGROUND	0	0
	MCD03D	PASSENGER SIDE VISIBILITY OPTIONS	AUXILIARY WINDOW IN RH DOOR	3	0
	5870G7	GRAB HANDLES	PREMIUM BLACK EXTERIOR CAB GRAB HANDLE, BLACK GRAB	0	0
	LXXC1X	HORN - ELECTRICAL	HANDLE RH INTERIOR WINDSHIELD POST SINGLE TONE	0	0
	1520A2	MIRRORS - EXTERIOR	AERO MIRROR - BLACK, WIDE ANGLE both sides, W/O LAMPS	0	0
				WEIGH	HT (LB)
FRO	DYNAMIC DEVIC	CFS	DESCRIPTION	FRONT	REA
_,,,	159AA1	CAB AERODYNAMIC PACKAGES	WITHOUT CAB AERODYNAMIC DEVICES	0	0
	MCM998	FRONT CHASSIS AERODYNAMIC	WITHOUT FRONT AERODYNAMIC FAIRINGS	0	0
	мскозк	PACKAGE REAR CHASSIS AERODYNAMIC PACKAGE	WITHOUT REAR AERODYNAMIC FAIRING	0	0
HEE	LS & TIRES		DESCRIPTION	WEIGH FRONT	HT (LB) REA
	900AS0	TIRES BRAND/TYPE - FRONT	11R22.5 G BRIDGESTONE R268 ECOPIA (12350 lbs) (Total for QTY =	243	0
	4WCC1X	GHG STEER TIRE CATEGORY	2) LOW ROLLING RESISTANCE, BETTER FUEL ECONOMY	0	0
		(PAWS)	22.5x8.25 ACCURIDE ACCU-LITE WHITE POWDER COAT STEEL,		
	5312D1	WHEELS - FRONT	6.60" OFFSET, 5 HAND HOLE (Total for QTY = 2) 11R22.5 G BRIDGESTONE M713 ECOPIA (23360 lbs) (DRIVE ONLY)	137	0
	901601	TIRES BRAND/TYPE - REAR	(Total for QTY = 8)	0	953
	4XCA1X	GHG DRIVE TIRE CATEGORY (PAWS)	ADVANCED LOW ROLLING RESISTANCE, BEST FUEL ECONOMY	0	0
	3462J6	WHEELS - REAR	22.5x8.25 ACCURIDE ACCU-LITE WHITE POWDER COAT STEEL, 6.60" OFFSET, 5 HAND HOLE (Total for QTY = 8)	0	547
	H1EB1X	DRIVE WHEEL STUDS	DRIVE WHEEL STUDS LONGER LENGTH	0	0
	15XABX	TIRE INFLATION VALVE	STANDARD VALVE STEMS AND CAPS	0	0

NC SHERIFFS' ASSOCIATION INC

6 of 11

TRANSOURCE, INC.

### TECHNICAL SPECIFICATION (cont.)

20210104 BLAN2021000324C626 4/20/2021



				WEIGH	IT (LB)
VHEE	LS & TIRES		DESCRIPTION	FRONT	REA
	МСН03Н	FRONT HUB/WHEEL TRIM	WITHOUT FRONT HUB/WHEEL TRIM	0	0
	MCI03I	REAR HUB/WHEEL TRIM	WITHOUT REAR HUB/WHEEL TRIM (Total for QTY = 2)	0	0
	MCJ03J	AUXILIARY HUB/WHEEL TRIM	WITHOUT AUXILIARY HUB/WHEEL TRIM	0	0
	80AA1X	WHEEL NUT & FINISH, FRONT	WHEEL NUT BASIC FINISH, FRONT	0	0
	3PBA1X	WHEEL NUT FINISH, REAR (CA)	WHEEL NUT BASIC FINISH, REAR	0	0
				WEIGH	IT (LB)
MC	MUNICATION SY	YSTEMS	DESCRIPTION	FRONT	REA
	3YAA1X	CO-PILOT - DISPLAY FEATURES ACCESS LEVEL	CO-PILOT DISPLAY, DRIVER ACCESS LEVEL 1	0	0
	M30060	TELEMATIC GATEWAY	TELEMATICS GATEWAY, 4G/LTE AND WLAN SYSTEM WITH	0	0
		SOFTWARE DOWNLOAD	DIAGNOSTIC SERVICES SOFTWARE DOWNLOAD NOTIFICATION TO DRIVER, POPUP &		
	9YDA1X	NOTIFICAQTION	ICON	0	0
				WEIGH	IT (LB)
VGI1	NE ELECTRONI		DESCRIPTION	FRONT	REA
	WOXA1X	OIL PRESSURE, ENGINE SHUTDOWN	OIL PRESSURE, ENGINE SHUTDOWN	0	0
	WMXA1X	COOLANT TEMP, ENGINE SHUTDOWN	COOLANT TEMP, ENGINE SHUTDOWN	0	0
	K5XA2X	ENGINE PROTECTION SYSTEM	ENGINE PROTECTION (SHUTDOWN)	0	0
	C7AABX	ENG FAN CNTL, A/C ON, TIME SET	ENG FAN CONTROL, A/C ON, TIME SETTING, 60 SEC	0	0
	K7XH3X	ENGINE IDLE CONTROL	IDLE CONTROL, 650 RPM	0	0
	X0AB0X	SMART IDLE ELEVATED IDLE RPM TIME	INCREASE 10 MINUTE MAXIMUM TIME	0	0
	M3CA1X	IDLE S/D ABS TAMPER CHECK	IDLE SHUTDOWN ABS TAMPER CHECK, ENABLED	0	0
	A8AALX	IDLE S/D IF WARM-UP TEMP	38C DEG (100F), WARM UP TEMP DELAY	0	0
	A4AAEX	IDLE S/D WARM-UP TIMER	5 MIN. WARM UP TIME DELAY	0	0
	B0AAAX	IDLE SHUTDOWN IF POWER >	ENG IDLE SHUTDOWN TIME OVERRIDDEN IF TORQUE > THAN	0	0
	M4CB1X	LIMIT IDLE S/D OVERIDE %ENGINE	LIMIT IDLE SHUTDOWN OVERIDE UPTO 20% ENGINE LOAD THRESHOLD	0	0
	D2AAFX	LOAD  AMBIENT TEMP MIN TRESHOLD	AMBIENT TEMP MIN TRESHOLD, 16 DEG C, (60 DEG F)	0	0
	D3AAEX	AMBIENT TEMP MAX TRESHOLD	AMBIENT TEMP MAX TRESHOLD, 10 DEG C, (60 DEG F)	0	0
		EL HD THROTTLE,MAX ROAD	ELECTRONIC HAND THROTTLE, MAX ROAD SPEED, 16 KMH (10		
	B3ABAX	SPEED EL HAND THROTTLE,MAX ENG	MPH)	0	0
	B6ABAX	SPEED	ELECTRONIC HAND THROTTLE, MAX ENGINE SPEED, 1000 RPM	0	0
	B4ADAX	EL HAND THROTTLE,MIN ENG SPEED	ELECTRONIC HAND THROTTLE, MIN ENGINE SPEED, 700 RPM	0	0
				WEIGH	IT (LB)
RAN	SMISSION ELE	CTRONICS	DESCRIPTION	FRONT	REA
	M08038	ECONO ROLL	ECONO ROLL DISABLE mDRIVE (REQUIRED FOR ALL OTHER TRANSMISSIONS)	0	0
	779001	TRANSMISSION ELECTRONICS	W/O ELEC TRANS PACKAGE OPTION (all non-Allison transmissions)	0	0
	MAV01V	PACKAGE TRANSMISSION ELECTRONIC SHIFTING PROPERTIES	W/O ALLISON FUELSENSE 2.0 PROGRAMMING	0	0
				WEIGH	łΤ ( <u>LΒ)</u> _
EHIC	CLE ELECTRON	IICS	DESCRIPTION	FRONT	REA
	JCXE6X	ROAD SPEED LIMITER SETTING	105 KM/H ROAD SPEED LIMITER(65 MPH)	0	0

NC SHERIFFS' ASSOCIATION INC

7 of 11

TRANSOURCE, INC.



				WEIGH	IT (LB)
VEHIC	CLE ELECTRONI	ics	DESCRIPTION	FRONT	REAR
S	Y3CC1X	PEDAL RSL SETTING	101 KM/H PEDAL ROAD SPEED LIMITER (63MPH)	0	0
S	JDXA1X	CRUISE CONTROL	CRUISE CONTROL	0	0
S	JFXLLX	CRUISE CONTROL, MAX SPEED	MAX CRUISE, 105 KPH (65 MPH)	0	0
S	E3AACX	CRUISE CONTROL MIN SPEED	MIN CRUISE, 32 KPH (20 MPH)	0	0
S	S E4AAAX CRUISE RESUME WITH C	CRUISE RESUME WITH CLUTCH	CRUISE RESUME WITH CLUTCH	0	0
S	E5AACX	ENG BRK ENGAGE IN CRUISE	ENG BRK ENGAGE IN CRUISE, 3 MPH, ABOVE SET SPEED	0	0
S	X2BB1X	ROAD SPEED LIMIT CONTROL TYPE	RSL CONTROL TYPE NORMAL	0	0
s	L2CA1X	PDLO ENGAGED VLS	POWER DIVIDER LOCK OUT (PDLO) ROAD SPEED LIMIT 8KMH (5MPH)	0	0
S	W5BA1X MAXIMUM ENG SPEED AT 0 MPH		1000 MAXIMUM ENGINE SPEED AT 0 MPH	0	0
S	A4BAAX DETECTION SPEED SENSR TMPRNG		DETECTION OF SPEED SENSOR TAMPERING, ENABLE	0	0
s	8RXAEX	ENG TORQUE LIMIT, SPEED ENG	ENG TORQUE LIMITED TO 50%, IF SPEED SENSOR TAMPER DETECTED	0	0
S	X3CB1X	DRIVER ID FUNCTION	DRIVER ID FUNCTION, DISABLED	0	0
S	0PAZ1X	DR PERFORMANCE PARAMETERS	WITHOUT DRIVER PERFORMANCE PARAMETERS	0	0
s	G5AAHX	ENGINE OVERSPEED,ALL COND, LOG	ENGINE OVERSPEED, ALL CONDITIONS, TIME LOG IF ABOVE 2200 RPM	0	0
S	G2AAGX	ENGINE OVERSPEED, FUELED, LOG	ENGINE OVERSPEED, FUELED, TIME LOG IF ABOVE 2100 RPM	0	0
s	G4AAUX	VEHICLE OVERSPEED,ALL COND,LOG	VEHICLE OVERSPEED,ALL COND, TIME LOG IF ABOVE 75MPH (121KMH)	0	0
s	G3AAPX	VEHICLE OVERSPEED, FUELED, LOG	VEHICLE OVERSPEED, FUELED, TIME LOG IF ABOVE 70MPH (113KMH)	0	0
S	G1AABX	ENGINE IDLE DELAY TO LOG	ENGINE IDLE DELAY TO START LOG, 2 MIN	0	0
S	W9A01X	PERIODIC TRIP LOG DAY OF MONTH	PERIODIC TRIP LOG, DAY 1 OF THE MONTH	0	0

				WEIGH	T (LB)
PAINT			DESCRIPTION	FRONT	REAR
s	950AC0	PAINT DESIGN	SINGLE COLOR	0	0
s	924014	PAINT TYPE	SOLID PAINT	0	0
	944DR8	PAINT COLOR - FIRST COLOR	WHITE; L0006	0	0
s	945998	PAINT COLOR - SECOND COLOR	NO SECOND TRUCK COLOR PROVIDED; NO COLOR	0	0
S	946998	PAINT COLOR - THIRD COLOR	NO THIRD TRUCK COLOR PROVIDED; NO COLOR	0	0
s	996AA3	PAINT - CAB PAINT SYSTEM	PAINT - CAB, URETHANE CLEAR COAT	0	0
S	MPB944	CAB COLOR	SAME AS FIRST COLOR - CAB	0	0
S	MPD944	HOOD COLOR	SAME AS FIRST COLOR - HOOD	0	0
S	MPA998	ROOF FAIRING COLOR	WITHOUT ROOF FAIRING	0	0
S	951AA6	CHASSIS RUNNING GEAR	MACK BLACK (URETHANE)	0	0
s	958028	BUMPER	W/O OPTIONAL BUMPER PAINT	0	0
s	959019	FUEL TANK - ***NO INVENTED VARIANTS ALLOWED in the FUEL TANK PAINT FAMILY***	W/O OPTIONAL FUEL TANK PAINT	0	0
S	962032	HUBS & DRUMS-FRONT	SAME AS CHASSIS RUNNING GEAR	0	0
S	963033	HUBS & DRUMS-REAR	SAME AS CHASSIS RUNNING GEAR	0	0

					HT (LB)
CAL	CALCULATED CODES - KAX		DESCRIPTION	FRONT	REAR
S 9JXA1X PROPCALC SELECTION		PROPCALC SELECTION	YES, THE ORDER MUST BE CALCULATED	0	0

PRICELIST DATE	QUOTATION	DATE	PAGE	CUSTOMER NAME	DEALER NAME
20210104	BLAN2021000324C626	4/20/2021	8 of 11	NC SHERIFFS' ASSOCIATION INC	TRANSOURCE, INC.

### TECHNICAL SPECIFICATION (cont.)




				WEIGH <sup>*</sup>	T (LB)
	CALCULATED CODES	- KAX	DESCRIPTION	FRONT	REAR
Ī	D5EA1X	AUTO ROUTING & CLIPPING, CENTER	AUTOMATIC ROUTING & CLIPPING PLACEMENT, CENTER SECTION	0	0

				WEIGH	T (LB)
BASE	WARRANTY &	PURCHASED COVERAGES	DESCRIPTION	FRONT	REAR
S	898002	VEHICLE WARRANTY TYPE	NORMAL DUTY WARRANTY CLASSIFICATION	0	0
s	M50020	BASIC CHASSIS COVERAGE	NORMAL DUTY STANDARD BASE COVERAGE 12 MONTHS/100,000 MILES (161,000KM)	0	0
s	M51021	ENGINE WARRANTY	MACK MP7/MP8 BASE ENGINE COVERAGE 24 MONTHS / 250,000 MILES (402,000KM)	0	0
s	M52022	EMISSION COMPONENT COVERAGE	US and CANADA EQUIPPED VEHICLE EMISSION COMPONENTS COVERAGE 60 MONTHS/100,000 MILES (161,000 KM)	0	0
	M54094	TRANSMISSION WARRANTY	36/350K MI: EATON TRANSMISSION STANDARD NORMAL AND HEAVY DUTY COVERAGE	0	0
	M550G6	CARRIER & AXLE HOUSING WARRANTY	STANDARD MACK NORMAL DUTY COVERAGE 60 MONTHS / 750,000 (1,207,008 KM)	0	0
s	M56026	AIR CONDITIONING WARRANTY	AIR CONDITIONING STANDARD COVERAGE (Sealed System Only) 12 MONTHS UNLIMITED MILEAGE	0	0
s	M57027	CHASSIS TOWING WARRANTY	STANDARD NORMAL / HEAVY DUTY CHASSIS TOWING 90 DAYS OR 5,000 MILES	0	0
s	M58028	ENGINE TOWING WARRANTY	STANDARD MACK ENGINE TOWING COVERAGE 24 MONTHS/250,000 MILES (402,000 KM)	0	0
s	M690F9	GUARDDOG CONNECT BUNDLE	24 MONTH - GUARDDOG CONNECT WITH MACK OTA (with ASIST and Mack OneCall))	0	0
S	M78010	PREPAID API	WITHOUT PREPAID API	0	0
s	M67017	PREMIUM MAINTENANCE - CHASSIS LUBE AND INSPECTION	W/O PREMIUM MAINTENANCE - CHASSIS LUBE AND INSPECTION COVERAGE	0	0

		WEIGH	HT (LB)	
ADDITIONAL ENGINEERING (NonApproved)	DESCRIPTION	FRONT	REAR	
CA 1		0	0	
	FRONT / REAR AXLE WEIGHTS (LB)	8535	8087	
	TOTAL WEIGHT (LB)	16	16621	



VEHICLE SPECIFICATION/CALCULATED PERFORMANCE SUMMARY						
Description	Sales Code	Dwg Ref	Length	UOM		
Front Frame Extension	N/A	FE	0.0	INCHES		
Bumper to Front Axle	N/A	BA	29.8	INCHES		
Wheelbase	N/A	WB	186.8	INCHES		
Rear Overhang	N/A	ОН	56.3	INCHES		
Overall Length	N/A	OL	272.9	INCHES		
Bumper to Back of Cab	N/A	BBC	117.3	INCHES		
Eff. Bumper to Back of Cab	N/A	EBBC	117.3	INCHES		
Eff. Cab to Rear Axle	N/A	ECA	99.3	INCHES		
Eff. Front Axle to Back of Cab	N/A	EAC	87.5	INCHES		
Eff. Cab to End of Frame	N/A	ECEF	155.6	INCHES		
Unladen 5th Wheel Height	E5BADX	5W	48.0	INCHES		
Unladen Frame Height	N/A	FH	41.9	INCHES		
Cab Height	N/A	СН	73.0	INCHES		
Overall Height	N/A	OVH	114.9	INCHES		
Driver CG	N/A	DCG	73.2	INCHES		
50" AXLE SPACING (BOGIE WHEELBASE)	GWXABX	BS	50.0	INCHES		
Second Front Axle Spacing	RHXZ1X	SFAS	0.0	INCHES		





VEHICLE SPECIFICATION/CALCULATED PERFORMANCE SUMMARY					
Description	Sales Code	Dwg Ref	Left Value(in)	Right Value(in)	
Wheelbase	N/A	WB	186.8	186.8	
Available Rail Space Right	N/A	ARSR	N/A	42.5	
Available Rail Space Left	N/A	ARSL	41.5	N/A	
Eff. Front Axle to Back of Cab	N/A	REF	87.5	87.5	
Front Axle To Fender	CDX30X	N/A	48.4	35.4	
Cleartech One Unit	DPF04F	N/A	0.0	48.0	
Battery Box	393AA9	N/A	0.0	15.0	
53 GALLON (200 L) 22" ALUMINUM ROUND / W/O RH FUEL TANK	288AB2 / 290AA1	N/A	35.0	0.0	
Ad-Blue Tank	DF10M1	N/A	16.0	0.0	
Drive Tire Radius	901601	N/A	20.9	20.9	

Top View image is intended for illustration purposes only and is not presented to scale. Wheelbase, Axle Spacing and After frame are not shown as specified, but are a representation. Customer Adaptation (CA) options and relocated components are not represented in these images. Most CA options impact the variation of the image, thus an image may not populate. Calculations are approximate to a tolerance of ± 4 inches due to component mounting variation. Certain chassis component options are NOT represented in the Top View image, such as, but not exclusive to, Front Frame Extensions, Fuel Water Separators, Air Dryers, PTOs, Fifth Wheels, Chassis Fairings, Toolboxes, Trailer Connections. For further information on these items and their respective locations on your specification, please refer to the data sheets associated with those items in the configurator.

