SPECIFICATION PROPOSAL

| | Data Code | Description | Weight Front | Weight Rear | |
|---------|-----------------|---|-----------------|----------------|--|
| Price L | evel | | | | |
| | PRL-17M | M2 PRL-17M (EFF:11/14/17) | | | |
| Data Ve | ersion | | | | |
| | DRL-011 | SPECPRO21 DATA RELEASE VER 011 | | | |
| Vehicle | e Configuration | on | | | |
| | 001-172 | M2 106 CONVENTIONAL CHASSIS | 5,759 | 3,503 | |
| | 004-219 | 2019 MODEL YEAR SPECIFIED | | | |
| | 002-004 | SET BACK AXLE - TRUCK | | | |
| | 019-002 | STRAIGHT TRUCK PROVISION | | | |
| | 003-012 | PREP FOR LH PRIMARY STEERING LOCATION AND CUSTOMER SUPPLIED RH SIT-DOWN SECONDARY STEERING LOCATION WITH DUAL INSTRUMENT CLUSTER | | | |
| Genera | I Service | | | | |
| | AA1-002 | TRUCK CONFIGURATION | | | |
| | AA6-001 | DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES) | | | |
| | A85-010 | UTILITY/REPAIR/MAINTENANCE SERVICE | | | |
| | A84-1GM | GOVERNMENT BUSINESS SEGMENT | | | |
| | AA4-011 | FIXED LOAD COMMODITY | | | |
| | AA5-002 | TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS | | | |
| | AB1-008 | MAXIMUM 8% EXPECTED GRADE | | | |
| | AB5-001 | SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE | | | |
| | 995-091 | MEDIUM TRUCK WARRANTY | | | |
| | A66-99D | EXPECTED FRONT AXLE(S) LOAD: 12000.0 lbs | | | |
| | A68-99D | EXPECTED REAR DRIVE AXLE(S) LOAD : 21000.0 lbs | | | |



| | Data Code | Description | Weight Front | Weight Rear | |
|---------|--------------|--|-----------------|----------------|--|
| | A63-99D | EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 33000.0 lbs | | | |
| | A70-99D | EXPECTED GROSS COMBINATION WEIGHT: 0.0 lbs | | | |
| Truck | Service | | | | |
| | AA3-022 | STREET SWEEPER BODY | | | |
| | A88-99D | EXPECTED TRUCK BODY LENGTH: 11.0 ft | | | |
| | AF3-999 | CUSTOM MFR'S/BODY TYPE IDENTIFICATION | | | |
| | S | CCARAB | | | |
| | AF7-99D | EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE FRAME "XX" INCHES: 32.0 in | | | |
| Engine | | | | | |
| | 101-21N | CUM B6.7 200 HP @ 2400 RPM, 2600 GOV, 520 LB/FT @ 1600 RPM | | | |
| Electro | nic Paramete | ers | | | |
| | 79A-075 | 75 MPH ROAD SPEED LIMIT | | | |
| | 79B-000 | CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT | | | |
| | 79F-004 | CUMMINS TRIP INFORMATION REPORTS ENABLED; LEVEL 1: 4 MPH, LEVEL 2: 7 MPH ABOVE ROAD SPEED LIMIT | | | |
| | 79K-002 | PTO MODE ENGINE RPM LIMIT - 700 RPM | | | |
| | 79M-001 | PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED | | | |
| | 79P-002 | PTO RPM WITH CRUISE SET SWITCH - 700 RPM | | | |
| | 79Q-002 | PTO RPM WITH CRUISE RESUME SWITCH - 700 RPM | | | |
| | 79S-001 | PTO MODE CANCEL VEHICLE SPEED - 5 MPH | | | |
| | 79U-007 | PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND | | | |
| | 80G-002 | PTO MINIMUM RPM - 700 | | | |
| | 80J-001 | REGEN INHIBIT SPEED THRESHOLD - 0 MPH | | | |
| Engine | Equipment | | | | |
| | 99C-017 | 2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION | | | |
| | 99D-011 | 2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR) | | | |
| | 13E-001 | STANDARD OIL PAN | | | |
| | 105-001 | ENGINE MOUNTED OIL CHECK AND FILL | | | |
| | 133-004 | ONE PIECE VALVE COVER | | | |



| Data Code | Description | Weight Front | Weight Rear | |
|-----------|--|-----------------|----------------|--|
| 014-099 | SIDE OF HOOD AIR INTAKE WITH FIREWALL MOUNTED DONALDSON AIR CLEANER | | | |
| 124-1D7 | DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE | | | |
| 292-098 | (2) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 2250 CCA THREADED STUD BATTERIES | | | |
| 290-017 | BATTERY BOX FRAME MOUNTED | | | |
| 281-001 | STANDARD BATTERY JUMPERS | | | |
| 282-001 | SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB | | | |
| 291-017 | WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN | | | |
| 289-001 | NON-POLISHED BATTERY BOX COVER | | | |
| 293-058 | POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT | 8 | | |
| 295-029 | POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER | 2 | | |
| 107-032 | CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE | | | |
| 108-002 | STANDARD MECHANICAL AIR COMPRESSOR GOVERNOR | | | |
| 131-013 | AIR COMPRESSOR DISCHARGE LINE | | | |
| 152-041 | ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM | | | |
| 016-1C2 | RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE | 30 | 25 | |
| 28F-002 | ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH | | | |
| 239-026 | 10 FOOT 06 INCH (126 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT | | | |
| 237-1CR | RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP | | | |
| 23U-001 | 6 GALLON DIESEL EXHAUST FLUID TANK | | | |
| 30N-003 | 100 PERCENT DIESEL EXHAUST FLUID FILL | | | |
| 43X-002 | LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION | | | |
| 23Y-001 | STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING | | | |



| | Data Code | Description | Weight Front | Weight Rear |
|--------|---------------|--|-----------------|----------------|
| | 43Y-001 | STANDARD DIESEL EXHAUST FLUID TANK CAP | | |
| | 242-011 | ALUMINUM AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD(S) | | |
| | 273-035 | HORTON HT650 FRONTAL AIR ON/OFF ENGINE FAN CLUTCH | | |
| | 276-001 | AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED | | |
| | 110-003 | CUMMINS SPIN ON FUEL FILTER | | |
| | 118-001 | FULL FLOW OIL FILTER | | |
| | 266-078 | 950 SQUARE INCH ALUMINUM RADIATOR | | |
| | 103-039 | ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT | | |
| | 171-007 | GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT | | |
| | 172-001 | CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES | | |
| | 270-016 | RADIATOR DRAIN VALVE | | |
| | 168-002 | LOWER RADIATOR GUARD | | |
| | 134-001 | ALUMINUM FLYWHEEL HOUSING | | |
| | 132-004 | ELECTRIC GRID AIR INTAKE WARMER | | |
| | 155-057 | DELCO 12V 29MT STARTER WITH INTEGRATED MAGNETIC SWITCH | | |
| Transm | ission | | | |
| | 342-1MN | ALLISON 2500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION | | |
| Transm | ission Equipi | ment | | |
| | 343-301 | ALLISON VOCATIONAL PACKAGE 354 - AVAILABLE ON 1000/2000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, EVS, HS, MH, PTS AND SPS | | |
| | 84B-012 | ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES | | |
| | 84C-007 | PRIMARY MODE GEARS, 6 FORWARD GEARS WITH MANUAL SELECTION FOR 3, 2 AND 1, AVAILABLE FOR 1000/2000 PRODUCT FAMILIES ONLY | | |
| | 84E-000 | PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE | | |
| | 84F-000 | SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE | | |



| | Data Code | Description | Weight Front | Weight Rear |
|---------|---------------|---|-----------------|----------------|
| | 84G-000 | PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE | | |
| | 84H-000 | SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE | | |
| | 84L-010 | DISABLE - LOAD BASED SHIFT SCHEDULE, DISABLE - VEHICLE ACCELERATION CONTROL | | |
| | 84N-000 | NEUTRAL AT STOP - DISABLED, FUELSENSE - DISABLED | | |
| | 84U-000 | DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES | | |
| | 34C-002 | ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR MOUNTED BACK OF CAB | | |
| | 341-018 | MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN | | |
| | 345-075 | DASH MOUNTED T-HANDLE SHIFT CONTROL, PROVIDE 83 INCH CABLE FOR SUPPLIER RELOCATION OF T-HANDLE SHIFTER WITHOUT PARK BRAKE POSITION TO CENTER CONSOLE | | |
| | 97G-006 | TRANSMISSION PROGNOSTICS - DISABLED (N/A) 2013, FOR USE IN 1000/2000 ONLY | | |
| | 370-015 | WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK | | |
| | 346-001 | TRANSMISSION OIL CHECK AND FILL | | |
| | 35T-001 | SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT) | | |
| Front A | xle and Equip | oment | | |
| | 400-1A6 | DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE | | |
| | 402-020 | MERITOR 15X4 Q+ CAM FRONT BRAKES | | |
| | 403-002 | NON-ASBESTOS FRONT BRAKE LINING | | |
| | 419-023 | CONMET CAST IRON FRONT BRAKE DRUMS | | |
| | 427-001 | FRONT BRAKE DUST SHIELDS | 5 | |
| | 409-006 | FRONT OIL SEALS | | |
| | 408-001 | VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL | | |
| | 416-022 | STANDARD SPINDLE NUTS FOR ALL AXLES | | |
| | 405-002 | MERITOR AUTOMATIC FRONT SLACK ADJUSTERS | | |
| | 536-050 | TRW THP-60 POWER STEERING | | |
| | 539-003 | POWER STEERING PUMP | | |



| Data Code | Description | Weight Front | Weight Rear | |
|-------------------------|---|-----------------|----------------|--|
| 534-015 | 2 QUART SEE THROUGH POWER STEERING RESERVOIR | | | |
| 40T-002 | SYNTHETIC 75W-90 FRONT AXLE LUBE | | | |
| Front Suspension | | | | |
| 620-1E9 | 12,000# MONO TAPERLEAF FRONT SUSPENSION | | | |
| 619-005 | MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION | | | |
| 410-001 | FRONT SHOCK ABSORBERS | | | |
| Rear Axle and Equ | ipment | | | |
| 420-117 | RS-21-230 21,000# R-SERIES 2-SPEED SINGLE REAR AXLE | | 90 | |
| 421-023 | 5.86/8.17 REAR AXLE RATIO | | | |
| 424-001 | IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING | | | |
| 386-055 | SPL100 DANA SPICER MAIN DRIVELINE WITH HALF ROUND YOKES | -15 | -15 | |
| 423-020 | MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES | | | |
| 433-002 | NON-ASBESTOS REAR BRAKE LINING | | | |
| 434-011 | BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) | | | |
| 451-023 | CONMET CAST IRON REAR BRAKE DRUMS | | | |
| 425-002 | REAR BRAKE DUST SHIELDS | | | |
| 440-006 | REAR OIL SEALS | | | |
| 426-100 | WABCO TRISTOP D LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS | | | |
| 428-002 | MERITOR AUTOMATIC REAR SLACK ADJUSTERS | | | |
| 876-004 | ELECTRIC OVER AIR CONTROL WITH INDICATOR LAMP FOR 2-SPEED REAR AXLE | | | |
| 87C-001 | LOW RANGE TWO-SPEED DEFAULT WITH IGNITION OFF | | | |
| 898-002 | AIR SHIFTER FOR 2-SPEED REAR AXLE | | | |
| 41T-002 | SYNTHETIC 75W-90 REAR AXLE LUBE | | | |
| Rear Suspension | | | | |
| 622-1MJ | 23,000# 52 INCH VARIABLE RATE MULTI-LEAF SPRING REAR SUSPENSION WITH LEAF SPRING HELPER | | 110 | |
| 621-001 | SPRING SUSPENSION - NO AXLE SPACERS | | | |
| 431-001 | STANDARD AXLE SEATS IN AXLE CLAMP GROUP | | | |



| Data Code | Description | Weight Front | Weight Rear | |
|----------------------------|--|-----------------|----------------|--|
| Brake System | | | | |
| 018-002 | AIR BRAKE PACKAGE | | | |
| 490-100 | WABCO 4S/4M ABS WITHOUT TRACTION CONTROL | | | |
| 871-001 | REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES | | | |
| 904-001 | FIBER BRAID PARKING BRAKE HOSE | | | |
| 412-001 | STANDARD BRAKE SYSTEM VALVES | | | |
| 46D-002 | STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM | | | |
| 413-002 | STD U.S. FRONT BRAKE VALVE | | | |
| 432-003 | RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE | | | |
| 480-083 | WABCO SS-1200 PLUS AIR DRYER WITH INTEGRAL AIR GOVERNOR AND HEATER | | | |
| 479-012 | AIR DRYER MOUNTED UNDER HOOD | | | |
| 460-008 | STEEL AIR BRAKE RESERVOIRS MOUNTED INSIDE RAIL | | | |
| 607-001 | CLEAR FRAME RAILS FROM BACK OF CAB TO FRONT REAR SUSPENSION BRACKET, BOTH RAILS OUTBOARD | | | |
| 477-001 | PULL CABLE ON WET TANK, PETCOCK DRAIN VALVES ON ALL OTHER AIR TANKS | | | |
| Trailer Connections | | | | |
| 335-004 | UPGRADED CHASSIS MULTIPLEXING UNIT | | | |
| 32A-002 | UPGRADED BULKHEAD MULTIPLEXING UNIT | | | |
| Wheelbase & Frame | | | | |
| 545-452 | 4525MM (178 INCH) WHEELBASE | | | |
| 546-099 | 9/32X3-7/16X10-1/16 INCH STEEL FRAME (7.14MMX255.6MM/0.281X10.06 INCH) 120KSI | -60 | -10 | |
| 552-030 | 1600MM (63 INCH) REAR FRAME OVERHANG | | | |
| 55W-006 | FRAME OVERHANG RANGE: 61 INCH TO 70 INCH | | | |
| AC8-99D | CALC'D BACK OF CAB TO REAR SUSP C/L (CA): 112.45 in | | | |
| AE8-99D | CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA): 109.45 in | | | |
| AE4-99D | CALC'D FRAME LENGTH - OVERALL: 270.39 | | | |
| AM6-99D | CALC'D SPACE AVAILABLE FOR DECKPLATE : 112.45 in | | | |
| FSS-0LH | CALCULATED FRAME SPACE LH SIDE: 117.7 in | | | |
| FSS-0RH | CALCULATED FRAME SPACE RH SIDE: 97.67 in | | | |



| Data Code | Description | Weight Front | Weight Rear | |
|--------------------------|---|-----------------|----------------|--|
| 553-001 | SQUARE END OF FRAME | | | |
| 550-001 | FRONT CLOSING CROSSMEMBER | | | |
| 559-001 | STANDARD WEIGHT ENGINE CROSSMEMBER | | | |
| 562-001 | STANDARD MIDSHIP #1 CROSSMEMBER(S) | | | |
| 572-001 | STANDARD REARMOST CROSSMEMBER | | | |
| 565-001 | STANDARD SUSPENSION CROSSMEMBER | | | |
| Chassis Equipment | : | | | |
| 556-1AN | THREE-PIECE 14 INCH STEEL CENTER BUMPER WITH FLEXIBLE PLASTIC ENDS | | | |
| 558-001 | FRONT TOW HOOKS - FRAME MOUNTED | 15 | | |
| 574-001 | BUMPER MOUNTING FOR SINGLE LICENSE PLATE | | | |
| 586-024 | FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS | | | |
| 551-007 | GRADE 8 THREADED HEX HEADED FRAME FASTENERS | | | |
| Fuel Tanks | | | | |
| 204-215 | 50 GALLON/189 LITER SHORT RECTANGULAR ALUMINUM FUEL TANK - LH | 20 | | |
| 218-005 | RECTANGULAR FUEL TANK(S) | | | |
| 215-005 | PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS | | | |
| 212-007 | FUEL TANK(S) FORWARD | | | |
| 232-530 | 30 GALLONS ADDITIONAL FUEL | | | |
| 664-001 | PLAIN STEP FINISH | | | |
| 205-001 | FUEL TANK CAP(S) | | | |
| 122-1J1 | DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR, HAND PRIMER AND 12 VOLT PREHEATER | -5 | | |
| 216-020 | EQUIFLO INBOARD FUEL SYSTEM | | | |
| 11F-998 | NO NATURAL GAS VEHICLE FUEL TANK VENT LINE/STACK | | | |
| 202-016 | HIGH TEMPERATURE REINFORCED NYLON FUEL LINE | | | |
| Tires | | | | |
| 093-2C5 | HANKOOK AL11 11R22.5 14 PLY RADIAL FRONT TIRES | 8 | | |
| 094-2C6 | HANKOOK DL11 11R22.5 14 PLY RADIAL REAR TIRES | | 60 | |
| Hubs | | | | |



| | Data Code | Description | Weight Front | Weight Rear | |
|--------|-----------|--|-----------------|----------------|--|
| | 418-060 | CONMET PRESET PLUS PREMIUM IRON FRONT HUBS | | | |
| | 450-060 | CONMET PRESET PLUS PREMIUM IRON REAR HUBS | | | |
| Wheels | ; | | | | |
| | 502-523 | MAXION WHEELS 90262 22.5X8.25 10-HUB PILOT 6.19 INSET 5-HAND STEEL DISC FRONT WHEELS | 18 | | |
| | 505-523 | MAXION WHEELS 90262 22.5X8.25 10-HUB PILOT 5-HAND STEEL DISC REAR WHEELS | | 36 | |
| | 496-011 | FRONT WHEEL MOUNTING NUTS | | | |
| | 497-011 | REAR WHEEL MOUNTING NUTS | | | |
| Cab Ex | terior | | | | |
| | 829-071 | 106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB | | | |
| | 650-009 | RUBBER CAB MOUNTS | | | |
| | 648-002 | NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE | | | |
| | 678-001 | LH AND RH GRAB HANDLES | | | |
| | 646-009 | PAINTED PLASTIC GRILLE | | | |
| | 65X-001 | ARGENT SILVER HOOD MOUNTED AIR INTAKE GRILLE | | | |
| | 644-004 | FIBERGLASS HOOD | | | |
| | 726-002 | DUAL ELECTRIC HORNS | | | |
| | 657-1CV | DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME WITH (4) KEYS | | | |
| | 575-001 | REAR LICENSE PLATE MOUNT END OF FRAME | | | |
| | 312-043 | INTEGRAL HEADLIGHT/MARKER ASSEMBLY | | | |
| | 302-047 | LED AERODYNAMIC MARKER LIGHTS | | | |
| | 311-001 | DAYTIME RUNNING LIGHTS | | | |
| | 294-1AY | INTEGRAL LED STOP/TAIL/BACKUP LIGHTS | | | |
| | 300-015 | STANDARD FRONT TURN SIGNAL LAMPS | | | |
| | 744-1BC | DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE | | | |
| | 797-001 | DOOR MOUNTED MIRRORS | | | |
| | 796-001 | 102 INCH EQUIPMENT WIDTH | | | |
| | 743-204 | LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS | | | |
| | 74B-080 | RH AND LH 8 INCH STAINLESS STEEL FENDER MOUNTED CONVEX MIRRORS WITH TRIPOD BRACKETS | 8 | | |



| Data Code | Description | Weight Front | Weight Rear | |
|--------------|--|-----------------|----------------|--|
| 729-001 | STANDARD SIDE/REAR REFLECTORS | | | |
| 677-087 | LH/RH DUAL CAB ENTRY Z STYLE STEPS WITH AGGRESSIVE EDGE ENHANCED TRACTION | | | |
| 768-043 | 63X14 INCH TINTED REAR WINDOW | | | |
| 661-003 | TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS | | | |
| 654-027 | RH AND LH ELECTRIC POWERED WINDOWS, PASSENGER SWITCHES ON DOOR(S) | 4 | | |
| 663-013 | TINTED WINDSHIELD | | | |
| 659-020 | 2 GALLON WINDSHIELD WASHER RESERVOIR WITH FLUID LEVEL INDICATOR, FRAME MOUNTED | | | |
| Cab Interior | | | | |
| 707-1AK | OPAL GRAY VINYL INTERIOR | | | |
| 706-013 | MOLDED PLASTIC DOOR PANEL | | | |
| 708-013 | MOLDED PLASTIC DOOR PANEL | | | |
| 772-006 | BLACK MATS WITH SINGLE INSULATION | | | |
| 785-001 | DASH MOUNTED ASH TRAYS AND LIGHTER | | | |
| 691-008 | FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS WITHOUT NETTING | | | |
| 694-010 | IN DASH STORAGE BIN | | | |
| 742-007 | (2) CUP HOLDERS LH AND RH DASH | | | |
| 680-006 | GRAY/CHARCOAL FLAT DASH | | | |
| 700-002 | HEATER, DEFROSTER AND AIR CONDITIONER | | | |
| 701-001 | STANDARD HVAC DUCTING | | | |
| 703-005 | MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH | | | |
| 170-015 | STANDARD HEATER PLUMBING | | | |
| 130-033 | DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR | | | |
| 702-002 | BINARY CONTROL, R-134A | | | |
| 739-034 | PREMIUM INSULATION | | | |
| 285-013 | SOLID-STATE CIRCUIT PROTECTION AND FUSES | | | |
| 280-007 | 12V NEGATIVE GROUND ELECTRICAL SYSTEM | | | |
| 324-014 | DOME LIGHT WITH 3-WAY SWITCH ACTIVATED BY LH AND RH DOORS | | | |
| 655-005 | LH AND RH ELECTRIC DOOR LOCKS | | | |
| 756-1J3 | BASIC HIGH BACK AIR SUSPENSION DRIVER SEAT WITH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION | 30 | | |



| Dat | a Code | Description | Weight Front | Weight Rear | |
|------------|-----------|---|-----------------|----------------|--|
| 760 | -1J3 | BASIC HIGH BACK AIR SUSPENSION PASSENGER SEAT WITH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION | 25 | 10 | |
| 759 | -002 | INBOARD DRIVER AND PASSENGER SEAT ARMRESTS | | | |
| 711 | -004 | LH AND RH INTEGRAL DOOR PANEL ARMRESTS | | | |
| 758 | -036 | VINYL WITH VINYL INSERT DRIVER SEAT | | | |
| 761 | -036 | VINYL WITH VINYL INSERT PASSENGER SEAT | | | |
| 763 | -101 | BLACK SEAT BELTS | | | |
| 532 | -027 | ADJUSTABLE STEERING COLUMN, SUPPLIER CONVERSION TO LH AND RH ADJUSTABLE TILT STEERING COLUMNS | 10 | | |
| 540 | -015 | 4-SPOKE 18 INCH (450MM) STEERING WHEEL | | | |
| 765 | -002 | DRIVER AND PASSENGER INTERIOR SUN VISORS | | | |
| Instrument | s & Contr | ols | | | |
| 732 | -004 | GRAY DRIVER INSTRUMENT PANEL | | | |
| 734 | -004 | GRAY CENTER INSTRUMENT PANEL | | | |
| 870 | -001 | BLACK GAUGE BEZELS | | | |
| 486 | -001 | LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM | | | |
| 840 | -002 | 2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES | | | |
| 198 | -003 | DASH MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS | | | |
| 721 | -001 | 97 DB BACKUP ALARM | | 3 | |
| 149 | -013 | ELECTRONIC CRUISE CONTROL WITH SWITCHES IN LH SWITCH PANEL | | | |
| 156 | -007 | KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY | | | |
| 811 | -042 | ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED | | | |
| 160 | -038 | HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH | | | |
| 844 | -001 | 2 INCH ELECTRIC FUEL GAUGE | | | |
| 148 | -003 | PROGRAMMABLE RPM CONTROL - ELECTRONIC ENGINE | | | |
| 856 | -001 | ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE | | | |
| 864 | -001 | 2 INCH TRANSMISSION OIL TEMPERATURE GAUGE | | | |



| | Data Code | Description | Weight Front | Weight Rear |
|--------|-----------|---|-----------------|----------------|
| | 830-017 | ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY | | |
| | 852-002 | ELECTRIC ENGINE OIL PRESSURE GAUGE | | |
| | 746-1B4 | AM/FM/WB WORLD TUNER RADIO WITH CD PLAYER, BLUETOOTH, IPOD INTERFACE, USB AND AUXILIARY INPUTS, J1939 | 10 | |
| | 747-001 | DASH MOUNTED RADIO | | |
| | 750-002 | (2) RADIO SPEAKERS IN CAB | | |
| | 753-001 | AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF | | |
| | 810-027 | ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER | | |
| | 817-001 | STANDARD VEHICLE SPEED SENSOR | | |
| | 812-001 | ELECTRONIC 3000 RPM TACHOMETER | | |
| | 813-998 | NO VEHICLE PERFORMANCE MONITOR | -5 | |
| | 162-011 | IDLE LIMITER, ELECTRONIC ENGINE | | |
| | 81Y-001 | PRE-TRIP LAMP INSPECTION, ALL OUTPUTS FLASH, WITH SMART SWITCH | | |
| | 836-015 | DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY | | |
| | 660-008 | SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY | | |
| | 304-001 | MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH | | |
| | 882-009 | ONE VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR | | |
| | 299-013 | SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE | | |
| | 298-039 | INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS | | |
| Design | | | | |
| | 065-000 | PAINT: ONE SOLID COLOR | | |
| Color | | | | |
| | 980-3F6 | CAB COLOR A: N0006EA WHITE ELITE SS | | |
| | 986-020 | BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT | | |
| | 962-972 | POWDER WHITE (N0006EA) FRONT WHEELS/RIMS (PKWHT21, TKWHT21, W, TW) | | |
| | 966-972 | POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW) | | |



| Data Code | Description | Weight Front | Weight Rear | |
|---------------------|--|-----------------|----------------|--|
| 964-6Z7 | BUMPER PAINT: FP24812 ARGENT SILVER DUPONT FLEX | | | |
| 963-003 | STANDARD E COAT/UNDERCOATING | | | |
| Certification / Com | pliance | | | |
| 996-009 | U.S. AND CANADA (DUAL CERTIFICATION), EXCEPT SALES CABS AND GLIDER KITS | | | |
| Secondary Factory | Options | | | |
| 998-001 | CORPORATE PDI CENTER IN-SERVICE ONLY | | | |
| 99B-012 | SHIP TO THIRD PARTY (CHARLOTTE, NC) PRIOR TO DELIVERY | | | |
| 999-014 | DEALER HAS BEEN ADVISED OF AND ACCEPTED RESPONSIBILITY FOR MODIFICATIONS DUE TO POSSIBLE PTO/CHASSIS INTERFERENCE | | | |

| Weight Summary | | | |
|-----------------------------|-----------------|----------------|-----------------|
| | Weight Front | Weight Rear | Total Weight |
| Factory Weight ⁺ | 5867 lbs | 3812 lbs | 9679 lbs |
| Total Weight ⁺ | 5867 lbs | 3812 lbs | 9679 lbs |

TOTAL VEHICLE SUMMARY

Extended Warranty

WAG-009 TOWING: 6 MONTHS/UNLIMITED MILES/KM EXTENDED TOWING COVERAGE \$550 CAP FEX APPLIES

(+) Weights shown are estimates only.
If weight is critical, contact Customer Application Engineering.



QUOTATION

M2 106 CONVENTIONAL CHASSIS

SET BACK AXLE - TRUCK

CUM B6.7 200 HP @ 2400 RPM, 2600 GOV, 520 LB/FT @ 1600 RPM

ALLISON 2500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION

RS-21-230 21,000# R-SERIES 2-SPEED SINGLE REAR AXLE

23,000# 52 INCH VARIABLE RATE MULTI-LEAF SPRING REAR SUSPENSION WITH LEAF SPRING HELPER DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE

12,000# MONO TAPERLEAF FRONT SUSPENSION 106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB

4525MM (178 INCH) WHEELBASE 9/32X3-7/16X10-1/16 INCH STEEL FRAME (7.14MMX255.6MM/0.281X10.06 INCH) 120KSI 1600MM (63 INCH) REAR FRAME OVERHANG

| | | PER UNIT | TOTAL |
|---------------------------|----------------------|--------------|---------------|
| VEHICLE PRICE | TOTAL # OF UNITS (2) | \$ 77,036 | \$ 154,072 |
| EXTENDED WARRANTY | | \$ 100 | \$ 200 |
| DEALER INSTALLED OPTIONS | | \$ 0 | \$ 0 |
| CUSTOMER PRICE BEFORE TAX | | \$ 77,136 | \$ 154,272 |
| TAXES AND FEES | | | |
| FEDERAL EXCISE TAX (FET) | | \$ (151) | \$ (303) |
| TAXES AND FEES | | \$ 0 | \$ 0 |
| OTHER CHARGES | | \$ 0 | \$ 0 |
| TRADE-IN | | | |
| TRADE-IN ALLOWANCE | | \$ (0) | \$ (0) |
| BALANCE DUE | (LOCAL CURRENCY) | \$ 76,985 | \$ 153,969 |

Charge breakdown:



Prepared for: Carolina Tractor 9000 Statesville Rd Charlotte, NC 28269 Prepared by:
Jay Mcgary
Charlotte Truck Center, IncFreightliner
4633 EQUIPMENT DRIVE
CHARLOTTE, NC 28269

QUOTATION DETAILS

| FEDERAL EXCISE TAX | | |
|--------------------|----------------|----------------|
| TAX BEFORE CREDITS | \$.00 | \$.00 |
| CREDITS | \$ (151.38) | \$ (302.76) |

Daimler Truck Financial

Financing that works for you.

See your local dealer for a competitive quote from Daimler Truck Financial, or contact us at Information@dtfoffers.com.

Daimler Truck Financial offers a variety of finance, lease and insurance solutions to fit your business needs. For more information about our products and services, visit our website at www.daimler-truckfinancial.com.

