

**2021 Vac Con 212E-850 Standard Equipment**

212E/850	Includes: 2 Stage Vac-Con Blower, 12 CY Debris Tank, 850 Gal H2O, 6X4, Extended Frame
----------	---

- 3/16" Corten Steel Debris Tank - (size as specified by model number)
- Full opening rear door
- Hydraulic rear door locks, with door grabber with safety latch
- 5" Butterfly valve with 10' layflat hose
- Debris tank Dumping: minimum 50 deg., hydraulic scissors lift - power up/power down
- Polyethylene water tank
- Automatic Vacuum Breaker and overfill protection
- 8" vacuum intake hose
- Boom travel tie down
- 4 Way hydraulic boom with 270 deg. Rotation and joystick controls
- Front mounted 600' capacity (1" hose)/hydraulic hose reel
- 60 gpm/2000 psi water pump system
- Water pump drive: Standard Aux Engine is GM 5.7L Gasoline, 140HP
- 400' high pressure jet rodder hose (1" or 3/4")
- Manual hose rewind guide
- Hose guide (Tiger Tail)
- 30" leader hose
- 20 gpm at 600 psi wash down hand gun with 25' of hose and nozzle
- Sealed and locking tool box (es) {as indicated by model number}
- 1) each sanitary and penetrator nozzles
- 20.5' aluminum intake pipe(1-3', 1-5', 1-6', and 1-6.5' nozzle)
- ICC lighting
- DuPont Elite Polyurethane Paint
- 12 month standard warranty - see certificate for details
- 
- Note: PD Units Include Price for required Hydrostatic Drive Option.
- 5# Fire Extinguisher
- Set Triangles
- Hydrostatic Blower Drive