

## **2021 Vac Con 312E-1300 Standard Equipment**

312E/1300	Includes: 3 Stage Vac-Con Blower, 12 CY Debris Tank, 1300 Gal H2O, 6X4, Extended Frame
-----------	--

3/16" Corten Steel Debris Tank - (size as specified by model number)

Full opening rear door

Hydraulic rear door locks, with door grabber with safety latch

5" Butterfly valve with 10' layflat hose

Debris tank Dumping: minimum 50 deg., hydraulic scissors lift - power up/power down

Polyethylene water tank

Automatic Vacuum Breaker and overfill protection

8" vacuum intake hose

Boom travel tie down

4 Way hydraulic boom with 270 deg. Rotation and joystick controls

Front mounted 600' capacity (1" hose)/hydraulic hose reel

60 gpm/2000 psi water pump system

Water pump drive: Standard Aux Engine is GM 5.7L Gasoline, 140HP

400' high pressure jet rodder hose (1" or 3/4")

Manual hose rewind guide

Hose guide (Tiger Tail)

30" leader hose

20 gpm at 600 psi wash down hand gun with 25' of hose and nozzle

Sealed and locking tool box (es) {as indicated by model number}

1) each sanitary and penetrator nozzles

20.5' aluminum intake pipe(1-3', 1-5', 1-6', and 1-6.5' nozzle)

ICC lighting

DuPont Elite Polyurethane Paint

12 month standard warranty - see certificate for details

-

Note: PD Units Include Price for required Hydrostatic Drive Option.

5# Fire Extinguisher

Set Triangles

Hydrostatic Blower Drive