

### **2021 Vac Con 390-1000 Standard Equipment**

390/1000	Includes: 3 Stage Vac-Con Blower, 9 CY Debris Tank, 1000 Gal H2O, 4X2
----------	---

3/16" Corten Steel Debris Tank - (size as specified by model number)  
Full opening rear door  
Hydraulic rear door locks, with door grabber with safety latch  
5" Butterfly valve with 10' layflat hose  
Debris tank Dumping: minimum 50 deg., hydraulic scissors lift - power up/power down  
Polyethylene water tank  
Automatic Vacuum Breaker and overfill protection  
8" vacuum intake hose  
Boom travel tie down  
4 Way hydraulic boom with 270 deg. Rotation and joystick controls  
Front mounted 600' capacity (1" hose)/hydraulic hose reel  
60 gpm/2000 psi water pump system  
Water pump drive: Standard Aux Engine is GM 5.7L Gasoline, 140HP  
400' high pressure jet rodder hose (1" or 3/4")  
Manual hose rewind guide  
Hose guide (Tiger Tail)  
30" leader hose  
20 gpm at 600 psi wash down hand gun with 25' of hose and nozzle  
Sealed and locking tool box (es) {as indicated by model number}  
1) each sanitary and penetrator nozzles  
20.5' aluminum intake pipe(1-3', 1-5', 1-6', and 1-6.5' nozzle)  
ICC lighting  
DuPont Elite Polyurethane Paint  
12 month standard warranty - see certificate for details  
-  
Note: PD Units Include Price for required Hydrostatic Drive Option.  
5# Fire Extinguisher  
Set Triangles  
Hydrostatic Blower Drive