

## **2021 Vac Con PD3511HEN-1300 Standard Equipment**

PD3511HEN/1300 (624 at 18")	Includes: Roots 624 PD Blower Free Air up to 3670 CFM (2650 CFM at 18" HG), Hydrostatic Drive and Cyclone Separator, 11 CY Debris Tank, 1300 Gal H2O, Single Engine, 6X4, Extended Frame
-----------------------------	--

Vacuum System (as specified by Model Number)

Vacuum Drive: Hydrostatic - Required

3/16" Corten Steel Debris Tank - (size as specified by model number)

Full opening rear door

Hydraulic rear door locks, with door grabber with safety latch

5" Butterfly valve with 10' layflat hose

Debris tank Dumping: minimum 50 deg., hydraulic scissors lift - power up/power down

Polyethylene water tank

Automatic Vacuum Breaker and overfill protection

8" vacuum intake hose

Boom travel tie down

4 Way hydraulic boom with 270 deg. Rotation and joystick controls

Front mounted 600' capacity (1" hose)/hydraulic hose reel

FMC Water Pump is Standard on Single Engine Unit: 60 gpm/2000 psi system

Water pump drive: Hydrostatic

400' high pressure jet rodder hose (1" or 3/4")

Manual hose rewind guide

Hose guide (Tiger Tail)

30" leader hose

20 gpm at 600 psi wash down hand gun with 25' of hose and nozzle

Sealed and locking tool box(es) {as indicated by model number}

1) each sanitary and penetrator nozzles

20.5' aluminum intake pipe(1-3', 1-5', 1-6', and 1-6.5' nozzle)

ICC lighting

DuPont Elite Polyurethane Paint

12 month standard warranty - see certificate for details

-

Note: Includes Hydrostatic Drive Option

5# Fire Extinguisher

Set of Triangles