

350VX

VACUUM EXCAVATOR SERIES



350VX model shown.

FEATURES

- » Patented Viper Pothole Tool available – the fastest, cleanest, easiest-to-use pothole gun in its class.
- » Power by CAT or KUBOTA – unexcelled performance and reliability.
- » Positive Displacement Vacuum Pump – rugged and high performance.
- » Premium silencer package – reduced noise complaints.
- » Compact low profile – good visibility for your driver and stability in rough locations.
- » Rugged construction the way a contractor needs it – heavy duty frames and largest axle capacity in its class.
- » Balanced design with optimum tongue weight – easy on your trucks.
- » Narrowest machine in it's class makes it maneuverable and easy to see around.
- » Reverse flow is standard – fast tank emptying, blow obstructions out of vacuum hose and backflush the filters for quick-easy cleaning.

AN IDEAL MACHINE FOR

- » Potholing – safely dig test holes in the ground to locate buried utilities for horizontal directional drills.
- » Safe utility locating and/or daylighting.
- » Clean out storm drains, catch basins and valve boxes.
- » Cleaning up drilling fluids and mud.
- » General construction site cleanup.
- » Keyholing or utility microsurgery.
- » Environmental cleanup – everything from hurricane aftermath to oil spills.
- » Slot trenching.

350VX VACUUM EXCAVATOR SERIES

FEATURES	350VLX	350VX STD CFM	350VX HI CFM
Mountings	Trailer, truck & skid mounting	Trailer, truck & skid mounting	Trailer, truck & skid mounting
Spoils Capacity (gallons / liters)	350 gallons / 1,325 liters	350 gallons / 1,325 liters	350 gallons / 1,325 liters
Water Capacity (gallons / liters)	1 x 100 gallons / 1 x 378 liters	1 x 100 gallons / 1 x 378 liters	1 x 100 gallons / 1 x 378 liters
Optimum & Balanced Tongue Weight	680 lbs	1,100 lbs	1,100 lbs
Engine	31 Hp OHV Twin air-cooled gasoline	42 Hp CAT diesel / 64 HP Kubota diesel; Tier 4F	60/74 Hp CAT diesel / 64 HP Kubota diesel; Tier 4F
Fuel Tank Capacity (gallons / liters)	8 gallons / 30 liters	29 gallons / 110 liters	29 gallons / 110 liters
Dual LED work lights and strobe	Optional	Standard	Standard
Warranty	One Year	One Year	One Year
OPERATOR CONTROLS			
Controls Location	Front curbside with lockable cabinet	Front curbside with lockable cabinet	Front curbside with lockable cabinet
Hour Meter / Tachometer / Vacuum Gauge	Optional	Standard	Standard
Water Supply Reel	Rear Curbside	Rear Curbside	Rear Curbside
Load Level Indicator and Auto Shutoff	Auto Shutoff	Sight Glass & Auto Shutoff	Sight Glass & Auto Shutoff
Reverse Flow	Available	Standard	Standard
SPOILS TANK DETAILS			
Hydraulic Hoist Unload	Single cylinder	Single cylinder	Single cylinder
Full Opening Rear Door	Hydraulically operated	Hydraulically operated	Hydraulically operated
Rear Door Latch	Manual, power door lock available	Power door lock	Power door lock
Inlet Valve Size / Drain Valve Size	4" / 6"	4" / 6"	4" / 6"
TRAILER DETAILS - HEAVY DUTY 4" C-CHANNEL FRAME			
Trailer/Hitch Type	Single Axle / Pintle	Single Axle / Pintle	Single Axle / Pintle
Height x Length x Width (feet / inches)	81" x 14'0" x 76"	81" x 14'0" x 76"	81" x 14'0" x 76"
Empty Weight - lbs / kg	3,600 lbs / 1633 kg	4,500 lbs / 2041 kg	4,500 / 2041 kg
Gross Vehicle Weight Rating (lbs / kg)	7,250 lbs / 4531 kg	13,000 lbs / 5898 kg	13,000 lbs / 5898 kg
Axles, Capacity and Suspension Type	7,000 lbs Dexter Torflex	7,000 lbs Dexter Torflex	7,000 lbs Dexter Torflex
Tire Size	ST235/80 R 16 Load Range E	ST235/80 R 16 Load Range E	ST235/80 R 16 Load Range E
Trailer Brakes	Never adjust electric	Never adjust electric	Never adjust electric
VACUUM PUMP / BLOWER DETAILS			
Vacuum Pump/Blower Type	Positive displacement lobe pump	Positive displacement lobe pump	Positive displacement lobe pump
CFM / Max Hg	600 CFM / 15"	600 CFM / 15"	1,000 CFM / 15"
Reverse Flow	Available	Standard	Standard
Cyclo-Separator Air Filter Type / Capacity	Cyclo-Separator with 3 micron filter, 6,300 sq in capacity	Cyclo-Separator with 3 micron filter, 12,500 sq in capacity	Cyclo-Separator with 3 micron filter, 16,750 sq in capacity
WATER SYSTEM DETAILS			
Water Pressure / Water Supply	3,000 psi / 4.9 gpm	4,000 psi *factory set @ 3,500 psi / 6 gpm	4,000 psi *factory set @ 3,500 psi / 6 gpm
Electronic Low Water Shut-Off	Standard	Standard	Standard
Auto Water Pump Unloader to Reduce Engine Loading & Wear	Standard	Standard	Standard
Water Pump Drive	Belt w/ Electric Clutch	Belt w/ Electric Clutch	Belt w/ Electric Clutch
Water Supply Hose	50' x 3/8" ID	50' x 3/8" ID	50' x 3/8" ID
Water Supply Reel Location	Rear, curbside	Rear, curbside	Rear, curbside
Easy-to-Use Winterize System	Standard	Standard	Standard
OPTIONS			
Patented Cyclo-Jet Pothole Excavator – Stainless or Dielectric	Available	Recommended	Recommended
Curbside Remote Auxiliary Hydraulics	Optional	Optional	Optional
Lighted Arrow Bar to Direct Traffic	Optional	Optional	Optional
Removable Water Heater	Optional	Optional	Optional
4" Vac Hose	Available on HiCFM only	Available on HiCFM only	Optional
In Tank Clean Out System	Optional	Optional	Optional