



## **FEATURES**

- » Range of Industrial Power Options.
  - 1. Cat Diesel Option for unexcelled performance and reliability.
  - 2. Air Cooled Gasoline where low initial cost is important.
- » Rugged vacuum pump / blowers for durability and high vacuum performance.
- » Premium silencer package reduced noise complaints from work site neighbors and machine operators.
- » Compact, low-profile construction good visibility for driver and stability in rough locations.
- » Rugged construction the way a contractor needs it heavy duty frames and the largest axle capacities in their class, so your machines will last.
- » Balanced design with optimum tongue weight easy on your trucks.
- » Reverse flow vacuum pump/blower available.
  - 1. Fast tank emptying.
  - 2. Blow obstructions out of vacuum hose.
  - 3. Backflush filters for quick-easy cleaning.
- » Unique single handle rear door latch design for easier, faster opening and closing.

## AN IDEAL MACHINE FOR

- » Clean up drilling fluids from well and horizontal drilling.
- » Clean out storm drains, catch basins, and valve boxes.
- » General construction site cleanup.
- » Environmental soil remediation.
- » Environmental cleanup everything from hurricane aftermaths to oil well spills to flooded basements.
- » Cleaning out industrial sumps/pits.
- » Cleaning out carwash sediment pits.

## **850**V VACUUM SERIES

OPERATOR CONTROLS			
Engine Controls	Included		
Hour Meter	Available		
Tachometer	Available		
Vacuum Gauge	Front, curbside		
Auto Shutoff	In spoils tank		
Hydraulic Hoist Tank Unload Controls	Included		
Rear Door Controls	Included		
WARRANTY			
Warranty	1 year		
Engine Warranty	See engine packages		
SPOILS TANK DETAILS			
Spoils Tank Capacity (Gal / L)	800 / 3,000		
Spoils Tank Capacity (Cu. Yards / Cu. Meters)	4.0 / 3.0		
Hydraulic Hoist Unload	Twin cylinder		
Rear Door Opening	Full, with hydraulic opener		
Rear Door Latch	Single handle, power door		
	lock available		
Inlet Valve Size (Inches / mm)	4 / 102		
Drain Valve Size (Inches / mm)	6 / 152		

<b>TRAILER DETAILS - HEAVY DUTY</b>	5" C-CHANNEL FRAME		
(All units also available for Truck Mount or Sk			
Trailer Type	Low Profile Tandem Axle		
Hitch Type	2-5/16" Ball		
Height (Inches / mm)	78 / 1,981		
Length (Feet / Inches - mm)	20' / 6,096		
Width (Inches / mm)	80 / 2,032		
Tongue Weight - Dry (Lbs / Kg)	800 / 360		
Tongue Weight - Full (Lbs / Kg)	500 / 230		
Total Weight - Dry (Lbs / Kg)	5,300 / 2,400		
Gross Vehicle Weight Rating (Lbs / Kg)	12,500 / 5,700		
Axles, Capacity and Suspension Type	2 x 6,000 lb axles,		
	DexterTorflex		
Tire Size	ST235/80 R16 Load Range E		
Trailer Brakes	Never Adjust Electric		
OPTIONS			
Pneumatic Load Breaker to Help Free Stubborn Mudcake	Available		
Strobe and Dual LED Worklight Kit	Available		
Additional 25' x 3" Vac Hose	Available		
50' X 3" Vac Hose (Continuous Length)	Available		
3" X 8' Vac Tube Only	Available		
Sight Glass in Rear Door (up to 2)	Available		
Decanting valve in Rear Door (up to 2)	Available		
Customer Logo or Bill-Board Applied on Right and Left Sides (15" x 48" Max) supplied by customer.	Available		
Custom Color (Single Color)	Available		
Alloy Wheels (4)	Available		
Auxiliary Pressure Washer & Water Tank	Available		

ENGINE VACUUM-PUMP/ BLOWER PACKAGES	DEEP VAC	DEEP VAC II	ENVIROVAC	SUPER VAC	SUPER VAC HICFM
Engine (Gas / Diesel)	OHV Air Cooled V-twin	OHV Air Cooled V-twin	OHV Air Cooled V-twin (Gas) (Diesel Option)	OHV Air Cooled V-twin (Gas) (Diesel Option)	OHV Air Cooled V-twin (Gas) (Diesel Option)
Horsepower (HP / Kw)	21 / 15.7	23 / 17	26 / 19.3 (Gas)	31 HP (Gas)	37 HP (Gas)
Fuel Type	Gasoline	Gasoline	Gasoline (Diesel Option)	Gasoline (Diesel Option)	Gasoline (Diesel Option)
Positive Displacement Blower	Masport Vane Pump	Masport Vane Pump	Masport Vane Pump (Gas) National Vacuum (Diesel)	Howden/Roots Positive Displacement Blower	Howden/Roots Positive Displacement Blower
Displacement (CFM / L/sec)	230 / 132	350 / 165	282 / 133 (Gas) 420 / 198 (Diesel)	600 / 283	1,000 / 472
Max Vacuum (In Hg / Bar)	25 / 0.85	20 / .068	25 / 0.85 (Gas) 24 / 0.81 (Diesel)	15 / 0.51	15 / 0.51
Air Filter Type	Bag house with backflush	Bag house with backflush	Bag house with backflush	Bag house	Bag house
Pressure Off-Load	Standard	Standard	Standard	Available	Available
Filter Back-Flush	Standard	Standard	Standard	Available	Available
Hose Back-Flow	Standard	Standard	Standard	Available	Available
Hour Meter	Standard	Standard	Standard	Standard	Standard
Tachometer	Available	Available	Available	Available	Available
Warranty	1 year limited	1 year limited	1 year limited	1 year limited	1 year limited