| INTERNATIONAL® |
|----------------|
|----------------|

Vehicle Specifications 2022 HV513 SFA (HV513)

\$0.00

\$0.00

\$168.00

Description List (US DOLLAR) Base Chassis, Model HV513 SFA with 191.00 Wheelbase, 107.50 CA, and 63.00 Axle to Frame. \$183,134.00 **AXLE CONFIGURATION** \$0.00 AXLE CONFIGURATION {Navistar} 4x2 ENGINE ENGINE, DIESEL {International A26} EPA 2017, 365HP @ 1700 RPM, 1250 lb-ft Torque @ 1000 RPM, \$0.00 2100 RPM Governed Speed, 365 Peak HP (Max) RADIATOR Aluminum, Welded, Cross Flow, Front to Back System, 1292 SgIn, with 1008 SgIn Charge Air \$0.00 Cooler FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for \$0.00 **Disengaged Fan Speed**

AIR CLEANER Single Element ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection COLD STARTING EQUIPMENT Automatic; with Engine ECM Control

- EMISSION COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes \$97.00 "Certified Clean Idle" Decal on Hood
- FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted\$0.00FEDERAL EMISSIONS {International A26} EPA, OBD and GHG Certified for Calendar Year 2021, for EPA\$0.002017 A26 Engines\$0.00

TRANSMISSION

| TRANSMISSION, AUTOMATIC {Allison 3000 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway | \$616.00 |
|--|------------|
| ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS) and Regional Haul Series (RHS), General Purpose Trucks, Construction, Package Number 223 | \$0.00 |
| NEUTRAL AT STOP OMIT | (\$210.00) |
| OIL COOLER, AUTO TRANSMISSION {Modine} Water to Oil Type | \$898.00 |
| PTO LOCATION Customer Intends to Install PTO at Left Side of Transmission | \$0.00 |
| SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, Performance Programming | \$0.00 |
| TRANSMISSION OIL Synthetic; 29 thru 42 Pints | \$203.00 |
| TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission | \$50.00 |

CLUTCH

| CLUTCH Omit Item (Clutch & Control) | \$0.00 |
|--|--------|
| REAR AXLES, SUSPENSIONS | |
| AXLE, REAR, SINGLE {Meritor RS-23-160} Single Reduction, 23,000-lb Capacity, 200 Wheel Ends . Gear Ratio: 4.89 | \$0.00 |

Vehicle Specifications 2022 HV513 SFA (HV513)

| 2022 (10313 SFA (110313) | |
|--|------------------------|
| Description | <u>List</u> |
| SUSPENSION, REAR, SINGLE 23,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs | (US DOLLAR) \$82.00 |
| FRONT AXLES | |
| AXLE, FRONT NON-DRIVING {Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,000-lb Capacity | \$0.00 |
| FRONT SUSPENSIONS | |
| SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,000-lb Capacity, with Shock Absorbers | \$0.00 |
| CABS, COWLS, BODIES | |
| CAB Conventional, Day Cab | \$0.00 |
| ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab | \$0.00 |
| AIR CONDITIONER with Integral Heater and Defroster | \$1,187.00 |
| CAB INTERIOR TRIM Classic, for Day Cab | \$0.00 |
| CAB REAR SUSPENSION Air Bag Type | \$0.00 |
| GAUGE CLUSTER Base Level; English with English Speedometer and Tachometer, for Air Brake Chassis, Includes Engine Coolant Temperature, Primary and Secondary Air Pressure, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 3 Inch Monochromatic Text Display | \$0.00 |
| INSTRUMENT PANEL Flat Panel | \$0.00 |
| IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster | \$0.00 |
| MIRRORS (2) C-Loop, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width | \$0.00 |
| MIRROR, CONVEX, HOOD MOUNTED {Lang Mekra} (2) Right and Left Sides, Black 7.5" Sq. | \$137.00 |
| SEAT, DRIVER {National 2000} Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, with 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust | \$0.00 |
| SEAT, PASSENGER {National} Non Suspension, High Back, Fixed Back, Integral Headrest, Vinyl | \$368.00 |
| WINDOW, MANUAL (2) and Manual Door Locks, Left and Right Doors | \$0.00 |
| FRAMES | |
| FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm); 456.0" (11582mm) Maximum OAL | \$337.00 |
| BUMPER, FRONT Swept Back, Steel, Heavy Duty | \$0.00 |
| WHEELBASE RANGE 163" (415cm) Through and Including 209" (530cm) | \$686.00 |
| BRAKES | |
| BRAKE SYSTEM, AIR Dual System for Straight Truck Applications | \$0.00 |
| AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System | \$0.00 |

Vehicle Specifications 2022 HV513 SFA (HV513)

| 2022 AV513 SFA (AV513) | |
|--|-----------------------------|
| Description | (US DOLLAD) |
| BRAKES, FRONT {Meritor 15X4 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 15" X 4", 13,200-lb Capacity | (US DOLLAR) (\$1,633.00) |
| BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 SqIn | \$0.00 |
| SLACK ADJUSTERS, FRONT {Gunite} Automatic | \$0.00 |
| DUST SHIELDS, FRONT BRAKE for Air Cam Brakes | \$35.00 |
| BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle | (\$1,424.00) |
| BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake | \$0.00 |
| SLACK ADJUSTERS, REAR {Gunite} Automatic | \$0.00 |
| DUST SHIELDS, REAR BRAKE for Air Cam Brakes | \$70.00 |
| AIR COMPRESSOR {Bendix BA-921 Head Unload} 15.9 CFM | \$0.00 |
| AIR DRYER {Bendix AD-IP} with Heater | \$526.00 |
| AIR DRYER LOCATION Mounted Outside Left Rail, Back of Cab | \$156.00 |
| AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Right Rail, Back of Cab, Perpendicular to Rail | \$50.00 |
| DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank | \$165.00 |
| STEERING | |
| STEERING GEAR {Sheppard M100} Power | \$0.00 |
| STEERING COLUMN Tilting | \$125.00 |
| STEERING WHEEL 4-Spoke; 18" Dia., Black | \$0.00 |
| DRIVELINES | |
| DRIVELINE SYSTEM {Dana Spicer} SPL170, for 4x2/6x2 | \$253.00 |
| EXHAUST SYSTEMS | |
| EXHAUST SYSTEM Single, Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab | \$1,210.00 |
| AFTERTREATMENT COVER Steel, Black | \$0.00 |
| ENGINE COMPRESSION BRAKE by Jacobs; for N13/A26 Engines, with Selector Switch and On/Off Switch | \$0.00 |
| EXHAUST HEIGHT 10' | \$0.00 |
| MUFFLER/TAIL PIPE GUARD (1) Aluminum | \$0.00 |
| TAIL PIPE (1) Turnback Type | \$64.00 |
| ELECTRICAL SYSTEMS | |
| ELECTRICAL SYSTEM 12-Volt, Standard Equipment | \$0.00 |
| ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount | \$0.00 |
| BACK-UP ALARM Electric, 102 dBA | \$120.00 |

Vehicle Specifications 2022 HV513 SFA (HV513)

| 2022 111010 01 A (111010) | |
|---|----------------------------|
| Description | <u>List</u> (US DOLLAR) |
| BATTERY BOX Steel, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Right Side Back of Cab | (00 DOLLAR) \$101.00 |
| BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud | \$0.00 |
| BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Sleeper, Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn | \$100.00 |
| CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses | \$0.00 |
| CIGAR LIGHTER Includes Ash Cup | \$18.00 |
| CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade | \$0.00 |
| HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord | \$94.00 |
| HORN, ELECTRIC Disc Style | \$0.00 |
| POWER SOURCE, ADDITIONAL Auxiliary Power Outlet (APO) & USB Port, Located in the Instrument Panel | \$38.00 |
| RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input | \$483.00 |
| RUNNING LIGHT (2) Daytime | \$58.00 |
| SPEAKERS (2) 6.5" Dual Cone Mounted in Doors | \$48.00 |
| STARTING MOTOR {Delco Remy 39MT} 12 Volt, Gear Reduced, with Thermal Over-Crank Protection | \$42.00 |
| TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender | \$0.00 |
| FRONT END | |
| FRONT END Tilting, Fiberglass, with Three Piece Construction, Includes Long Hood | \$0.00 |
| FENDER EXTENSIONS Rubber | \$0.00 |
| GRILLE Stationary, Chrome | \$0.00 |
| INSULATION, SPLASH PANELS for Sound Abatement | \$76.00 |
| LOGOS EXTERIOR Model Badges | \$0.00 |
| LOGOS EXTERIOR, ENGINE Badges | \$0.00 |
| SPEEDOMETER, TOOLS, MISC | |
| PAINT SCHEMATIC, PT-1 Single Color, Design 100 | \$0.00 |
| PAINT TYPE Base Coat/Clear Coat, 1-2 Tone | \$0.00 |
| PROMOTIONAL PACKAGE Government Silver Package | \$0.00 |
| FUEL TANKS | |
| FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 16" Tank Depth, 50 US Gal (189L), Mounted Left Side, Under Cab | (\$55.00) |
| DEF TANK 9.5 US Gal (36L) Capacity, Frame Mounted Outside Left Rail, Under Cab | \$0.00 |
| FUEL COOLER Less Thermostat; Mounted in Front of Cooling Module | \$276.00 |
| FUEL/WATER SEPARATOR {Davco Fuel Pro 382} 12 VDC Electric Heater, Includes Pre-Heater, Includes Water-in-Fuel Sensor | \$421.00 |
| LOCATION FUEL/WATER SEPARATOR Mounted Outside Left Rail, 15" Back of Cab | \$50.00 |

Vehicle Specifications 2022 HV513 SFA (HV513)

April 21, 2021

| Description | List |
|---|--------------|
| WHEELS, TIRES - FRONT | (US DOLLAR) |
| WHEELS, FRONT {Maxion 90541} DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs | \$24.00 |
| (2) TIRE, FRONT 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position | (\$158.00) |
| WHEELS, TIRES - REAR | |
| | \$46.00 |
| (4) TIRE, REAR 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position | (\$316.00) |
| WHEELS MISC OPTIONS | |
| PAINT IDENTITY, FRONT WHEELS Disc Front Wheels; with Vendor Applied White Powder Coat Paint | \$24.00 |
| PAINT IDENTITY, REAR WHEELS Disc Rear Wheels; with Vendor Applied White Powder Coat Paint | \$48.00 |
| Total of Product Features | \$188,888.00 |
| Services Section: | |
| WARRANTY | |
| WARRANTY Standard for HV513, HV613 Models, Effective with Vehicles Built July 1, 2017 or Later, CTS-2030A | \$0.00 |
| Total of Service Features | \$0.00 |
| Total List Price Including Options: | \$188,888.00 |
| SAFETY EQUIPMENT & NC OR DOT INSPECTION. | \$150.00 |
| DEALER PDI & PREP | \$200.00 |
| ***ADIDIONAL OPTIONS ARE AVAILABLE UPON REQUEST.*** ***MATERIAL & GOVERNMENT SURCHARGES ARE NOT DISCOUNTED.*** ***LOCAL INSTALLATIONS BILLED AT NET PRICE, NOT DISCOUNTED.*** | \$0.00 |
| Total Goods Purchased: | \$350.00 |