

DescriptionList  
(US DOLLAR)  
\$183,134.00

Base Chassis, Model HV613 SBA with 175.00 Wheelbase, 107.90 CA, and 59.00 Axle to Frame.

**AXLE CONFIGURATION**

AXLE CONFIGURATION {Navistar} 4x2 \$0.00

**ENGINE**

ENGINE, DIESEL {International A26} EPA 2017, 365HP @ 1700 RPM, 1250 lb-ft Torque @ 1000 RPM, 2100 RPM Governed Speed, 365 Peak HP (Max) \$0.00

RADIATOR Aluminum, Welded, Cross Flow, Front to Back System, 1292 SqIn, with 1008 SqIn Charge Air Cooler \$0.00

FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed \$0.00

AIR CLEANER Single Element \$0.00

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection \$0.00

COLD STARTING EQUIPMENT Automatic; with Engine ECM Control \$168.00

EMISSION COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood \$97.00

FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted \$0.00

FEDERAL EMISSIONS {International A26} EPA, OBD and GHG Certified for Calendar Year 2021, for EPA 2017 A26 Engines \$0.00

**TRANSMISSION**

TRANSMISSION, AUTOMATIC {Allison 3000 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway \$616.00

ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS) and Regional Haul Series (RHS), General Purpose Trucks, Construction, Package Number 223 \$0.00

NEUTRAL AT STOP OMIT (\$210.00)

OIL COOLER, AUTO TRANSMISSION {Modine} Water to Oil Type \$898.00

PTO LOCATION Customer Intends to Install PTO at Left Side of Transmission \$0.00

SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, Performance Programming \$0.00

TRANSMISSION OIL Synthetic; 29 thru 42 Pints \$203.00

TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 &amp; 2000 Series Transmission \$50.00

**CLUTCH**

CLUTCH Omit Item (Clutch &amp; Control) \$0.00

**REAR AXLES, SUSPENSIONS**

AXLE, REAR, SINGLE {Meritor RS-23-160} Single Reduction, 23,000-lb Capacity, 200 Wheel Ends . Gear Ratio: 5.38 \$0.00

**Description****List**  
(US DOLLAR)  
\$82.00

SUSPENSION, REAR, SINGLE 23,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs

**FRONT AXLES**

AXLE, FRONT NON-DRIVING {Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,000-lb Capacity \$0.00

**FRONT SUSPENSIONS**

SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,000-lb Capacity, with Shock Absorbers \$0.00

**CABS, COWLS, BODIES**

CAB Conventional, Day Cab \$0.00

ACCESS, CAB Steel, Driver &amp; Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab \$0.00

AIR CONDITIONER with Integral Heater and Defroster \$1,187.00

CAB INTERIOR TRIM Classic, for Day Cab \$0.00

CAB REAR SUSPENSION Air Bag Type \$0.00

GAUGE CLUSTER Base Level; English with English Speedometer and Tachometer, for Air Brake Chassis, Includes Engine Coolant Temperature, Primary and Secondary Air Pressure, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 3 Inch Monochromatic Text Display \$0.00

GRAB HANDLE, EXTERIOR (2) Black, Aluminum, for Cab Entry Mounted Left and Right Side at B-Pillar \$87.00

INSTRUMENT PANEL Flat Panel \$0.00

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster \$0.00

MIRRORS (2) C-Loop, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width \$0.00

MIRROR, CONVEX, HOOD MOUNTED {Lang Mekra} (2) Right and Left Sides, Black 7.5" Sq. \$137.00

SEAT, DRIVER {National 2000} Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, with 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust \$0.00

SEAT, PASSENGER {National} Non Suspension, High Back, Fixed Back, Integral Headrest, Vinyl \$368.00

WINDOW, MANUAL (2) and Manual Door Locks, Left and Right Doors \$0.00

**FRAMES**

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm); 456.0" (11582mm) Maximum OAL \$337.00

BUMPER, FRONT Swept Back, Steel, Heavy Duty \$0.00

TOW HOOK, FRONT (2) Frame Mounted \$118.00

WHEELBASE RANGE 148" (375cm) Through and Including 193" (490cm) \$686.00

**BRAKES**

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications \$0.00

<u>Description</u>	<u>List</u> (US DOLLAR)
AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System	\$0.00
BRAKES, FRONT {Meritor 15X4 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 15" X 4", 13,200-lb Capacity	(\$1,633.00)
BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 Sqli	\$0.00
SLACK ADJUSTERS, FRONT {Gunitex} Automatic	\$0.00
DUST SHIELDS, FRONT BRAKE for Air Cam Brakes	\$35.00
BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle	(\$1,424.00)
BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Sqli Spring Brake	\$0.00
SLACK ADJUSTERS, REAR {Gunitex} Automatic	\$0.00
DUST SHIELDS, REAR BRAKE for Air Cam Brakes	\$70.00
AIR COMPRESSOR {Bendix BA-921 Head Unload} 15.9 CFM	\$0.00
AIR DRYER {Bendix AD-IP} with Heater	\$526.00
AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab	\$0.00
AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Back of Cab, Perpendicular to Rail	\$0.00
DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank	\$165.00
<b>STEERING</b>	
STEERING GEAR {Sheppard M100} Power	\$0.00
STEERING COLUMN Tilting	\$125.00
STEERING WHEEL 4-Spoke; 18" Dia., Black	\$0.00
<b>DRIVELINES</b>	
DRIVELINE SYSTEM {Dana Spicer} SPL170, for 4x2/6x2	\$253.00
<b>EXHAUST SYSTEMS</b>	
EXHAUST SYSTEM Single, Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab, for Single Short Horizontal Tail Pipe, Frame Mounted Right Side Back of Cab	\$0.00
AFTERTREATMENT COVER Steel, Black	\$0.00
ENGINE COMPRESSION BRAKE by Jacobs; for N13/A26 Engines, with Selector Switch and On/Off Switch	\$0.00
TAIL PIPE (1) Horizontal, Short, with Heat Diffuser	\$0.00
<b>ELECTRICAL SYSTEMS</b>	
ELECTRICAL SYSTEM 12-Volt, Standard Equipment	\$0.00
ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount	\$0.00
BACK-UP ALARM Electric, 102 dBA	\$120.00
BATTERY BOX Steel, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Left Side Back of Cab	\$0.00

<u>Description</u>	<u>List</u> (US DOLLAR)
BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud	\$0.00
BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Sleeper, Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn	\$100.00
CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	\$0.00
CIGAR LIGHTER Includes Ash Cup	\$18.00
CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade	\$0.00
HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord	\$94.00
HORN, ELECTRIC Disc Style	\$0.00
POWER SOURCE, ADDITIONAL Auxiliary Power Outlet (APO) & USB Port, Located in the Instrument Panel	\$38.00
RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input	\$483.00
SPEAKERS (2) 6.5" Dual Cone Mounted in Doors	\$48.00
STARTING MOTOR {Delco Remy 39MT} 12 Volt, Gear Reduced, with Thermal Over-Crank Protection	\$42.00
TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender	\$0.00
<b>FRONT END</b>	
FRONT END Tilting, Fiberglass, with Three Piece Construction, Includes Long Hood	\$0.00
FENDER EXTENSIONS Rubber	\$0.00
GRILLE Stationary, Chrome	\$0.00
INSULATION, SPLASH PANELS for Sound Abatement	\$76.00
LOGOS EXTERIOR Model Badges	\$0.00
LOGOS EXTERIOR, ENGINE Badges	\$0.00
<b>SPEEDOMETER, TOOLS, MISC</b>	
PAINT SCHEMATIC, PT-1 Single Color, Design 100	\$0.00
PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	\$0.00
PROMOTIONAL PACKAGE Government Silver Package	\$0.00
<b>FUEL TANKS</b>	
FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 19" Tank Depth, 50 US Gal (189L), Mounted Left Side, Under Cab	\$0.00
DEF TANK 9.5 US Gal (36L) Capacity, Frame Mounted Outside Left Rail, Under Cab	\$0.00
FUEL/WATER SEPARATOR {Davco Fuel Pro 382} 12 VDC Electric Heater, Includes Pre-Heater, Includes Water-in-Fuel Sensor	\$421.00
LOCATION FUEL/WATER SEPARATOR Mounted Outside Left Rail, 8" Back of Cab	\$50.00
<b>WHEELS, TIRES - FRONT</b>	
WHEELS, FRONT {Maxion 90541} DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	\$24.00

DescriptionList  
(US DOLLAR)  
(\$158.00)

(2) TIRE, FRONT 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position

**WHEELS, TIRES - REAR**

WHEELS, REAR {Maxion 90541} DUAL DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs \$46.00

(4) TIRE, REAR 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position (\$316.00)

**WHEELS MISC OPTIONS**

PAINT IDENTITY, FRONT WHEELS Disc Front Wheels; with Vendor Applied White Powder Coat Paint \$24.00

PAINT IDENTITY, REAR WHEELS Disc Rear Wheels; with Vendor Applied White Powder Coat Paint \$48.00

**Total of Product Features** **\$187,233.00****Services Section:****WARRANTY**

WARRANTY Standard for HV513, HV613 Models, Effective with Vehicles Built July 1, 2017 or Later, CTS-2030A \$0.00

**Total of Service Features** **\$0.00****Total List Price Including Options:** **\$187,233.00**

SAFETY EQUIPMENT &amp; NC OR DOT INSPECTION. \$150.00

DEALER PDI &amp; PREP \$200.00

\*\*\*ADIDIONAL OPTIONS ARE AVAILABLE UPON REQUEST.\*\*\* \$0.00

\*\*\*MATERIAL &amp; GOVERNMENT SURCHARGES ARE NOT DISCOUNTED.\*\*\*

\*\*\*LOCAL INSTALLATIONS BILLED AT NET PRICE, NOT DISCOUNTED.\*\*\*

**Total Goods Purchased:** **\$350.00**