



TLG Peterbilt - Greensboro (P641)  
7061 Albert Pick Road  
Greensboro, North Carolina 27409

North Carolina Sheriff  
323 West Jones Street Suite 505  
Raleigh, North Carolina 27603  
United States of America

Howie Dingess  
Cell Phone: 336-669-4408  
Office Phone: 336-668-3050  
Email: hdingess@piedmontpeterbilt.com

## Vehicle Summary

Unit		Chassis	
Model:	Model 348	Fr Axle Load (lbs):	12000
Type:	Full Truck	Rr Axle Load (lbs):	22700
Description 1:		G.C.W. (lbs):	34700
Description 2:			
Application		Road Conditions:	
Intended Serv.:	City Delivery	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:	Van	Wheelbase (in):	178
Length (ft):	24	Overhang (in):	62.8
Height (ft):	13.5	Fr Axle to BOC (in):	69.8
Max Laden Weight (lbs):	1000		
Trailer		Cab to Axle (in):	108.2
No. of Trailer Axles:	0	Cab to EOF (in):	171
Type:		Overall Comb. Length (in):	279
Length (ft):	0	Special Req.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	65		
Width (in):	102		
Height (ft):	13.5		

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
<b>Base Model</b>				
0003481	S	<b>Model 348</b> The Model 348 was designed to exceed the rigid demands of Class 7 and Class 8 specialty application markets that require rugged durability and a wide range of optional content. The Model 348 represents a multi-dimensional performer with a GVW from 33,000 to 66,000 lbs. and optional capacity ratings to suit almost any vocation. The 348 is also available in a specifically designed all-wheel-drive configuration. From construction and crane service to utility and delivery services in both Class 7 and Class 8 markets, the 348 is in a class by itself.	110,721	10,610
0091200	S	<b>Other Commodity</b>	0	0
0093340	S	<b>City Delivery</b> Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.	0	0
0095040	S	<b>Van</b>	0	0
0098170	S	<b>United States Registry</b> Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
<b>Configuration</b>				
0200700	S	<b>Not Applicable</b> Secondary Manufacturer	0	0
<b>Frame &amp; Equipment</b>				
0515030	S	<b>10-5/8" Steel Rails to 285"</b> 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	0	118
0612160	O	<b>178" Wheelbase</b>	0	0
0613090	S	<b>Three-Piece Crossmembers</b>	0	0
0644090	S	<b>EOF Square without Crossmember</b> End-of-frame square without crossmember. For use with body builder installed crossmember.	0	0
0651090	S	<b>Omit Rear Mudflaps and Hangers</b>	0	0
<b>Front Axle &amp; Equipment</b>				
1011875	S	<b>Dana Spicer E1202IL 12,000 lb, 3.5 in. Drop</b> Axle is designed for applications with a gross axle weight rating (GAWR) of 12,000 lb. The axles have exclusive one-piece forged design knuckle including steer arm, tie rod arm and spindle. This feature helps in greater durability and reduced maintenance.	0	0
1111190	S	<b>Taper Leaf Springs, Shocks 12,000 lb</b>	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:47:26 AM

Date: April 24, 2021

Quote Number: QUO-814606-W5X3M5



Sales Code	Std/ Opt	Description	\$ List	Weight
		Hendrickson taper leaf springs, shocks for 12,000 lbs.		
1243040	S	<b>Power Steering Sheppard HD94</b> Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 10,000 to 13,200 lb. axle ratings.	0	0
1250180	S	<b>Power Steering Reservoir Frame Mounted</b> The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1354845	S	<b>PHP10 Iron PreSet Hubs</b>	0	0
1380260	S	<b>Bendix Air Cam Front Drum Brakes 16.5x5</b> For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.	0	0
1391410	S	<b>Gusseted Cam Brackets, Steer Axle</b>	0	0
<b>Rear Axle &amp; Equipment</b>				
1513280	S	<b>Dana Spicer S23-172, 23,000lb</b>	0	0
1616370	S	<b>PHP10 Iron PreSet Hubs</b>	0	0
1680500	S	<b>SBM Valve</b> Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680950	S	<b>Stability System Not Selected Or Not Available</b>	0	0
1682430	S	<b>Anti-Lock Braking System (ABS) 4S4M</b> ABS-6. Includes air braking system.	0	0
1684200	S	<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1686348	S	<b>Single Drive Axle (Model 348)</b>	0	0
1687010	S	<b>Bendix Air Cam Rear Drum Brakes 16.5x7</b> Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1704780	O	<b>Ratio 4.78 Rear Axle</b>	0	0
1811210	S	<b>Peterbilt Air Trac 23,000 lb Light Weight</b>	0	0
<b>Engine &amp; Equipment</b>				

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:47:26 AM

Date: April 24, 2021

Quote Number: QUO-814606-W5X3M5



Sales Code	Std/ Opt	Description	\$ List	Weight
2074211	S	<b>PACCAR PX-9 260@2200 GOV@2200 860@1200</b> Productivity (2021 Emissions)	0	0
		N21350 C121 64....Maximum Accelerator Pedal Ve		
		N21370 C128 64....Maximum Cruise Speed (P059)		
		N21460 C132 1400..Max PTO Speed (P046)		
		N21520 C133 5.....Timer Setting (P030)		
		N21610 C188 39....Low Ambient Temperature Thre		
		N21620 C189 60....Intermediate Ambient Tempera		
		N21630 C190 80....High Ambient Temperature Thr		
		N21550 C206 35....Engine Load Threshold (P516)		
		N21340 C209 120...Hard Maximum Speed Limit (P1		
		N21510 C225 YES...Enable Idle Shutdown Park Br		
		N21450 C231 NO....Gear Down Protection (P026)		
		N21570 C233 NO....Idle Shutdown Manual Overrul		
		N21440 C234 NO....Engine Protection Shutdown (		
		N21480 C238 NO....Auto Engine Brake in Cruise		
		N21470 C239 NO....Cruise Control Auto Resume (		
		N21430 C333 0.....Reserve Speed Limit Offset (		
		N21410 C334 0.....Maximum Cycle Distance (N202		
		N21590 C382 YES...Enable Hot Ambient Automatic		
		N21500 C395 0.....Expiration Distance (N209)		
		N21530 C396 YES...Enable Impending Shutdown Wa		
		N21540 C397 60....Timer For Impending Shutdown		
		N21320 C399 120...Standard Maximum Speed Limit		
		N21400 C400 252...Reserve Speed Function Reset		
		N21420 C401 10....Maximum Active Distance (N20		
		N21330 C402 0.....Expiration Distance (N207)		
2091305	O	<b>Engine Idle Shutdown Timer Enabled</b>	0	0
2091315	O	<b>Enable EIST Ambient Temp Override</b>	0	0
2091372		<b>Eff EIST NA Expiration Miles</b>	0	0
2091640		<b>Effective VSL Setting NA</b>	0	0
2092016	O	<b>Typical Operating Speed 62 MPH</b>	0	0
2092032	O	<b>Powertrain Optimized for Performance</b> Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0	0
2140200	S	<b>CARB Engine Idling Compliance</b> PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2513060	S	<b>PACCAR 160 Amp Alternator, Brushed</b> PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2522110	S	<b>PACCAR 12V Starter, N/A PACCAR MX Engines</b>	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:47:26 AM

Date: April 24, 2021

Quote Number: QUO-814606-W5X3M5



Sales Code	Std/ Opt	Description	\$ List	Weight
		PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.		
2538030	S	<b>2 PACCAR Premium 12V Starting Batteries 2000 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2621090	S	<b>DM Advantage ON/OFF Fan Clutch</b> Horton DM Advantage Two-Speed Fan Clutch On/Off for heavy-duty, medium-duty and a variety of off-highway equipment.	0	0
2723210	S	<b>18.7 CFM Air Compressor</b> N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2921160	S	<b>Spin-On Fuel/Water Separator</b>	0	0
2921210	S	<b>No Fluid Heat Option for Fuel Filter</b>	0	0
2921310	S	<b>No Electric Heat Option for Fuel Filter</b>	0	0
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0	0
3211120	S	<b>Radial Seal, Dry Type Air Cleaner, Frontal</b> Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365280	S	<b>Exhaust Single RH Horizontal</b> DPF/SCR RH Under Cab.	0	0
<b>Transmission &amp; Equipment</b>				
4040970	S	<b>Eaton FSO8406A 6-Speed</b> (Synchronized) 860 torque. Includes synthetic lubricant to reduce friction, improve efficiency, & extend component life. Magnetic transmission oil drain plug captures & holds any metal fragments in transmission oil to extend service life. Torque limiting clutch brake.	0	0
4210080	S	<b>1710 HD Driveline, 1 Midship Bearing</b>	0	0
4256100	S	<b>Manual Shifter, Black</b>	0	0
<b>Air &amp; Trailer Equipment</b>				
4510190	S	<b>Bendix AD-HF Air Dryer, Heater</b> Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:47:26 AM

Date: April 24, 2021

Quote Number: QUO-814606-W5X3M5



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
		oil aerosols before they can contaminate the moisture removing desiccant.		
4540420	S	<b>Nylon Chassis Hose</b>	0	0
4543320	S	<b>Steel Painted Air Tanks</b> All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
<b>Tires &amp; Wheels</b>				
5069610	S	<b>FF: BR 14ply 295/75R22.5 R268 Ecopia</b> Efficiency Rating: Fair The R268 Ecopia is an all-position/steer radial that stands up the rigors of severe, high scrub environments in regional pickup and delivery applications. Not a tread for line haul. Diameter = 40.3 inches; SLR = 18.8 inches	0	0
5169610	S	<b>RR: BR 14ply 295/75R22.5 R268 Ecopia</b> Efficiency Rating: Fair R268 tread is not a Line Haul tire and is only for Pickup and Delivery or Regional use. Diameter = 40.3 inches; SLR = 18.8 inches	0	0
5190004	O	<b>Code-rear Tire Qty 04</b>	0	0
5211990	S	<b>FF: Accu-Lite Steel Armor 51408PK 22.5X8.25</b> PHP10-2 hand holes	0	0
5311990	S	<b>RR: Accu-Lite Steel Armor 51408PK 22.5X8.25</b> PHP10-2 hand holes	0	0
5390004	O	<b>Code-rear Rim Qty 04</b>	0	0
<b>Fuel Tanks</b>				
5532040	S	<b>23" Aluminum 50 Gallon Fuel Tank RH BOC</b> Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	0	0
5603050	S	<b>Location RH BOC 50 Gallon</b>	0	0
5652890	S	<b>DEF Tank Mounted LH BOC</b> Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	O	<b>DEF To Fuel Ratio 2:1 Or Greater</b>	0	0
5655019	S	<b>DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal</b>	0	0
<b>Battery Box &amp; Bumper</b>				

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:47:26 AM

Date: April 24, 2021

Quote Number: QUO-814606-W5X3M5



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
6021000	S	<b>Steel Battery Box LH Under Cab, Non-Slip Step</b>	0	0
6040550	S	<b>Aftertreatment Aluminum Non-Slip Cab Entry</b> Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6121180	S	<b>Steel Styled Aero Bumper Painted Cab Color</b> Two tow points	0	0
<b>Cab &amp; Equipment</b>				
6510110	S	<b>Alum Cab 108in BBC Metton Hood w/Bright Crown</b> Includes view window RH door and convex mirror over RH door.	0	0
6911700	S	<b>National Driver Seat</b> Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0	0
6921700	S	<b>National Passenger Seat</b> Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0	0
6939400	S	<b>Air Ride Driver</b>	0	0
6939420	S	<b>High Back Driver</b>	0	0
6939470	S	<b>Vinyl Driver</b>	0	0
6939510	S	<b>Non-Air Ride Passenger</b>	0	0
6939520	S	<b>High Back Passenger</b>	0	0
6939570	S	<b>Vinyl Passenger</b>	0	0
7000015	S	<b>Adjustable Steering Column - Tilt Only</b>	0	0
7001620	S	<b>Steering Wheel With Peterbilt Logo</b> Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7036120	S	<b>Interior Gray/Black</b> Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0	0
7210540	S	<b>Day Cab Rear Window</b> Day cab rear window flush to back of cab.	0	0
7230060	S	<b>1-Piece Curved Windshield</b>	0	0
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b>	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:47:26 AM

Date: April 24, 2021

Quote Number: QUO-814606-W5X3M5





Sales Code	Std/ Opt	Description	\$ List	Weight
		With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.		
7510010	S	<b>Stainless Steel Mirrors 7 x 16</b>	0	0
7564110	S	<b>Power Package</b> Includes power door locks and power windows.	0	0
7610250	S	<b>Air Horn None Furnished</b>	0	0
7725720	S	<b>No Head Unit or Audio Speakers Selected</b>	0	0
7851480	S	<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0	0
8021380	S	<b>Air Restriction Indicator</b> Mounted on air cleaner, intake piping, or firewall	0	0
8071870	S	<b>Main Instrumentation Panel, Graphics Display</b> Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights with audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0	0
8111110	S	<b>Headlights Composite Fender Mounted</b> Integral park, turn, and side marker	0	0
8120980	S	<b>(5) Marker Lights, Aero LED</b>	0	0
8140120	S	<b>Incandescent Square Stop/Turn/Tail/Backup</b> Left-hand / right-hand square end of frame or dropped a-brace	0	0
<b>Paint</b>				
8500710	S	<b>Standard Paint Color Selection</b>	-200	0
8530770	S	<b>(1) Color Axalta Two Stage - Cab/Hood</b> Base Coat/Clear Coat N85020 A - L0006EY WHITE N85700 BUMPER L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0

## Shipping Destination

## Options Not Subject To Discount

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:47:26 AM

Date: April 24, 2021

Quote Number: QUO-814606-W5X3M5





<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
9400091	S	<b>Peterbilt Class 7 Standard Coverage</b> 1 year/Unlimited Miles/km	0	<b>0</b>
9400094	S	<b>PACCAR PX-9 Standard Coverage</b> 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	<b>0</b>
9408731	S	<b>2021 Peterbilt MD Delivery</b>	750	<b>0</b>
<b>Miscellaneous</b>				
9409831	O	<b>2021 EPA Emissions Engine</b> Warranty Only	0	<b>0</b>

### Promotions

### Order Comments

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:47:26 AM

Date: April 24, 2021

Quote Number: QUO-814606-W5X3M5



Total List Price (W/O Freight & Warranty & Surcharges )	\$110,521
Marketing and Service Support Fee	\$875
Prepaid Freight	\$2,450
Total Surcharge/Options Not Subject To Discount	\$750
Total Weight	10,728

## Prices and Specifications Subject to Change Without Notice.

---

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### **PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*