



TLG Peterbilt - Greensboro (P641)  
7061 Albert Pick Road  
Greensboro, North Carolina 27409

North Carolina Sheriff  
323 West Jones Street Suite 505  
Raleigh, North Carolina 27603  
United States of America

Howie Dingess  
Cell Phone: 336-669-4408  
Office Phone: 336-668-3050  
Email: hdingess@piedmontpeterbilt.com

## Vehicle Summary

Unit		Chassis	
Model:	Model 389	Fr Axle Load (lbs):	12000
Type:	Tractor	Rr Axle Load (lbs):	38000
Description 1:		G.C.W. (lbs):	50000
Description 2:			
Application		Road Conditions:	
Intended Serv.:	General Freight	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:		Wheelbase (in):	195
Length (ft):	0	Overhang (in):	54.7
Height (ft):	0	Fr Axle to BOC (in):	92.8
Max Laden Weight (lbs):	0		
Trailer		Cab to Axle (in):	102.2
No. of Trailer Axles:	2	Cab to EOF (in):	156.9
Type:	Van	Overall Comb. Length (in):	826
Length (ft):	53	Special Req.	
Height (ft):	13.5		
Kingpin Inset (in):	36		
Corner Radius (in):	2		
Restrictions			
Length (ft):	65		
Width (in):	102		
Height (ft):	13.5		

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

**Note: All sales are F.O.B. designated plant of manufacture.**



Sales Code	Std/ Opt	Description	\$ List	Weight
<b>Base Model</b>				
0003891	S	<b>Model 389</b> The Model 389 embodies the Peterbilt heritage and merges it with a proven design to create a legendary classic for vocational applications. The lightweight, all-aluminum cab with lap seam construction, aircraft grade fasteners and bulkhead style doors is legendary for its durability. The pod-mounted headlamps are durable, corrosion-resistant and cost-effective to replace. Peterbilt's all-aluminum cab is not only extremely durable, it's also lightweight to allow for increased payloads to maximize performance and profitability.	191,702	<b>14,915</b>
0091200	S	<b>Other Commodity</b>	0	<b>0</b>
0093170	S	<b>General Freight</b> Truck or tractor used in over-the-road hauling of general freight. Pickup to delivery distance is typically over 100 miles and annual mileage is typically over 60,000 miles per year. Operation is typically on-highway.	0	<b>0</b>
0096010	S	<b>Van</b> An enclosed box trailer without temperature control. Designed to carry pallets or boxes of cargo or equipment.	0	<b>0</b>
0098170	S	<b>United States Registry</b> Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	<b>0</b>
<b>Configuration</b>				
0200685	O	<b>Probilt Natural Gas Fuel System Assembler</b>	0	<b>0</b>
<b>Frame &amp; Equipment</b>				
0515030	S	<b>10-5/8" Steel Rails to 285"</b> 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	0	<b>0</b>
0644000	S	<b>EOF Tractor Tapered with Crossmember</b> Includes Kingpin Cutout	0	<b>0</b>
0651010	S	<b>Peterbilt Rear Mudflaps and Straight Hangers</b> Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	0	<b>0</b>
0854010	S	<b>Fifth Wheel Not Furnished</b>	0	<b>0</b>
0940330	S	<b>No Access Package or Deckplate Desired</b> Use with tractors without access package or deckplate	0	<b>0</b>
<b>Front Axle &amp; Equipment</b>				
1012140	S	<b>Meritor MFS+12E 12,500 lb, 3.5 in. Drop</b> Axle is designed for applications with a gross axle weight rating (GAWR) of 13,000 pounds. Axles include special low-friction bushings,	0	<b>0</b>

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 8:08:28 AM

Date: April 24, 2021

Quote Number: QUO-815237-M4P2P9



Sales Code	Std/ Opt	Description	\$ List	Weight
		double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service.		
1111190	S	<b>Taper Leaf Springs, Shocks 12,000 lb</b> Hendrickson taper leaf springs, shocks for 12,000 lbs.	0	0
1243000	S	<b>Power Steering Sheppard M100</b> For use with 10,000 to 13,200 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	0	0
1250180	S	<b>Power Steering Reservoir Frame Mounted</b> The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1353550	S	<b>PHP10 Aluminum PreSet PLUS Hubs Air Disc</b> PHP10 aluminum PreSet PLUS hubs air disc have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug, with a seal and bearings. Use with Front Axle.	0	0
1380290	S	<b>Bendix Air Disc Front Brakes</b> Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
1390630		<b>80mm Front Spring Spacer Blocks</b>	0	0
<b>Rear Axle &amp; Equipment</b>				
1527050	S	<b>PACCAR DX-40 40K Tandem Axle</b>	0	0
1616290	S	<b>PHP10 Aluminum PreSet PLUS Hubs</b>	0	0
1680390	S	<b>Bendix ESP Electronic Stability Program With ATC</b> Tractor service only. The Bendix ESP system is designed to continuously monitor a variety of vehicle parameters and sensors to determine if the vehicle is reaching a critical stability threshold. If such a situation develops, the system will quickly and automatically intervene to assist the driver by selectively applying tractor and trailer brakes, and de-throttling the engine.	0	0
1682710	S	<b>Anti-Lock Braking System (ABS) 6S6M</b> ABS-6. Includes air braking system.	0	0
1684200	S	<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687010	S	<b>Bendix Air Cam Rear Drum Brakes 16.5x7</b> Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1703550	O	<b>Ratio 3.55 Rear Axle</b>	0	0
1821700	S	<b>Peterbilt Air Leaf 38,000 lb, 52in Axle Spacing</b> Light Weight with Tracking Rods.	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 8:08:28 AM

Date: April 24, 2021

Quote Number: QUO-815237-M4P2P9



Sales Code	Std/ Opt	Description	\$ List	Weight
<b>Engine &amp; Equipment</b>				
2072826	O	<b>PACCAR MX-13 430@1600 1550@900</b> (2021 Emissions)	0	0
		N20700 AA003 64....CC MAX TARGET SPEED		
		N20800 AA004 10....CC MIN ENABLE SPEED		
		N22000 AA005 OFF...DYNAMIC CC ENABLE		
		N20830 AA006 MT....MULTI TORQUE IN CC		
		N21930 AA009 0.....DRIVER REWARD VEH SPD BONUS		
		N21940 AA010 -5....DRIVER REWARD VEH SPD PNLTY		
		N21920 AA013 BOTH..OFFSET MODE		
		N21950 AA015 3.....MIN SPEED FOR DR SHIFT AID		
		N21960 AA016 1.....DSA LOWEST ACTV GEAR		
		N21970 AA017 10....DSA HIGHEST ACTV GEAR		
		N21640 AA019 YES...EIST PARK BRAKE RESET ENABLE		
		N21910 AA022 30....EIST LO CLNT TEMP OVRDE		
		N20870 AA023 80....EIST HI AMBAIR TEMP OVRDE		
		N20860 AA024 39....EIST LO AMBAIR TEMP OVRDE		
		N20900 AA025 5.....EIST PTO MAX IDLE TIME		
		N20840 AA026 5.....EIST PARKED MAX IDLE TIME		
		N20850 AA027 5.....EIST STANDSTILL IDLE TIME		
		N20910 AA029 YES...EIST RESET FROM ENG LOAD		
		N21170 AA030 NO....EIST OVERRIDE FROM ENG LOAD		
		N21190 AA031 0.....EIST EXPIRATION DISTANCE		
		N21230 AA032 YES...EIST ACCEL PEDAL RESET		
		N21240 AA033 YES...EIST SERVICE BRK RESET		
		N21250 AA034 YES...EIST CLUTCH PEDAL RESET		
		N21260 AA035 YES...EIST PTO OVERRIDE		
		N20770 AA037 4.....DSL SPD OFFSET		
		N20760 AA038 2.....AUTO RTRDR VEH SPD OFFSET		
		N20750 AA039 0.1...TIME DELAY FOR RTRDR ACT		
		N20940 AA042 1900..FIC MAX ENG SPEED		
		N22080 AA043 CNCL..CAB/REM: CUSTOM PRESET 1 FUN		
		N22090 AA044 750...CAB/REM: CUSTOM PRESET 1		
		N22100 AA045 CNCL..CAB/REM: CUSTOM PRESET 2 FUN		
		N22110 AA046 850...CAB/REM: CUSTOM PRESET 2		
		N22120 AA047 CNCL..CAB/REM: CUSTOM PRESET 3 FUN		
		N22130 AA048 950...CAB/REM: CUSTOM PRESET 3		
		N22010 AA049 CNCL..CAB: CUSTOM PRESET 1 FUNC		
		N22020 AA050 0.....CAB: CUSTOM PRESET 1		
		N22030 AA051 CNCL..CAB: CUSTOM PRESET 2 FUNC		
		N22040 AA052 0.....CAB: CUSTOM PRESET 2		
		N22050 AA053 CNCL..CAB: CUSTOM PRESET 3 FUNC		
		N22060 AA054 0.....CAB: CUSTOM PRESET 3		
		N20990 AA055 ON A..CAB: CLUTCH INTLK		
		N21010 AA058 ON A..CAB: PARK BRK INTLK		
		N21030 AA057 ON A..CAB: NEUTRAL INTLK		
		N21150 AA059 ON A..SER BRK INTLK: NO PTO		
		N21130 AA060 OFF...CAB: PRESET +/- SWITCH TYPE		
		N21180 AA061 2000..CAB: MAX ENG SPD- ACCEL CTRL		

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 8:08:28 AM

Date: April 24, 2021

Quote Number: QUO-815237-M4P2P9



Sales Code	Std/ Opt	Description	\$ List	Weight
		N21120 AA062 2000..CAB: MAX ENG SPD- SW CTRL		
		N21020 AA063 6.....CAB:MAX VEH SPEED		
		N21200 AA064 650...CAB: MIN ENG SPD		
		N21220 AA065 800...CAB: DEDICATED PRESET (-)		
		N21270 AA066 900...CAB: DEDICATED PRESET (+)		
		N21900 AA067 TRQ...CAB: ACCEL PEDAL TYPE IN PTO		
		N21140 AA068 YES...CAB: ACCEL ACTV IN CAB PTO		
		N21990 AA069 YES...PTO REM PEDAL ENABLE		
		N21600 AA070 ON AD.REM: CLUTCH INTLK		
		N22140 AA071 OFF...REM: CUSTOM INTLK		
		N21700 AA072 ON AD.REM: NEUTRAL INTLK		
		N21710 AA073 ON AD.REM: SER BRK INTLK: NO PTO		
		N21980 AA074 2000..REM:MAX ENG SPD-ACCEL CTRL		
		N21110 AA075 2000..REM: MAX ENG SPD-SW/ TSC1 CT		
		N21320 AA076 650...REM: MIN ENG SPD		
		N21290 AA077 800...REM: DEDICATED PRESET (-)		
		N21490 AA078 900...REM: DEDICATED PRESET (+)		
		N21580 AA079 DEDIC.REM: PRESET +/- SWITCH TYPE		
		N20690 AA086 64....MAX ACCEL PEDAL VEH SPD		
		N21300 AA087 0.....VSL EXPIRATION DISTANCE		
		N21310 AA088 155...LRSL SPD LMT		
		N20740 AE001 NO....ENBL MX RETARDER IN NEUTRAL		
		N20710 AE002 600...IDLE TARGET		
		N20930 AE003 ON....FIC ENABLE/DISABLE		
		N22070 AA056 OFF...CAB: CUSTOM INTLK		
2091130	S	<b>VMUX Electronics Architecture</b>	0	0
2091305	S	<b>Engine Idle Shutdown Timer Enabled</b>	0	0
2091315	O	<b>Enable EIST Ambient Temp Override</b>	0	0
2091372		<b>Eff EIST NA Expiration Miles</b>	0	0
2091640		<b>Effective VSL Setting NA</b>	0	0
2092014	S	<b>Typical Operating Speed 65 MPH</b>	0	0
2092027	O	<b>MX Retarder State Cruise Control On</b> (Manual Mode Engine Parameter)	0	0
2092032	O	<b>Powertrain Optimized for Performance</b> Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0	0
2092082	S	<b>Engine Monitoring Protection - Derate</b> (PACCAR MX) A warning is provided in the A-Panel display when DPF regeneration is required. Continued operation without regeneration will initiate automate derating of the engine's power and can result in damage to the engine.	0	0
2140200	S	<b>CARB Engine Idling Compliance</b>	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 8:08:28 AM

Date: April 24, 2021

Quote Number: QUO-815237-M4P2P9



Sales Code	Std/ Opt	Description	\$ List	Weight
		PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.		
2140410	S	<b>Engine Brake Controls Located on RH Column</b>	0	0
2513060	S	<b>PACCAR 160 Amp Alternator, Brushed</b> PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	S	<b>Immersion Type Block Heater 110-120V</b> Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522080	S	<b>PACCAR Premium Starter - MX Engines Only</b> PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 5-yr/500K miles.	0	0
2538040	S	<b>3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2621090	S	<b>DM Advantage ON/OFF Fan Clutch</b> Horton DM Advantage Two-Speed Fan Clutch On/Off for heavy-duty, medium-duty and a variety of off-highway equipment.	0	0
2738410	S	<b>WABCO 25.9 CFM Air Compressor, MX only</b> WABCO 25.9 CFM air compressor, MX only, provides greater air output aiding in cleaner operation, higher efficiency, and durability.	0	0
2811160	S	<b>Compression Brake, MX</b> The Mx brake features a Jacobs Brake with an integrated compression-release brake and engine overhead. the specially designed exhaust came lobe provides both exhaust cam motion and deicated Compression release timing. This results in precise timing of the valve opening, unleashing higher retarding performance with minimum loading on the engine.	0	0
2921180	S	<b>PACCAR Fuel/Water Separator On Engine</b> Optimized for MX engines and Includes fuel heat, 12V electric heat and WIF sensor.	0	0
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0	0
3213500	S	<b>(1) 15" Painted Air Cleaner Cowl Mtd, Painted Cap</b> Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake. Stainless steel air cleaner straps, brackets, & fasteners provide a durable bright finish.	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 8:08:28 AM

Date: April 24, 2021

Quote Number: QUO-815237-M4P2P9



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
3365270	S	<b>Exhaust Single RH Side of Cab</b> DPF/SCR right-hand Under Cab.	0	0
3387870	S	<b>24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)</b>	0	0
<b>Transmission &amp; Equipment</b>				
4040760	S	<b>Eaton FRO16210C 10-Speed</b> Includes oil-to-water cooler and internal pump, direct shift pattern. Synthetic lubricant to reduce friction, improve efficiency, & extend component life. Magnetic transmission oil drain plug captures & holds any metal fragments in transmission oil to extend service life. Torque limiting clutch brake. Forward ratios: 1st-12.69, 2nd-9.29, 9th-1.00, 10th-0.74. Reverse ratios: L-13.75, H-2.80	0	0
4210200	O	<b>1760 HD Driveline, 1 Midship Bearing</b>	355	60
4216590	O	<b>1710 Driveline Interaxle</b> For tandem rear axles	288	0
4256100	S	<b>Manual Shifter, Black</b>	0	0
<b>Air &amp; Trailer Equipment</b>				
4510190	S	<b>Bendix AD-HF Air Dryer, Heater</b> Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0	-8
4540420	S	<b>Nylon Chassis Hose</b>	0	0
4543320	S	<b>Steel Painted Air Tanks</b> All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4610920	S	<b>Self-Returning Brake Hand Valve</b> Dash mounted controls	0	0
4614810	S	<b>AE Connections BOC/BOS, Hose Tenna</b>	0	0
<b>Tires &amp; Wheels</b>				
5066100	S	<b>FF: BR 14ply 295/75R22.5 R213 Ecopia</b>	0	0
5166100	S	<b>RR: BR 14ply 295/75R22.5 R213 Ecopia</b>	0	0
5190008	S	<b>Code-rear Tire Qty 08</b>	0	0
5211990	S	<b>FF: Accu-Lite Steel Armor 51408PK 22.5X8.25</b> PHP10-2 hand holes	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 8:08:28 AM

Date: April 24, 2021

Quote Number: QUO-815237-M4P2P9



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
5311990	S	<b>RR: Accu-Lite Steel Armor 51408PK 22.5X8.25</b> PHP10-2 hand holes	0	0
5390008	S	<b>Code-rear Rim Qty 08</b>	0	0
<b>Fuel Tanks</b>				
5552070	S	<b>26" Aluminum 60 Gallon Fuel Tank RH BOC</b> Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	0	0
5556070	S	<b>26" Aluminum 60 Gallon Fuel Tank LH BOC</b> Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	0	0
5603060	S	<b>Location RH BOC 60 Gallon</b>	0	0
5604060	S	<b>Location LH BOC 60 Gallon</b>	0	0
5652890	S	<b>DEF Tank Mounted LH BOC</b> Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	O	<b>DEF To Fuel Ratio 2:1 Or Greater</b>	0	0
5655019	S	<b>DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal</b>	0	0
<b>Battery Box &amp; Bumper</b>				
6010030	S	<b>Aluminum Battery Box LH Under Cab, Non-Slip Step</b> Includes diamond pattern block shaped cover in traditional/vocational models and a smooth finish tapered cover on aerodynamic models	0	0
6040550	S	<b>Aftertreatment Aluminum Non-Slip Cab Entry</b> Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6121090	S	<b>Steel Bumper Deep Tapered Chromed</b> Two tow points	0	0
<b>Cab &amp; Equipment</b>				
6510140	S	<b>Alum Cab 123in BBC Alum Hood SFFA</b> fenders w/polished crown, spring tilt assist. Proprietary anti-blow-down locking mechanism that keeps hood open during servicing & prevents unintentional closing. Hood latch each side secures hood to cowl. Proprietary all-alum cab is light weight & durable for long service life. One-piece roof reduces potential for leaks. Two-piece windshield for cost effective windshield replacement. Lap seam construction & aircraft fasteners has greater clamp load than rivets. Bulkhead style doors provide virtually water-tight, rattle-free performance. Extruded alum door frames for strength & durability. Full length, heavy-duty piano-type	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 8:08:28 AM

Date: April 24, 2021

Quote Number: QUO-815237-M4P2P9



Sales Code	Std/ Opt	Description	\$ List	Weight
		stainless steel door hinges & pins provide durability. View window in RH door for safety. Electric windshield wipers & washers w/intermittent wiper function. Grab handles mtd on cab LH & RH for cab access. Convex mirror over RH door & below each rear view mirror for improved visibility & safety.		
6700000	S	<b>No Sleeper Selected</b>	0	0
6911170	S	<b>Sears Driver Seat</b> Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0	0
6921170	S	<b>Sears Passenger Seat</b> Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0	0
6939400	S	<b>Air Ride Driver</b>	0	0
6939420	S	<b>High Back Driver</b>	0	0
6939470	S	<b>Vinyl Driver</b>	0	0
6939510	S	<b>Non-Air Ride Passenger</b>	0	0
6939520	S	<b>High Back Passenger</b>	0	0
6939570	S	<b>Vinyl Passenger</b>	0	0
7000025	S	<b>Steering Wheel With Multi-Function</b> Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	0	0
7000350	S	<b>Power Door Locks Both Doors</b>	0	0
7001520	S	<b>Adjustable Steering Column - Tilt/Telescope</b>	0	0
7039050	S	<b>ProBilt Interior - Arctic Gray</b> Includes rugged charcoal instrument panels, gray dash with glare-resistant, charcoal soft-touch upper, dark gray hard trim, black bezels on gauges, cigar lighter and ashtray with power port, monochromatic dark gray durable doorpads with map pocket on driver's side, dark gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted domelight, driver and passenger dome/reading lights, footwell lighting, integrated "dead pedal", (5) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, cup holder and map bin in dash.	0	0
7210540	S	<b>Day Cab Rear Window</b> Day cab rear window flush to back of cab.	0	0
7230060	S	<b>1-Piece Curved Windshield</b>	0	0
7230680	S	<b>Power Lift Windows - Both Doors</b> For use with ProBilt or Prestige Interior	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 8:08:28 AM

Date: April 24, 2021

Quote Number: QUO-815237-M4P2P9



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7330700	S	<b>Peterbilt Comfort Control - Cab</b>	0	0
7510010	S	<b>Stainless Steel Mirrors 7 x 16</b>	0	0
7560850	S	<b>(2) Convex 8 Inch SSTL Mirrors</b> Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	0	0
7610470	S	<b>(1) Air Horn 24.5" Chrome - Round w/Horn Shield</b>	0	0
7725720	S	<b>No Head Unit or Audio Speakers Selected</b>	0	0
7788055	S	<b>SmartLINQ Remote Diagnostics</b> SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.	0	0
7788056	S	<b>24 Months SmartLINQ Subscription With OTA</b> Functionality - PACCAR MX Engines	0	0
7851480	S	<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0	0
8011830	S	<b>Engine Oil Temperature</b> Located in Digital Cluster Display.	0	0
8021380	S	<b>Air Restriction Indicator</b> Mounted on air cleaner, intake piping, or firewall	0	0
8021810	S	<b>Brake Application Air Pressure (Tractor)</b> Located in Digital Cluster Display.	0	0
8070810	S	<b>Engine Manifold Pressure (Turbo Boost)</b> Located in Digital Cluster Display	0	0
8070820	S	<b>Engine Percent Torque</b> Located in Digital Cluster Display	0	0
8070830	O	<b>Main Instrumentation Panel</b> Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, OAT and Voltmeter.	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 8:08:28 AM

Date: April 24, 2021

Quote Number: QUO-815237-M4P2P9



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
8111140	S	<b>Headlights Projector Module Pod</b> Integral Turn Signals	0	0
8120980	S	<b>(5) Marker Lights, Aero LED</b>	0	0
8140000	S	<b>Incandescent Oval Stop/Turn/Tail/Backup</b> In tractor taper end of frame crossmember	0	0

#### **Paint**

8500710	O	<b>Standard Paint Color Selection</b>	-200	0
8530770	S	<b>(1) Color Axalta Two Stage - Cab/Hood</b> Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE N85720 SK FAIRINGS L0006EY WHITE	0	0

#### **Shipping Destination**

#### **Options Not Subject To Discount**

9400090	S	<b>Peterbilt Class 8 Standard Coverage</b> 1 year/100,000 Miles (160,000 km)	0	0
9400092	S	<b>PACCAR MX Standard Coverage</b> 2 yrs/250,000 mi (400,000 km)/6,250 hrs	0	0
9408730	S	<b>2021 Peterbilt HD Delivery</b>	1,000	0

#### **Miscellaneous**

9409000	S	<b>Day Cab / ProBilt Interior (DB)</b>	0	0
9409831	S	<b>2021 EPA Emissions Engine</b> Warranty Only	0	0

#### **Promotions**

#### **Order Comments**

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 8:08:28 AM

Date: April 24, 2021

Quote Number: QUO-815237-M4P2P9



Total List Price (W/O Freight & Warranty & Surcharges )	\$192,145
Marketing and Service Support Fee	\$875
Prepaid Freight	\$2,475
Total Surcharge/Options Not Subject To Discount	\$1,000
Total Weight	14,967

## Prices and Specifications Subject to Change Without Notice.

---

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### **PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*