



TLG Peterbilt - Greensboro (P641)
7061 Albert Pick Road
Greensboro, North Carolina 27409

North Carolina Sheriff
323 West Jones Street Suite 505
Raleigh, North Carolina 27603
United States of America

Howie Dingess
Cell Phone: 336-669-4408
Office Phone: 336-668-3050
Email: hdingess@piedmontpeterbilt.com

Vehicle Summary

Unit		Chassis	
Model:	Model 567	Fr Axle Load (lbs):	12000
Type:	Full Truck	Rr Axle Load (lbs):	45400
Description 1:		G.C.W. (lbs):	57400
Description 2:			
Application		Road Conditions:	
Intended Serv.:	Refuse/On-Highway	Class A (Highway)	100
Commodity:	Refuse, Scrap, Recycling	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body			
Type:	Roll-Off	Maximum Grade:	6
Length (ft):	20	Wheelbase (in):	256
Height (ft):	7	Overhang (in):	60
Max Laden Weight (lbs):	5000	Fr Axle to BOC (in):	68.2
		Cab to Axle (in):	187.8
		Cab to EOF (in):	247.8
Trailer		Overall Comb. Length (in):	363.23
No. of Trailer Axles:	0		
Type:			
Length (ft):	0		
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions		Special Req.	
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0005671	S	Model 567 The Model 567 is available in both a set-forward and set-back front axle configuration to provide customers with maximum versatility for their application requirements. For weight-sensitive applications, the set-forward front axle provides optimized weight distribution and compliance with bridge laws. The Model 567 has steer axle ratings up to 22,000 lbs. The 567 also offers single, tandem or tridem drive axles and a variety of lift axles for added versatility. Available with a 115" or 121" BBC and as a day cab or with a selection of detachable sleeper configurations, the 567 is as versatile as it is reliable.	181,402	14,860
0091180	O	Refuse, Scrap, Recycling	0	0
0093035	O	Refuse/On-Highway Truck or tractor which hauls refuse, recycled material, etc. Includes roll-on/roll-off container movement, as well as hauling refuse from transfer stations to, but not into, landfills.	0	0
0095090	O	Roll-Off A rectangular open top dumpster which utilizes wheels and a hydraulically operated bed to roll the dumpster off the truck body onto the ground. Commonly used to transport construction, demolition waste, and other waste types.	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514000	O	10-3/4" Steel Rails To 354" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	366	459
0601500	O	Full Steel Inner Liner	1,367	731
0611790	S	Aluminum Frame Rail Crossmembers Excludes suspension	0	0
0644090	O	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	62	-64
0651010	S	Peterbilt Rear Mudflaps and Straight Hangers Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	0	0
Front Axle & Equipment				

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:58:18 AM

Date: April 24, 2021

Quote Number: QUO-814600-T9L1P4



Sales Code	Std/ Opt	Description	\$ List	Weight
1012140	S	Meritor MFS+12E 12,500 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 13,000 pounds. Axles include special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service.	0	0
1111190	S	Taper Leaf Springs, Shocks 12,000 lb Hendrickson taper leaf springs, shocks for 12,000 lbs.	0	0
1243040	S	Power Steering Sheppard HD94 Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 10,000 to 13,200 lb. axle ratings.	0	0
1250180	S	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1353550	S	PHP10 Aluminum PreSet PLUS Hubs Air Disc PHP10 aluminum PreSet PLUS hubs air disc have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug, with a seal and bearings. Use with Front Axle.	0	0
1380290	S	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
1380380	S	Tenneco Shocks For Steer Axle Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0	0
1390630		80mm Front Spring Spacer Blocks	0	0
Rear Axle & Equipment				
1523440	O	Dana Spicer D46-172 46,000 LBS Dana Spicer D46-172 46,000 lbs tandem drive axles offer efficiency improvement, axle weight reduction and reduced lube quantity.	1,900	521
1616290	S	PHP10 Aluminum PreSet PLUS Hubs	0	0
1680440	O	Refuse Service Brakes, Steer And Drive Axles Designed for heavy-duty applications for refuse industry, providing long brake life, safety and performance.	330	0
1680450	O	Rear Brake Camshaft Reinforcement Rear brake camshaft reinforcement helps guard against wear and corrosion.	124	9
1680500	O	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	261	0
1680950	O	Stability System Not Selected Or Not Available	-99	0
1682710	S	Anti-Lock Braking System (ABS) 6S6M ABS-6. Includes air braking system.	0	0
1684200	S	Synthetic Axle Lubricant All Axles	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:58:18 AM

Date: April 24, 2021

Quote Number: QUO-814600-T9L1P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.		
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1704300	O	Ratio 4.30 Rear Axle	0	0
1824410	O	Hendrickson HMX EX 460 46,000 LBS., 54" Haulmaax, 70K Creep Rating. Includes Traax Rod as standard, option 1920905 is not needed or available. Progressive load spring system easily adjusts to the load for an enhanced combination of empty-ride quality and loaded stability.	2,676	223

Engine & Equipment

2072728	O	PACCAR MX-11 430@1600 GV@2200 1650@900 (2021 Emissions)	0	-288
		N20700 AA003 64....CC MAX TARGET SPEED N20800 AA004 10....CC MIN ENABLE SPEED N22000 AA005 OFF...DYNAMIC CC ENABLE N20830 AA006 MT....MULTI TORQUE IN CC N21930 AA009 0.....DRIVER REWARD VEH SPD BONUS N21940 AA010 -5....DRIVER REWARD VEH SPD PNLTY N21920 AA013 BOTH..OFFSET MODE N21950 AA015 3.....MIN SPEED FOR DR SHIFT AID N21960 AA016 1.....DSA LOWEST ACTV GEAR N21970 AA017 10....DSA HIGHEST ACTV GEAR N21640 AA019 YES...EIST PARK BRAKE RESET ENABLE N21910 AA022 30....EIST LO CLNT TEMP OVRDE N20870 AA023 80....EIST HI AMBAIR TEMP OVRDE N20860 AA024 39....EIST LO AMBAIR TEMP OVRDE N20900 AA025 5.....EIST PTO MAX IDLE TIME N20840 AA026 5.....EIST PARKED MAX IDLE TIME N20850 AA027 5.....EIST STANDSTILL IDLE TIME N20910 AA029 YES...EIST RESET FROM ENG LOAD N21170 AA030 NO....EIST OVERRIDE FROM ENG LOAD N21190 AA031 0.....EIST EXPIRATION DISTANCE N21230 AA032 YES...EIST ACCEL PEDAL RESET N21240 AA033 YES...EIST SERVICE BRK RESET N21250 AA034 YES...EIST CLUTCH PEDAL RESET N21260 AA035 YES...EIST PTO OVERRIDE N20770 AA037 4.....DSL SPD OFFSET N20760 AA038 2.....AUTO RTRDR VEH SPD OFFSET N20750 AA039 0.1...TIME DELAY FOR RTRDR ACT N20940 AA042 1900..FIC MAX ENG SPEED		

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:58:18 AM

Date: April 24, 2021

Quote Number: QUO-814600-T9L1P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		N22080 AA043 CNCL..CAB/REM: CUSTOM PRESET 1 FUN		
		N22090 AA044 750...CAB/REM: CUSTOM PRESET 1		
		N22100 AA045 CNCL..CAB/REM: CUSTOM PRESET 2 FUN		
		N22110 AA046 850...CAB/REM: CUSTOM PRESET 2		
		N22120 AA047 CNCL..CAB/REM: CUSTOM PRESET 3 FUN		
		N22130 AA048 950...CAB/REM: CUSTOM PRESET 3		
		N22010 AA049 CNCL..CAB: CUSTOM PRESET 1 FUNC		
		N22020 AA050 0.....CAB: CUSTOM PRESET 1		
		N22030 AA051 CNCL..CAB: CUSTOM PRESET 2 FUNC		
		N22040 AA052 0.....CAB: CUSTOM PRESET 2		
		N22050 AA053 CNCL..CAB: CUSTOM PRESET 3 FUNC		
		N22060 AA054 0.....CAB: CUSTOM PRESET 3		
		N20990 AA055 ON A..CAB: CLUTCH INTLK		
		N21010 AA058 ON A..CAB: PARK BRK INTLK		
		N21030 AA057 ON A..CAB: NEUTRAL INTLK		
		N21150 AA059 ON A..SER BRK INTLK: NO PTO		
		N21130 AA060 OFF...CAB: PRESET +/- SWITCH TYPE		
		N21180 AA061 2000..CAB: MAX ENG SPD- ACCEL CTRL		
		N21120 AA062 2000..CAB: MAX ENG SPD- SW CTRL		
		N21020 AA063 6.....CAB:MAX VEH SPEED		
		N21200 AA064 650...CAB: MIN ENG SPD		
		N21220 AA065 800...CAB: DEDICATED PRESET (-)		
		N21270 AA066 900...CAB: DEDICATED PRESET (+)		
		N21900 AA067 TRQ...CAB: ACCEL PEDAL TYPE IN PTO		
		N21140 AA068 YES...CAB: ACCEL ACTV IN CAB PTO		
		N21990 AA069 YES...PTO REM PEDAL ENABLE		
		N21600 AA070 ON AD.REM: CLUTCH INTLK		
		N22140 AA071 OFF...REM: CUSTOM INTLK		
		N21700 AA072 ON AD.REM: NEUTRAL INTLK		
		N21710 AA073 ON AD.REM: SER BRK INTLK: NO PTO		
		N21980 AA074 2000..REM:MAX ENG SPD-ACCEL CTRL		
		N21110 AA075 2000..REM: MAX ENG SPD-SW/ TSC1 CT		
		N21320 AA076 650...REM: MIN ENG SPD		
		N21290 AA077 800...REM: DEDICATED PRESET (-)		
		N21490 AA078 900...REM: DEDICATED PRESET (+)		
		N21580 AA079 DEDIC.REM: PRESET +/- SWITCH TYPE		
		N20690 AA086 64....MAX ACCEL PEDAL VEH SPD		
		N21300 AA087 0.....VSL EXPIRATION DISTANCE		
		N21310 AA088 155...LRSL SPD LMT		
		N20740 AE001 NO....ENBL MX RETARDER IN NEUTRAL		
		N20710 AE002 600...IDLE TARGET		
		N20930 AE003 ON....FIC ENABLE/DISABLE		
		N22070 AA056 OFF...CAB: CUSTOM INTLK		
2091130	S	VMUX Electronics Architecture	0	0
2091305	S	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Overrule	0	0
2091372		Eff EIST NA Expiration Miles	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:58:18 AM

Date: April 24, 2021

Quote Number: QUO-814600-T9L1P4



Sales Code	Std/ Opt	Description	\$ List	Weight
2091640		Effective VSL Setting NA	0	0
2092013	O	Typical Operating Speed 60 MPH	0	0
2092027	O	MX Retarder State Cruise Control On (Manual Mode Engine Parameter)	0	0
2092032	O	Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0	0
2092065	O	PTO Mode Control - CAB Station	0	0
2092079	O	Decline Driver Performance Assistant	0	0
2092082	S	Engine Monitoring Protection - Derate (PACCAR MX) A warning is provided in the A-Panel display when DPF regeneration is required. Continued operation without regeneration will initiate automate derating of the engine's power and can result in damage to the engine.	0	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140410	S	Engine Brake Controls Located on RH Column	0	0
2140450	O	Remote PTO/Throttle, 12-Pin Eng Bay Remote Control Provision	31	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	S	Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522080	S	PACCAR Premium Starter - MX Engines Only PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 5-yr/500K miles.	0	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539720	S	Low Voltage Disconnect System	0	0
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	312	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:58:18 AM

Date: April 24, 2021

Quote Number: QUO-814600-T9L1P4



Sales Code	Std/ Opt	Description	\$ List	Weight
2738410	S	WABCO 25.9 CFM Air Compressor, MX only WABCO 25.9 CFM air compressor, MX only, provides greater air output aiding in cleaner operation, higher efficiency, and durability.	0	0
2811160	S	Compression Brake, MX The Mx brake features a Jacobs Brake with an integrated compression-release brake and engine overhead. the specially designed exhaust came lobe provides both exhaust cam motion and deicated Compression release timing. This results in precise timing of the valve opening, unleashing higher retarding performance with minimum loading on the engine.	0	0
2921180	S	PACCAR Fuel/Water Separator On Engine Optimized for MX engines and Includes fuel heat, 12V electric heat and WIF sensor.	0	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0	0
3291680	S	(1) Air Cleaner Firewall Mounted Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365270	S	Exhaust Single RH Side of Cab DPF/SCR right-hand Under Cab.	0	0
3387870	S	24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	0	0
Transmission & Equipment				
4020050	S	Eaton FAO16810C 10-Speed OD, Advantage Series Manual transmission with aluminum housing, no cooler	0	0
4210190	O	1810 HD Driveline, 1 Midship Bearing 4.5in x .180 wall tubing	613	90
4216590	O	1710 Driveline Interaxle For tandem rear axles	288	0
4256100	S	Manual Shifter, Black	0	0
Air & Trailer Equipment				
4510210	O	Bendix AD-HF EP Air Dryer, Heater Coalescing filter, extended purge. Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technonlgy in the the air dryer catridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	142	-2
4540260	O	Wrecker AE Connection EOF On Moveable Crossmember	307	17

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:58:18 AM

Date: April 24, 2021

Quote Number: QUO-814600-T9L1P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		Dash mounted air toggle valve plumbed to service brakes, 7-way socket (occupies the space of one gauge), winch brake switch on dash		
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4610920	S	Self-Returning Brake Hand Valve Dash mounted controls	0	0
Tires & Wheels				
5066100	S	FF: BR 14ply 295/75R22.5 R213 Ecopia	0	0
5166100	S	RR: BR 14ply 295/75R22.5 R213 Ecopia	0	0
5190008	S	Code-rear Tire Qty 08	0	0
5211990	S	FF: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP10-2 hand holes	0	0
5311990	S	RR: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP10-2 hand holes	0	0
5390008	S	Code-rear Rim Qty 08	0	0
Fuel Tanks				
5556130	O	26" Aluminum 80 Gallon Fuel Tank LH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	215	5
5604080	O	Location LH BOC 80 Gallon	0	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	O	DEF To Fuel Ratio 2:1 Or Greater	0	0
5655019	S	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0	0
5760010	O	RH Tank None Furnished	-540	-86
Battery Box & Bumper				
6010030	S	Aluminum Battery Box LH Under Cab, Non-Slip Step	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:58:18 AM

Date: April 24, 2021

Quote Number: QUO-814600-T9L1P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		Includes diamond pattern block shaped cover in traditional/vocational models and a smooth finish tapered cover on aerodynamic models		
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6111010	S	Aluminum Bumper Swept Back Polished Without FEPTO SBFA, two tow pins and step plates on top of bumper	0	0
Cab & Equipment				
6515690	S	Vocational 115" BBC Alum Cab and Metton Hood SBFA Stainless crown and grille with tilt assist.	0	0
6700000	S	No Sleeper Selected	0	0
6911100	S	Peterbilt ST Driver Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal carog/luggage. Standard vinyl finish - color coordinate with interior color.	0	0
6921740	S	Peterbilt ST Non-Adjustable Passenger Seat Standard vinyl, no suspension cover, no seat back recline.	0	0
6939140	S	Tube frame under Passenger Seat Only available with Peterbilt ST non-adjustable passenger seat.	0	0
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0
6939520	S	High Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0
7000025	S	Steering Wheel With Multi-Function Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	0	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7037130	S	Prestige Interior - Sterling Gray	0	0
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	0
7210550	S	1-Piece Glass Rear Cab Window Fixed	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:58:18 AM

Date: April 24, 2021

Quote Number: QUO-814600-T9L1P4



Sales Code	Std/ Opt	Description	\$ List	Weight
7230060	S	1-Piece Curved Windshield	0	0
7230360	S	Power Door Locks and Power Window Lifts Standard	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7510070	S	Aero Rear View Mirror Housing, Molded Black	0	0
7514000	S	Peterbilt Aero Rear View Mirror, Non-Motorized Includes top mirror with non-motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	0	0
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0	0
7610500	S	Air Horn Mounted Under Cab	0	0
7725720	S	No Head Unit or Audio Speakers Selected	0	0
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.	0	0
7788056	S	24 Months SmartLINQ Subscription With OTA Functionality - PACCAR MX Engines	0	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7852060	S	Solid Rear Day Cab Mounts	0	0
8011830	S	Engine Oil Temperature Located in Digital Cluster Display.	0	0
8021800	S	Air Filter Restriction Pressure Gauge Located in Digital Cluster Display	0	0
8021810	S	Brake Application Air Pressure (Tractor) Located in Digital Cluster Display.	0	0

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:58:18 AM

Date: April 24, 2021

Quote Number: QUO-814600-T9L1P4



Sales Code	Std/ Opt	Description	\$ List	Weight
8070810	S	Engine Manifold Pressure (Turbo Boost) Located in Digital Cluster Display	0	0
8070820	S	Engine Percent Torque Located in Digital Cluster Display	0	0
8070830	O	Main Instrumentation Panel Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, OAT and Voltmeter.	0	0
8110070	S	Headlights Projector Module Pod Fender mounted turn signals, projector module low beam, complex reflector high beam, pod mounted	0	0
8120990	S	(5) Marker Lights, Aero LED On roof, visor, or fairing	0	0
8133960	S	Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0	0
8140120	O	Incandescent Square Stop/Turn/Tail/Backup Left-hand / right-hand square end of frame or dropped a-brace	50	9
8140650	S	Peterbilt Signature Door Light Turn Signal	0	0
Paint				
8500710	S	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0
Shipping Destination				
Options Not Subject To Discount				
9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
9400092	S	PACCAR MX Standard Coverage 2 yrs/250,000 mi (400,000 km)/6,250 hrs	0	0
9408730	S	2021 Peterbilt HD Delivery	1,000	0
Miscellaneous				
9409001	S	Day Cab / Prestige Interior (DM)	0	0
9409831	S	2021 EPA Emissions Engine Warranty Only	0	0
Promotions				

Price Level: April 1, 2021

Deal:

Printed On: 4/24/2021 7:58:18 AM

Date: April 24, 2021

Quote Number: QUO-814600-T9L1P4



<i>Sales Code</i>	<i>Std/ Opt</i>	<i>Description</i>	<i>\$ List</i>	<i>Weight</i>
-----------------------	---------------------	--------------------	----------------	---------------

Order Comments



Total List Price (W/O Freight & Warranty & Surcharges)	\$189,607
Marketing and Service Support Fee	\$875
Prepaid Freight	\$2,475
Total Surcharge/Options Not Subject To Discount	\$1,000
Total Weight	16,484

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information