

ZT6000



Bobcat®

One Tough Animal

**BUILT TO
WORK**

BRING TOUGH TO TURF

VERSATILITY AND DEPENDABILITY DEFINED

The ZT6000 will satisfy the toughest customers and give your crew something to fight over.



ZT6000

MODEL NUMBER	9996010	9996011
ENGINE		
Model	Kaw FX801V	
Displacement	52.0 cu. in. (852 cc)	
Fuel Capacity	15 gal. (56.7 L)	
Air Filter	Canister Air Filter	
ELECTRICAL		
Charging System	15 amp	
Clutch	225 lbf. (1000 N)	
DECK		
Mower Deck	AirFX™ Cutting System	
Leading Edge	Adjustable, Front Lip Standard	
Width	52 in. (1320 mm)	61 in. (1541 mm)
Adjustable Anti-Scalp Rollers	6	
Cutting Height	1.0-5.5 in. (25-139 mm)	
Blade Tip Speed	18,586 fpm @ 3550 Engine rpm	18,500 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer	
FRAME		
Front & Rear	Welded, 0.25 in., 7-gauge Steel; 1.5 x 2.5 in. Steel Tubing	
Machine Length	83.0 in. (2108 mm)	
Machine Weight	1371 wet lb.	1421 wet lb.
TRANSMISSION		
Type	HG ZT-4400 Hydrostatic Transaxles	
Pump Displacement	0.7 cu. in. (12 cc)	
Oil Capacity	1.1 gal. (4.5 qt.) each	
Forward Speed	0-12.0 mph (0-19.3 km/hr.)	
Reverse Speed (mph)	0-4.0 mph (0-6.4 km/hr.)	
WHEELS		
Drive Wheel Size	24 x 10.5-12	
Front Caster Wheel Size	13 x 6.5-6	
Caster Arm Attachment	Bolt-On	
SEAT		
Description	High-Back, Full-Mechanical Suspension Seat	
Fore-Aft Adjustment	Seat Slide Lever	

**2000
HOURS**

**BUMPER TO BUMPER
WARRANTY**

BOBCAT.COM



YOU ARE ONE TOUGH ANIMAL.®

Everything we put into Bobcat equipment is designed to make more of whatever you bring to the job. Whether it's strength, versatility, speed or agility, it's built around you.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Where applicable, dimensions are in accordance with ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for mini track loaders. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.

Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2021 Bobcat Company. All rights reserved.



Printed on 10% recycled paper

B-2001 (02/21)

Bobcat Company
250 East Beaton Drive • West Fargo, ND 58078

Bobcat.com



Bobcat®

One Tough Animal.