## **GEAR-DRIVE WALK-BEHIND**



MODEL NUMBER	932007	933007	934007
ENGINE			
Model	Kaw FS481V	Kaw FS481V	Kaw FS481V
Displacement (cc)	603	603	603
Lubrication	Full-Pressure–Spin-On Oil Filter		
Fuel Capacity (gal)	5	5	5
Air Filter	Dual Element		
ELECTRICAL			
Charging System (amp)	15	15	15
Clutch (ft lb)	125	125	125
DECK			
Mower Deck	DuraDeck™ Cutting System		
Leading Edge	Fabricated, 7-gauge Deck Top Plus 7-gauge Reinforcements and Skirts		
Width (in)	32	36	48
Cutting Height (in)	1.5-4.5	1.5-4.5	1.5-4.5
Blade Tip Speed	17886 fpm @ 3600 Engine rpm	18784 fpm @ 3600 Engine rpm	17886 fpm @ 3600 Engine rpm
Spindle Type	Maintenance-Free with 1-inch Shaft		
Spindle Bearing	Double-Sealed, Precision-Ground Ball Bearings		
Discharge Chute	Flexible Molded Polymer		
FRAME			
Machine Length (in)	78	78	78
Machine Weight—Wet (lb)	400	428	476
TRANSMISSION			
Туре	Pearless 5-Speed with Rev Assist		
Forward Speed (mph)	0-5.1	0-5.1	0-5.1
WHEELS			
Drive Wheel Size	13 x 5.0-6, 4-ply	13 x 5.0-6, 4-ply	13 x 5.0-6, 4-ply
Front Caster Wheel Size	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat
WARRANTY	3-year / 2,500 hour MOW WITH CONFIDENCE™ limited warranty		

Parts & Accessories: Mulching Baffle Kit – Eliminator Blades, Eco Plate, Grass Catcher: Poly-Dump—3.75 or 5.0 bushel, Grass Catcher – Metal, Jumbo, Easy-Dump 4.3 cu ft, Weight Kit (36", 48", 52"), Hydro Cold-Start Kit

