

HYDRO-DRIVE WALK-BEHIND



				ELECTRIC START	Z-CONTROL	Z-CONTROL
MODEL NUMBER	933305	934306	935308	934307	934331	934332
ENGINE						
Model	Kaw FS481V	Kaw FS541V	Kaw FS600V	Kaw FS541V	Kaw FS541V	Kaw FS541V
Lubrication	Full-Pressure—Spin-On Oil Filter					
Displacement (cc)	603	603	603	603	603	603
Fuel Capacity (gal)	5	5	5	5	5	5
Air Filter	Dual Element					
ELECTRICAL						
Charging System (amp)	15	15	15	15	15	15
Clutch (ft lb)	125	125	125	125	125	125
DECK						
Mower Deck	DuraDeck™ Cutting System					
Leading Edge	Fabricated, 7-gauge Deck Top Plus 7-gauge Reinforcements and Skirts					
Width (in)	36	48	52	48	36	48
Cutting Height (in)	1.38–4.63	1.38–4.63	1.38–4.63	1.38–4.63	1.38–4.63	1.38–4.63
Blade Tip Speed	16964 fpm @ 3600 Engine rpm	15315 fpm @ 3600 Engine rpm	16964 fpm @ 3600 Engine rpm	15315 fpm @ 3600 Engine rpm	16964 fpm @ 3600 Engine rpm	15315 fpm @ 3600 Engine rpm
Spindle Type	Maintenance-Free with 1-inch Shaft					
Spindle Bearing	Double-Sealed, Precision-Ground Ball Bearings					
Discharge Chute	Flexible Molded Polymer					
FRAME						
Machine Length (in)	78	78	78	78	78	78
Machine Weight—Wet (lb)	528	582	593	582	488	528
TRANSMISSION						
Type	HG Variable Displacement Pumps					
Forward Speed (mph)	0–6	0–6	0–6	0–6	0–6	0–6
WHEELS						
Drive Wheel Size	16 x 7.5–8, 4-ply	16 x 7.5–8, 4-ply	16 x 7.5–8, 4-ply	16 x 7.5–8, 4-ply	16 x 7.5–8, 4-ply	16 x 7.5–8, 4-ply
Front Caster Wheel Size	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat
WARRANTY	3-year / 2,500 hour MOW WITH CONFIDENCE™ limited warranty					

Parts & Accessories: Eliminator Blades, Eco Plate, Grass Catcher – Poly-Dump—3.75 or 5.0 bushel, Grass Catcher – Metal, Jumbo, Easy-Dump 4.3 cu ft, Weight Kit (36", 48", 52"), Hydro Cold-Start Kit



FIERCELY INDEPENDENT.

BOBCATTURF.COM