

COMMERCIAL-GRADE DURABILITY AND

Convenient maintenance and all-day mowing comfort

Description

Fore-Aft Adjustment



make the ZT3500 the perfect	machine for anyone		
ready to take on the toughest	turf.		
MODEL NUMBER	9993501	9993502	9993503
ENGINE	333301	333302	2222 202
Model	Kaw FX651V	Kaw FX691V	Kaw FX730V
Displacement	NAW I AGGIV	44.3 cu. in. (726 cc)	NAW 1 X7 00 V
Fuel Capacity	7.8 gal. (29.5 L)		
Air Filter	Dual-Stage Canister		
ELECTRICAL		,	
Charging System		15 amp	
Clutch	125 lbf. (556 N)		
DECK			
Mower Deck	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts		
Width	48.0 in. (1219 mm)	52.0 in. (1320 mm)	61.0 in. (1549 mm)
Adjustable Anti-Scalp Rollers	3	3	7
Cutting Height		1.5-4.8 in. (38-121 mm)	
Blade Tip Speed	17,365 fpm @ 3550 Engine rpm	18,142 fpm @ 3550 Engine rpm	18,809 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer		
FRAME			
Front & Rear	Welded 7-gauge Steel; 1.5- x 2.5-inch Steel Tubing		
Machine Length	76.0 in. (1930 mm)		79.0 in. (2006 mm)
Machine Weight	773 wet lb.	789 wet lb.	832 wet lb.
TRANSMISSION			
Туре	HG ZT-3400 Hydrostatic Transaxles		
Pump Displacement	0.7 cu. in. (12 cc)		
Oil Capacity	1.0 gal. (4 qt)		
Forward Speed	0-10.0 mph (0-16.0 km/hr.)		
Reverse Speed (mph)	0-3.5 mph (0-5.6 km/hr.)		
WHEELS			
Drive Wheel Size	23 x 10.5-12		
Front Caster Wheel Size	13 x 6.5-6		
Caster Arm Attachment	Welded to Frame		
SEAT			



High-Back, Full-Mechanical Suspension Seat

Seat Slide Lever



Everything we put into Bobcat equipment is designed to make more of whatever you bring to the job. Whether it's strength, versatility, speed or agility, it's built around you.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Where applicable, dimensions are in accordance with ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for mini track loaders. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.

Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2021 Bobcat Company. All rights reserved.



