



RedMax heavy-duty, commercial trimmers and brush cutters can clear, trim or edge with ease. Solid-steel drive shafts reduce vibration and improve acceleration. Low-friction and smooth-running, they're comfortable to use and deliver trouble-free operation with little maintenance.



# TRIMMERS

Specifications	TRZ230S	BCZ230TS	BCZ250S	BCZ260S	BCZ260TS	BCZ3050S	BCZ3060TS
Displacement (cc)	22.5	22.5	25.4	25.4	25.4	29.5	29.5
Power Output (hp)	1	1	1.2	1.3	1.3	1.4	1.4
Dry Weight (lbs)	10.1	10.1	11	10.8	10.8	12.3	12.3
Drive Shaft	Solid Steel	Solid Steel	Solid Steel	Solid Steel	Solid Steel	Solid Steel	Hollow Steel with Damper
Usage	Light Duty	Max Torque Professional	Professional	Heavy Duty	Max Torque Professional	Heavy Duty	Max Torque Professional
Warranty	2 Years	2 Years	2 Years	2 Years	2 Years	2 Years	2 Years

# BRUSHCUTTERS

Specifications	BCZ3050SW	BCZ350S
Displacement (cc)	29.5	34.6
Power Output (hp)	1.4	2.15
Dry Weight (lbs)	13	13
Drive Shaft	Solid Steel	Hollow Steel
Usage	Professional	Professional
Warranty	2 Years	2 Years



## MAXLINE™ ROUND

Diameter	SPOOL	SKU
.095"	280'	587 88 42-02
	840'	587 88 42-04
	1400'	587 88 42-06
.105"	230'	587 88 42-03
	690'	587 88 42-05
	1150'	587 88 42-07

## CUTTING HEADS



	MT104R	MT104	PT104 Plus	T45	PT100
SKU	537 33 83-12	537 33 83-10	511 01 06-01	596 29 79-01	515 51 61-01
Head Diameter	4"	4"	4"	5"	6"
Shaft Diameter	3/8"	M10	M10	M12	M10
Accepts Line Diameter	.065, .080, .095	.065, .080, .095	.095, .105	.095, .105, .130	.095

## MAXLINE™ TWIST

Diameter	SPOOL	SKU
.080"	320'	588 04 96-01
	1200'	588 04 96-05
.095"	855'	588 04 96-06
	1427'	588 04 96-09
.105"	185'	588 04 96-03
	690'	588 04 96-07
	1150'	588 04 96-10

## BRUSHCUTTER BLADES



**SGB089** | 9" dia. / 8-Tooth  
Part No.: 574 15 86-01

**SGB049** | 9" dia. / 4-Tooth  
Part No.: 574 15 84-01



**SST229** | 9" dia. / 22-Tooth  
Part No.: 574 15 93-01

**SST249** | 9" dia. / 24-Tooth  
Part No.: 574 15 94-01