

# Dynapac F1250CS

## Compact pavers



### Technical data



#### Masses

Paver weight (incl. standard screed)	15,400 lbs
--------------------------------------	------------



#### Dimensions

Basic width	3.9 ft
Working width, max.	11.5 ft
Working width, hydraulic extendable	7.9 ft
Working width, minimum (Cut Off Shoe)	1.64 ft
Front ramp angle	14°



#### Capacity

Paving thickness (max/min)	7.9 /-5.9 in
Theoretical placement capacity	300 t/h



#### Undercarriage

Crawler length	55.1 in
Crawler width	7.9 in
Final drive	Direct drive over transmissions



#### Propulsion

Paving speed	up to 90 ft/min
Transport speed	180.45 fpm



#### Operation stations

Control consoles	Slidable left/right
Platform	Extendable platform



#### Engine

Manufacturer/Model	Deutz TD2.9 L4
Emissions according to	EU Stage V /EPA Tier 4f
Rated power	55.4 kW (75 hp) @2200 rpm
Electrical system	2 x 24V, 72 Ah
Fuel tank capacity	22 gal



#### Engine

Manufacturer/Model	Deutz TD2.9 L4
Emissions according to	EU Stage III /EPA Tier 3
Rated power	54 kW (73hp) @2200 rpm
Electrical system	2 x 24V, 72 Ah
Fuel tank capacity	22 gal



#### Material hopper

Capacity	2.5 m³ (5.5 t)
Dumping height, center	22 in
Hopper width, internal	111 in



#### Conveyor

Conveyor type	Split drive conveyor with center cover
Conveyor width	24.4 in
Conveyor control	Automatic with limit switches



#### Auger

Auger diameter	12.6 in
Auger control	Automatic with ultrasonic sensor
Auger height adjustment	Infinitely variable by 6 in

Find us locally at [www.dynapac.us](http://www.dynapac.us)

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.



dynapac\_f1250cs\_us-20210303.080342.pdf 2021-03-03 08:03

# Dynapac F1250CS

## Compact pavers



### Technical data



#### Dimensions

A. Axle track	55.1 in
B1. Width, max.	111.0 in
B2. Width, standard	56.3 in
B3. Width, center of tracks	37.0 in
C1. Track width	7.9 in
H2. Height, transport	79.5 in
L1. Length, total	187.4 in
L2. Length, transport	175.2 in
L3. Length, hopper	64.5 in



#### Standard equipment

2 front & 2 rear lights, Conventional electrics, , Dashboard with display and toggle switches, Eco Mode, Extendable steps operator platform, Hopper hydraulic separate control, Auger height adjustm., Conveyor reversible (splitted)with limit switches, Ultrasonic sensors auger



#### Optional equipment

Back-up alarm, Reduction shoes (0.5 working width), Working widths (3.1m + 3.5m), Emulsion spray equipment with pump and hose dispenser, Fire extinguisher, First aid kit, 4x LED lights, Light for auger compartment, Bio degradable hydraulic oil, Remote steering device, Rotating flashing beacon, Heatable side shields, Special painting,

Find us locally at [www.dynapac.us](http://www.dynapac.us)

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines.  
The above information is a general description only, all informations are supplied without liability.

dynapac\_f1250cs\_us-20210303.080342.pdf 2021-03-03 08:03